



STATE OF HAWAII  
DEPARTMENT OF HAWAIIAN HOME LANDS  
91-5420 Kapolei Parkway,  
Kapolei, HI. 96707

# **PLANS**

FOR  
FURNISHING LABOR AND MATERIALS FOR

## **LAIOPUA VILLAGE 4 SUBDIVISION, PHASE 2 - HEMA**


Kailua-Kona, North Kona, Island of Hawaii, Hawaii

T.M.K. (3) 7-4-21:12 (portion)

IFB No.: IFB-21-HHL-007

November 2020





STREET & UTILITY PLANS FOR

# LA'TOPUA VILLAGE 4 SUBDIVISION

## PHASE 2 - HEMA


KAILUA-KONA, NORTH KONA, HAWAII

OWNER / DEVELOPER: DEPARTMENT OF HAWAIIAN HOME LANDS

HALE KALANIANA'OLE  
95-5420 KAPOLEI PARKWAY  
KAPOLEI, HAWAII 96707

TAX MAP KEY : (3) 7-4-21:12 (PORTION)  
SUBDIVISION APPLICATION NO: SUB-05-000170  
DPW FOLDER: 74139-A

PREPARED BY:  
AKINAKA & ASSOCIATES, LTD.  
1100 ALAKEA STREET, SUITE 1800  
HONOLULU, HAWAII 96813



APPROVED BY:

CHAIRMAN, HAWAIIAN HOMES COMMISSION  
STATE OF HAWAII

DIRECTOR, PLANNING DEPARTMENT  
COUNTY OF HAWAII

DIRECTOR, DEPARTMENT OF PUBLIC WORKS  
COUNTY OF HAWAII  
(PUD PERMIT 05-000003)

DIRECTOR, DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
COUNTY OF HAWAII (FOR SEWER)

MANAGER-CHIEF ENGINEER, DEPARTMENT OF WATER SUPPLY  
COUNTY OF HAWAII

DEPARTMENT OF HEALTH, STATE OF HAWAII

INDEX TO DRAWINGS

SHEET NO.	DESCRIPTION		
1	TITLE SHEET, ISLAND MAP, LOCATION MAP, INDEX TO DRAWINGS	27	KNUCKLE DETAIL
2-5	CONSTRUCTION NOTES	28-29	CURB RAMP DETAIL
6	ABBREVIATIONS	30	DRIVEWAY DETAILS
7	GENERAL LAYOUT PLAN	31-33	DRIVEWAY LAYOUT PLAN
8	UTILITY PLAN	34	SIGNING & STRIPING PLAN
9	EROSION & DUST CONTROL PLAN	35	CURB RAMP STRIPING DETAILS
10	EROSION & DUST CONTROL DETAILS	36-38	SIGHT DISTANCE DETAILS
11	TYPICAL LOT GRADING DETAILS	39	WATER DETAILS
12	TYPICAL SECTIONS	40	PRV DETAILS
13-15	GRADING PLANS	41-42	SEWER DETAILS
16-18	OHEMAKAI ST EXT (ROAD "B-1")	43	MISCELLANEOUS DETAILS
19-20	KOAI'A ST (ROAD "G-1")	44	GRADING SECTION KEY MAP
21-22	'ILIE'E PL (ROAD "H-1")	45-50	GRADING SECTIONS
23-24	KAWELU PL (ROAD "F")	S-1 TO S-6	STRUCTURAL PLANS
25	PUAKALA PL (ROAD "I")	E-1 TO E-12	ELECTRICAL PLANS
26	CURB RETURN GRADES		

G:\DHHL11-02 Laiohua Village  
4\ACAD\DHHL1102-Construction Notes 1.DWG

Last Save by: LRS  
Last Saved: 6/5/2019  
Plotted on: 3/9/2020

GENERAL NOTES

1.

ALL CONSTRUCTION SHALL BE PERFORMED IN ACCORDANCE WITH STANDARD DETAILS AND STANDARD SPECIFICATIONS OF THE DEPARTMENT OF PUBLIC WORKS, COUNTY OF HAWAII.
2.

THE CONTRACTOR SHALL VERIFY THE LOCATIONS OF ALL EXISTING VALVE BOXES, MANHOLE COVERS AND CENTERLINE MONUMENTS AND SHALL HAVE THEM RAISED TO MEET THE NEW PAVEMENT GRADE.
3.

EXISTING PAVEMENT SHALL BE BROOMED OFF AND SHALL RECEIVE A TACK COAT OF 0.15 GALLON PER SQUARE YARD OF EMULSIFIED ASPHALT (SS-1) BEFORE PLACING A.C. PAVEMENT. THE COST OF THE TACK COAT SHALL BE INCIDENTAL TO THE A.C. PAVEMENT.
4.

THE CONTRACTOR SHALL PAVE THE TOTAL WIDTH OF ROADWAY EACH DAY SO AS NOT TO LEAVE A LONGITUDINAL PAVEMENT DROP BETWEEN LANE PASSES OF THE PAVER. HOWEVER, AT THE DISCRETION OF THE ENGINEER, THE CONTRACTOR MAY CONSTRUCT A TRANSITION TAPER (1' WIDE) SO AS NOT TO LEAVE A VERTICAL FACE.
5.

THE CONTRACTOR SHALL PROVIDE A SMOOTH-RIDING CONNECTION TO EXISTING STREETS AND DRIVEWAYS AND AT THE BEGINNING AND ENDING OF THE PROJECT LIMITS AS DIRECTED BY THE ENGINEER.
6.

PAVEMENT STRIPING, INCLUDING CENTERLINE, CROSSWALK, STOP LINES, ETC. AND RAISED PAVEMENT MARKERS SHALL CONFORM TO THE COUNTY STANDARDS FOR PAVEMENT MARKINGS AND STRIPING NOTES OR AS MODIFIED BY THE DETAILS ON THESE PLANS.
7.

THE CONTRACTOR, AT HIS OWN EXPENSE, SHALL KEEP THE PROJECT AND SURROUNDING AREAS FREE FROM DUST NUISANCES. THE WORK SHALL BE IN CONFORMANCE WITH THE AIR POLLUTION CONTROL RULES OF THE STATE DEPARTMENT OF HEALTH, HAR 11-60.1, FUGITIVE DUST.
8.

THE CONTRACTOR SHALL PROVIDE AT LEAST ONE (1) LANE FOR TRAFFIC MOVEMENT AT ALL TIMES. TWO (2) LANES FOR TRAFFIC MOVEMENT SHALL BE PROVIDED BETWEEN THE HOURS OF 3:30 P.M. TO 8:00 A.M.
9.

THE CONTRACTOR, AT HIS OWN EXPENSE, SHALL COORDINATE THE REFERENCING OF THE CENTERLINE MONUMENTS TO BE RECONSTRUCTED BY A SURVEYOR LICENSED TO PRACTICE IN THE STATE OF HAWAII. AFTER PAVING, THE SURVEYOR SHALL LOCATE THE MONUMENTS, AND AFTER RECONSTRUCTION OF THE MONUMENTS, THE SURVEYOR SHALL PUNCH THE CENTERLINE LOCATION ON THE BRASS PINS. THE SURVEYOR SHALL SUBMIT WRITTEN CERTIFICATION OF THE INSTALLATION AND LOCATION OF THE CENTERLINE MONUMENTS TO THE ENGINEER.
10.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE DONE TO THE DWS EXISTING WATER SYSTEM.
11.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONFORMANCE WITH THE APPLICABLE PROVISIONS OF THE WATER QUALITY AND WATER POLLUTION CONTROL STANDARDS CONTAINED IN THE HAWAII ADMINISTRATIVE RULES, TITLE 11, CHAPTER 54, "WATER QUALITY STANDARDS" AND TITLE 11, CHAPTER 55, "WATER POLLUTION CONTROL". BEST MANAGEMENT PRACTICES SHALL BE EMPLOYED AT ALL TIMES DURING THE CONSTRUCTION PERIOD.
12.

THE GENERAL CONTRACTOR OF THE PROJECT SHALL BE RESPONSIBLE FOR CONFORMANCE WITH THE APPLICABLE PROVISIONS OF THE HAWAII ADMINISTRATIVE RULES, TITLE 11, CHAPTER 54, "WATER QUALITY STANDARDS," AND TITLE 11, CHAPTER 55, "WATER POLLUTION CONTROL." THE GENERAL CONTRACTOR OF THE PROJECT SHALL OBTAIN NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT COVERAGE(S) FOR THE FOLLOWING:

1.

STORM WATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITIES THAT DISTURB ONE (1) ACRE OR MORE, AND

2.

DISCHARGES OF HYDROTESTING EFFLUENT TO STATE WATERS.

IN ACCORDANCE WITH STATE LAW, ALL DISCHARGES RELATED TO PROJECT CONSTRUCTION OR OPERATIONS ARE REQUIRED TO COMPLY WITH STATE WATER QUALITY STANDARDS (HAWAII ADMINISTRATIVE RULES, CHAPTER 11-54). BEST MANAGEMENT PRACTICES SHALL BE USED TO MINIMIZE OR PREVENT THE DISCHARGE OF SEDIMENT, DEBRIS, AND OTHER POLLUTANTS TO STATE WATERS. PERMIT COVERAGE IS AVAILABLE FROM THE DEPARTMENT OF HEALTH, CLEAN WATER BRANCH AT HTTP://HEALTH.HAWAII.GOV/CWB. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING OTHER FEDERAL, STATE, OR LOCAL AUTHORIZATIONS AS REQUIRED BY LAW.

CONSTRUCTION NOTES

1.

ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE COUNTY OF HAWAII, DEPARTMENT OF PUBLIC WORKS "STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION," DATED SEPTEMBER 1984, AND "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION" DATED SEPTEMBER 1986.
2.

CONSTRUCTION SHALL BE DONE IN SUBSTANTIAL CONFORMANCE WITH THE SUBSURFACE INVESTIGATION REPORT, "LAIOPUA VILLAGE 4 AKAU AND HEMA SUBDIVISIONS KEALAKEHE, HAWAII, HAWAII" DATED MARCH 22, 2012, BY FEWELL GEOTECHNICAL ENGINEERING, LTD. WHERE APPLICABLE.
3.

THE ENGINEER RESERVES THE RIGHT TO MAKE CHANGES TO THE DRAINAGE SYSTEM AS SUCH CHANGES ARE FOUND TO BE NECESSARY AS THE LAND IS CLEARED AND EROSION CONTROL CONSTRUCTION PROGRESSES.
4.

ALL CONSTRUCTION LINES, GRADES AND SURVEY MONUMENT STAKEOUTS SHALL BE MADE BY LICENSED SURVEYORS.
5.

A LICENSED SURVEYOR SHALL SUBMIT A LETTER TO THE DEPARTMENT OF PUBLIC WORKS CERTIFYING THAT THE MONUMENT STAKEOUT AND INSTALLATION IS CORRECT.

6.

THE CONTRACTOR SHALL NOTIFY THE ENGINEER SUFFICIENTLY IN ADVANCE OF OPENING ANY OR UTILIZING EXISTING BORROW PITS OR ON SITE BORROW, SO THAT A DETERMINATION CAN BE MADE AS TO THE SUITABILITY OF THE BORROW MATERIAL TO BE INCORPORATED INTO THE ROAD CONSTRUCTION.
7.

THE CONTRACTOR SHALL CONDUCT ALL TESTS AS REQUESTED BY THE ENGINEER AND BE RESPONSIBLE FOR ALL EXPENSES INCURRED IN CONDUCTING THESE TESTS.
8.

THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING UTILITIES, WHETHER SHOWN ON THE PLAN OR NOT, AND SHALL BE RESPONSIBLE FOR THE REPAIR OR REPLACEMENT OF THE SAME IN THE EVENT OF DAMAGES DUE TO HIS CONSTRUCTION PRACTICES. THE CONTRACTOR SHALL COORDINATE HIS WORK WITH THE RESPECTIVE UTILITY COMPANIES.
9.

THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL TRAFFIC CONTROL DEVICES IN CONFORMANCE WITH THE CURRENT EDITION OF THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS," AND AS DIRECTED BY THE DEPARTMENT OF PUBLIC WORKS.
10.

ALL VEGETATION, INCLUDING TREES, SHALL BE REMOVED FROM WITHIN THE ENTIRE GRADED ROADWAY RIGHT-OF-WAY.
11.

TOPOGRAPHIC INFORMATION WAS OBTAINED FROM "VILLAGES OF LAIOPUA VILLAGE 4 TOPOGRAPHIC MAP" PREPARED BY ESAKI SURVEYING & MAPPING, FEBRUARY 2012 AND MAY NOT ACCURATELY REFLECT FIELD CONDITIONS. THE CONTRACTOR SHALL MAKE ADJUSTMENTS TO THE PROPOSED IMPROVEMENTS AS NECESSARY AT NO ADDITIONAL COST TO THE STATE.

NOTES FOR WORK WITHIN THE COUNTY RIGHT-OF-WAY

1.

ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE COUNTY OF HAWAII, DEPARTMENT OF PUBLIC WORKS (DPW), "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION," DATED SEPTEMBER 1986 AND "STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION," DATED SEPTEMBER 1984.
2.

THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING UTILITIES, WHETHER SHOWN ON THE PLAN OR NOT, AND SHALL BE RESPONSIBLE FOR THE REPAIR OR REPLACEMENT OF SAME IN THE EVENT OF DAMAGES DUE TO HIS CONSTRUCTION PRACTICES. THE CONTRACTOR SHALL COORDINATE HIS WORK WITH THE RESPECTIVE UTILITY COMPANIES.
3.

THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL TRAFFIC CONTROL DEVICES IN CONFORMANCE WITH THE CURRENT EDITION OF THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS," AND AS DIRECTED BY THE DEPARTMENT OF PUBLIC WORKS.
4.

THE CONTRACTOR SHALL NOTIFY THE DEPARTMENT OF PUBLIC WORKS 48 HOURS BEFORE THE COMMENCEMENT OF ANY UTILITY LINE WORK TO SCHEDULE A FIELD REVIEW AND SECURE APPROVAL OF THE PROPOSED UTILITY LINE LOCATION WITHIN THE COUNTY RIGHT-OF-WAY.
5.

THE PROPOSED UTILITY LINE LOCATION SHALL BE LAID OUT IN THE FIELD PRIOR TO THE CONDUCTING OF THE FIELD REVIEW BY THE DEPARTMENT OF PUBLIC WORKS.
6.

FIELD ADJUSTMENTS SHALL BE MADE AS DIRECTED BY THE DEPARTMENT OF PUBLIC WORKS PRIOR TO THE COMMENCEMENT OF ANY UTILITY LINE WORK.
7.

THE REQUIRED PERMIT, UNDER CHAPTER 22, ARTICLE 3, SECTION 22-44 OF THE HAWAII COUNTY CODE, SHALL BE OBTAINED FROM THE DEPARTMENT OF PUBLIC WORKS BY THE CONTRACTOR FOR WORK WITHIN THE COUNTY RIGHT-OF-WAY.
8.

THE CONTRACTOR SHALL PROVIDE AT LEAST ONE (1) LANE FOR TRAFFIC MOVEMENT AT ALL TIMES. TWO (2) LANES FOR TRAFFIC MOVEMENT SHALL BE PROVIDED BETWEEN THE HOURS OF 3:30 P.M. TO 8:00 A.M.
9.

THE EXISTING PAVEMENT SHALL BE SAW-CUT BEFORE COMMENCEMENT OF TRENCHING WORK.
10.

ANY PAVEMENT OUTSIDE THE CONTRACT ZONE LIMITS DAMAGED AS A RESULT OF CONSTRUCTION OPERATIONS SHALL BE RESTORED TO ITS ORIGINAL CONDITION, OR BETTER, AS DIRECTED BY THE DPW.
11.

A TEMPORARY COLD MIX PATCH SHALL BE APPLIED IMMEDIATELY UPON COMPLETION OF THE BACKFILLING OPERATION AND SHALL BE MAINTAINED BY THE CONTRACTOR UNTIL A PERMANENT PATCH IS AUTHORIZED BY THE DEPARTMENT OF PUBLIC WORKS.
12.

NO MATERIAL, EXCEPT THE TRENCH EXCAVATED MATERIAL, SHALL BE STOCKPILED CLOSER THAN SIX (6) FEET FROM THE EXISTING EDGE OF PAVEMENT.
13.

NO CONSTRUCTION EQUIPMENT SHALL BE PARKED WITHIN THE ROAD RIGHT-OF-WAY IN SUCH A MANNER THAT THE EQUIPMENT WILL OBSTRUCT THE NORMAL MOVEMENT AND SIGHT DISTANCE OF THE DRIVING MOTORIST, EXCEPT DURING ACTUAL WORKING HOURS.
14.

EXCEPT DURING ACTUAL WORKING HOURS, ALL SIGNS THAT DO NOT PERTAIN TO THE CONSTRUCTION ACTIVITY, SUCH AS "MEN WORKING" AND "FLAGMAN AHEAD" SHALL BE COVERED OR LAID DOWN. HOWEVER, ALL SIGNS NECESSARY FOR THE SAFETY OF THE PUBLIC SHALL BE MAINTAINED.
15.

ANY PAVEMENT MARKINGS, STRUCTURES, AND APPURTENANCES (WITHIN OR OUTSIDE OF THE CONTRACT ZONE LIMITS) DAMAGED AND/OR WORN AWAY UNDER THE PERMIT SHALL BE REPAINTED OR RECONSTRUCTED AS DIRECTED BY THE DEPARTMENT OF PUBLIC WORKS.
16.

NO TRENCHING SHALL BE LEFT OPEN FOR MORE THAN FIVE (5) WORKING DAYS.
17.

SHOULD TRENCHING OCCUR THROUGH AN EXISTING SIDEWALK OR SHOULD DAMAGES OCCUR TO THE SIDEWALK AS A RESULT OF TRENCHING, THE FOLLOWING PROCEDURE SHALL BE UTILIZED TO REPAIR THE SIDEWALK.

A.

ALL PORTLAND CEMENT CONCRETE TO BE REMOVED SHALL FIRST BE CUT WITH A CONCRETE SAW THAT HAS A DIAMOND OR CARBORUNDUM ABRASIVE WHEEL. THOSE CUTS SHALL BE MADE TO A DEPTH EQUAL TO AT LEAST ONE-FOURTH OF THE DEPTH OF THE SLAB, OR ENOUGH AS IS DEEMED NECESSARY BY THE DEPARTMENT OF PUBLIC WORKS, TO PERMIT BREAKING OUT THE BALANCE OF THE CONCRETE WITHOUT SPALLING OFF THE EXPOSED EDGES OF THE SLAB LEFT IN PLACE.

B.

IF ANY CONCRETE BLOCK IS TOUCHED, THE WHOLE BLOCK SHALL BE REMOVED AND LATER REPLACED, UNLESS A MINOR VARIATION IS AUTHORIZED BY THE DPW OR ITS REPRESENTATIVE.

C.

ANY DAMAGES TO ADJACENT AREAS DUE TO SETTLEMENT OR TO ANY OTHER EFFECTS WHATSOEVER CAUSED BY THE TRENCH CONSTRUCTION SHALL BE PROPERLY REPAIRED AND CORRECTED.

- D.

ALL OTHER INCIDENTAL WORK SHALL BE SATISFACTORILY PERFORMED TO EFFECT THE PROPER RESTORATION OF THE SIDEWALK AREA.
- E.

SHOULD DAMAGE TO A SIDEWALK, CURB AND/OR GUTTER OCCUR AT A LOCATION WHERE A CURB RAMP SHOULD EXIST, OR TO A DRIVEWAY THAT DOES NOT MEET WITH THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT (ADA), REPAIR WORK SHALL INCLUDE THE CONSTRUCTION OF A CURB RAMP, RECONSTRUCTION TO THE DRIVEWAY SUCH THAT THE REPAIR WORK COMPLIES WITH THE ADA AND MEETS WITH THE APPROVAL OF THE DPW.
18.

THE PERMITTEE SHALL MAINTAIN, TO THE SATISFACTION OF THE DEPARTMENT OF PUBLIC WORKS, THE AREA WORKED WITHIN THE GOVERNMENT RIGHT-OF-WAY INCLUDING ANY REPAIRS TO PAVEMENT AND SHOULDER DAMAGED AS A RESULT OF THE INSTALLATION WORK, FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF FINAL INSPECTION. THE PERMITTEE SHALL UNDERTAKE REPAIRS EXPEDITIOUSLY, WHENEVER DIRECTED BY THE DEPARTMENT OF PUBLIC WORKS DURING THE MAINTENANCE PERIOD.
19.

SUBDIVIDER SHALL BE INFORMED THAT CHAPTER 23, UNDERGROUND INJECTION CONTROL (UIC), ADMINISTRATIVE RULES, DEPT. OF HEALTH, PROHIBIT ANY PERSON FROM OPERATING, CONSTRUCTING OR MODIFYING AN INJECTION WELL (DRYWELL) UNLESS AUTHORIZED BY A PERMIT ISSUED BY THE DIRECTOR OF HEALTH, STATE OF HAWAII. FURTHERMORE, SHOULD DEDICATION OF ROADWAYS INCLUDING DRYWELL BE CONTEMPLATED, THE DEPT. OF PUBLIC WORKS WILL NOT APPROVE DEDICATION OF ROADWAYS PRIOR TO COMPLIANCE WITH CHAPTER 23, UIC, ADMINISTRATIVE RULES.

ARCHAEOLOGICAL NOTES

1.

IN THE EVENT THAT AN ARCHAEOLOGICAL OR HISTORICAL STRUCTURE WITHIN THE WORK AREA IS INADVERTENTLY DAMAGED DURING CONSTRUCTION, CEASE WORK IN THE VICINITY OF THE SITE AND NOTIFY THE DEPARTMENT OF HAWAIIAN HOME LANDS AND THE STATE HISTORIC PRESERVATION DIVISION (SHPD) OF THE DEPARTMENT OF LAND AND NATURAL RESOURCES OF THE DAMAGE. SHPD WILL DETERMINE THE APPROPRIATE MITIGATION MEASURES.
2.

IN THE EVENT THAT A PREVIOUSLY UNKNOWN ARCHAEOLOGICAL FEATURE IS EXPOSED BY CONSTRUCTION, CEASE WORK IN THE VICINITY OF THE NEW FEATURE AND NOTIFY THE DEPARTMENT OF HAWAIIAN HOME LANDS, THE SHPD, AND THE HAWAII COUNTY PLANNING DEPARTMENT OF THE NEW DISCOVERY.
3.

IN THE EVENT THAT PREVIOUSLY UNKNOWN HUMAN REMAINS ARE EXPOSED BY CONSTRUCTION, CEASE ALL WORK IN THE AREA OF THE REMAINS, AND PROTECT THE AREA WITH AN APPROPRIATE MATERIAL. NOTIFY THE DEPARTMENT OF HAWAIIAN HOME LANDS AND THE SHPD.

DEPT. OF HEALTH NOTES

1.

OWNER SHALL OBTAIN PERMIT TO CONSTRUCT AND OPERATE INJECTION WELL(S) IN COMPLIANCE WITH CHAPTER 23, UNDERGROUND INJECTION CONTROL (UIC), ADMINISTRATIVE RULES, DEPARTMENT OF HEALTH.

SOLID WASTE CONSTRUCTION NOTES


1.

UNLESS OTHERWISE SPECIFIED, THE CONTRACTOR IS RESPONSIBLE FOR THE PROPER HANDLING, STORAGE AND/OR DISPOSAL OF ALL WASTE GENERATED BY THIS CONSTRUCTION, INCLUDING GRUBBING AND EXCESS EXCAVATED MATERIAL. ANY MATERIAL BROUGHT TO THE COUNTY LANDFILLS WILL BE SUBJECTED TO THE INSTITUTED TIPPING FEE SYSTEM, WITH NO EXCEPTIONS OR EXEMPTIONS.
2.

ALL WASTES GENERATED BY CONSTRUCTION, INCLUDING GRUBBING, DEMOLITION AND EXCESS EXCAVATION MATERIAL MAY BE BROUGHT TO THE WEST HAWAII OR THE HILO LANDFILL. THE CONTRACTOR SHALL CHECK WITH THE SOLID WASTE DIVISION FOR DISCLOSURE OF THE CURRENT LANDFILL FEE AND CONSIDERATION OF THAT FEE SHALL BE INCLUDED IN THE CONTRACTOR'S BID SUM.
3.

CONSTRUCTION, DEMOLITION AND GRUBBING MATERIAL SHALL NOT BE DEPOSITED AT ANY OF THE COUNTY TRANSFER STATIONS, BUT SHALL BE TRANSPORTED FOR DISPOSAL TO EITHER THE WEST HAWAII OR HILO LANDFILL.
4.

ASBESTOS MATERIAL MUST BE SEPARATED, DOUBLE BAGGED AND LANDFILLED IN ACCORDANCE WITH REGULATIONS OF THE SOLID WASTE DIVISION, DEPARTMENT OF ENVIRONMENTAL MANAGEMENT. INFORMATION MAY BE OBTAINED BY CALLING THE DIVISION AT (808) 961-8339 BETWEEN 7:00 A.M. AND 4:00 P.M. MONDAY THROUGH FRIDAY.



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CONSTRUCTION NOTES 1			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

FILE	POCKET	FOLDER	NO.
------	--------	--------	-----



WATERLINE NOTES

- ALL WORK SHALL BE DONE ACCORDING TO THE WATER SYSTEM STANDARDS, STATE OF HAWAII, DATED 2002 AS AMENDED.
- THE CONTRACTOR SHALL INFORM THE DEPARTMENT OF WATER SUPPLY (DWS) ENGINEER 72 HOURS PRIOR TO THE BEGINNING OF ANY WATERLINE WORK AND TWO WEEKS PRIOR TO ANY CONNECTION, CHLORINATION, SHUT-OFF OR RELOCATION WORK.
- THE CONTRACTOR SHALL PAY FOR ALL WORK, EQUIPMENT AND MATERIALS FURNISHED BY THE DWS.
- ALL EXISTING WATERLINES, WATERLINE APPURTENANCES AND OTHER UTILITY LOCATIONS SHOWN ON THE PLANS ARE OBTAINED FROM THE LATEST RELIABLE SOURCES. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THE EXACT LOCATION OF ALL UTILITIES IN THE FIELD AND SHALL BEAR ALL COST FOR DAMAGES DONE TO THE WATER SYSTEM.
- ALL CONNECTIONS TO EXISTING WATERLINES SHALL BE DONE BY THE DWS. CONTRACTOR SHALL PERFORM ALL EXCAVATION, BACKFILL, ROAD REPAIR, TRAFFIC CONTROL, AND PROVIDE EQUIPMENT NECESSARY TO COMPLETE THE CONNECTION.
- WHERE WATER SHUT-OFF OF MORE THAN 3 HOURS BECOMES NECESSARY, THE CONTRACTOR, AT HIS OWN EXPENSE, SHALL PROVIDE A TEMPORARY BY-PASS LINE. THE DWS ENGINEER SHALL DETERMINE THE BY-PASS LINE SIZE. IF NECESSARY, THE DWS ENGINEER MAY REQUIRE A BY-PASS LINE, REGARDLESS OF THE EXPECTED SHUT-OFF PERIOD.
- MINIMUM HORIZONTAL CLEARANCE BETWEEN WATERLINE AND OTHER UTILITIES SHALL BE 8 FEET UNLESS OTHERWISE SPECIFIED. MINIMUM VERTICAL CLEARANCE BETWEEN WATERLINES AND OTHER UTILITIES SHALL BE 12" PROVIDED CONCRETE JACKETS ARE USED, AND 18" IF NO CONCRETE JACKETS ARE USED. IN ALL APPLICABLE INSTANCES, THE WATERLINES SHALL BE AT A GRADE HIGHER THAN OTHER UTILITIES.
- ALL MATERIALS FOR FITTINGS AND GATE VALVES SHALL MEET COUNTY STANDARDS AND HAVE MECHANICAL JOINTS UNLESS OTHERWISE SPECIFIED. MATERIALS FOR BUTTERFLY VALVES SHALL MEET COUNTY STANDARDS UNLESS OTHERWISE SPECIFIED.
- THE WATERLINE SHALL BE TESTED AT A MINIMUM OF 225 PSI OR ONE AND A HALF TIMES THE STATIC PRESSURE AT THE LOW POINT, WHICHEVER IS GREATER, UNDER DWS SUPERVISION JUST PRIOR TO PAVING.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CHLORINATION OF THE WATER SYSTEM AND SHALL BEAR ALL COSTS. THE PERSON(S) ENGAGED TO DO THE CHLORINATION WORK MUST HAVE THE APPROPRIATE LICENSE TO PERFORM THE WORK IN THE STATE OF HAWAII.
- EXISTING VALVES, FIRE HYDRANT UNITS, VALVE BOXES, FRAMES, AND COVERS DESIGNATED "REMOVE AND SALVAGE" SHALL BE CLEANED OF ALL DIRT, SCABS, AND CONCRETE AND DELIVERED TO THE RESPECTIVE DWS BASEYARD. THIS WORK SHALL BE CONSIDERED INCIDENTAL TO THE VARIOUS BID ITEMS, UNLESS SPECIFIED OTHERWISE.
- EXISTING WATERLINES, VALVES, FITTINGS AND APPURTENANCES NOT DESIGNATED "REMOVE AND SALVAGE" SHALL BE ABANDONED IN PLACE. ALL EXPOSED VALVE BOXES, VALVES, PIPES AND APPURTENANCES SHALL BE REMOVED AND DISPOSED OF PROPERLY AT NO COST TO THE DWS.
- RELOCATION OF EXISTING METERS SHALL BE DONE BY OR UNDER DWS SUPERVISION. RELOCATIONS OF CUSTOMER SERVICE LINES TO RELOCATED METERS SHALL BE DONE BY THE CONTRACTOR AND PIPE MATERIALS SHALL MEET COUNTY STANDARDS. ALL WORK AND MATERIALS REQUIRED SHALL BE PROVIDED BY THE CONTRACTOR AND CONSIDERED INCIDENTAL TO THE RELOCATION WORK. EXISTING METER BOXES DAMAGED BY THE CONTRACTOR SHALL BE REPLACED AT THE CONTRACTOR'S COST. A DIELECTRIC UNION SHALL BE USED TO CONNECT THE SERVICE LINE PIPE TO THE CUSTOMER'S G.I. PIPE (IF APPLICABLE).
- THE DWS WILL NOT ASSUME OWNERSHIP OF NOR GRANT ANY WATER SERVICE UNTIL THE WATER SYSTEM IS DEDICATED TO THE DWS ALONG WITH ALL NECESSARY EASEMENTS AND DOCUMENTS.
- WHEN COMPACTION TESTS ARE REQUIRED, THE CONTRACTOR SHALL BE RESPONSIBLE TO PROVIDE THE DWS WITH PROCTOR RESULTS OF MATERIALS TO BE USED FOR THAT PORTION OF WORK REQUIRING COMPACTION. THESE RESULTS SHALL BE CERTIFIED AND SHALL BE FURNISHED TO DWS ONE WEEK PRIOR TO COMMENCEMENT OF WORK. COST FOR COMPACTION TESTS SHALL BE INCIDENTAL TO PIPELINE INSTALLATION.
- ALL NEWLY INSTALLED WATERLINES SHALL HAVE A BLUE, NON METALLIC WARNING TAPE LABELED "CAUTION WATER LINE BURIED BLOW" PLACED DIRECTLY OVER THE COMPACTED CUSHION MATERIAL.
- CONSTRUCTION PROJECTS REQUIRING TEMPORARY WATER SERVICE SHALL BE METERED AND PAID FOR BY THE CONTRACTOR.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR RECORD DRAWINGS (AS-BUILT DRAWINGS) AND THE LICENSED ENGINEER SHALL CERTIFY THE DRAWINGS AS TO ACCURACY AND SUBMIT THE DRAWINGS AND AS-BUILT TRACINGS TO THE DWS.
- ALL PIPE MATERIALS FOR WATERLINES SHALL MEET COUNTY STANDARDS UNLESS OTHERWISE SPECIFIED.
- LOTS REQUIRING A DWS APPROVED REDUCED PRESSURE PRINCIPAL TYPE BACKFLOW PREVENTION ASSEMBLY SHALL HAVE ONE. IT MUST BE INSTALLED ON PRIVATE PROPERTY IN ACCORDANCE WITH STANDARD DETAIL V9 (ABOVE GROUND) AND DEPARTMENTAL STAFF MUST APPROVE THE INSTALLATION BEFORE WATER SERVICE CAN BE STARTED. NO TAPS OR CONNECTIONS ARE ALLOWED BETWEEN THE METER AND THE APPROVED BACKFLOW PREVENTION ASSEMBLY. THE OWNER IS REQUIRED TO TEST THE BACKFLOW PREVENTION ASSEMBLY 1 TIME PER YEAR. THE OWNER SHALL MAKE THEIR OWN PROVISIONS FOR THOSE TIMES WHEN THE BACKFLOW ASSEMBLY IS BEING TESTED.

GRADING NOTES

- ALL GRADING WORK SHALL CONFORM TO CHAPTER 10 OF THE HAWAII COUNTY CODE. SHOULD A GRADING PERMIT BE REQUIRED, NO WORK SHALL COMMENCE UNTIL THE DEPARTMENT OF PUBLIC WORKS (DPW) APPROVES A GRADING PERMIT.
- ALL GRADING WORK FOR LAIOPUA VILLAGE: PHASE 2 – HEMA SUBDIVISION SHALL BE IN CONFORMANCE WITH THE "SUBSURFACE INVESTIGATION REPORT, LAIOPUA VILLAGE 4 AKAU AND HEMA SUBDIVISIONS KEALAKEHE, HAWAII, HAWAII" DATED MARCH 22, 2012, BY FEWELL GEOTECHNICAL ENGINEERING, LTD. WHERE APPLICABLE.
- THE CONTRACTOR SHALL REMOVE ALL SILT AND DEBRIS DEPOSITED IN DRAINAGE FACILITIES, ROADWAYS AND OTHER AREAS RESULTING FROM HIS WORK. THE COSTS INCURRED FOR ANY NECESSARY REMEDIAL ACTION BY THE DPW SHALL BE PAYABLE BY THE CONTRACTOR.
- THE CONTRACTOR, AT HIS OWN EXPENSE, SHALL KEEP THE PROJECT AND SURROUNDING AREAS FREE FROM DUST NUISANCES. THE WORK SHALL BE IN CONFORMANCE WITH THE AIR POLUUTION CONTROL RULES OF THE STATE DEPARTMENT OF HEALTH, HAR 11-60-1, FUGITIVE DUST.
- ALL GRADING OPERATIONS SHALL BE PERFORMED IN CONFORMANCE WITH THE APPLICABLE PROVISIONS OF THE HAWAII ADMINISTRATIVE RULES, TITLE 11, CHAPTER 55, WATER POLLUTION CONTROL AND CHAPTER 54, WATER QUALITY STANDARDS, AND TO THE EROSION AND SEDIMENTATION CONTROL STANDARDS AND GUIDELINES OF THE DEPARTMENT OF PUBLIC WORKS, COUNTY OF HAWAII.
- THE CONTRACTOR SHALL MAT ALL SLOPES AND EXPOSED AREAS IMMEDIATELY AFTER THE GRADING WORK HAS BEEN COMPLETED.
- FILLS ON SLOPES STEEPER THAN 5:1 SHALL BE KEYED.
- THE CONTRACTOR SHALL INFORM THE DPW OF THE LOCATION OF THE DISPOSAL AND/OR BORROW SITE(S) REQUIRED FOR THIS PROJECT WHEN AN APPLICATION FOR A GRADING PERMIT IS MADE. THE DISPOSAL AND/OR BORROW SITE(S) MUST ALSO FULFILL THE REQUIREMENTS OF THE GRADING ORDINANCE.
- NO GRADING WORK SHALL BE DONE ON SATURDAYS, SUNDAYS AND HOLIDAYS ANYTIME WITHOUT PRIOR APPROVAL FROM THE DEPARTMENT OF PUBLIC WORKS. GRADING WORK ON NORMAL WORKING DAYS SHALL BE BETWEEN THE HOURS OF 7:00 A.M. TO 3:30 P.M.
- FILLS SHALL BE COMPACTED TO 90 PERCENT (90%) OF MAXIMUM DENSITY PER ASTM D-1557 TEST.
- THE CONTRACTOR SHALL REMOVE ALL VEGETATION BEFORE PLACING FILLS ON NATURAL GROUND SURFACE.
- THE CONTRACTOR SHALL PROVIDE ADEQUATE MEASURES TO PREVENT FLOODING AND EROSION PROBLEMS TO ADJACENT PROPERTIES.
- ALL GRADING OPERATIONS SHALL BE PERFORMED IN CONFORMANCE WITH THE APPLICABLE PROVISIONS OF THE HAWAII ADMINISTRATIVE RULES, TITLE 11, CHAPTER 46, COMMUNITY NOISE CONTROL.

TRAFFIC NOTES

- ALL TRAFFIC SIGNS AND PAVEMENT MARKINGS SHALL CONFORM TO THE LATEST AMENDED EDITIONS OF THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES", APPLICABLE SECTIONS OF PART 5 OF THE "STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION", DATED SEPTEMBER, 1984, AND THE "2005 HAWAII STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", UNLESS OTHERWISE INDICATED ON THE PLANS, SPECIFICATIONS, OR STANDARD TRAFFIC NOTES.
- THE CONTRACTOR SHALL INSTALL PERMANENT OR TEMPORARY PAVEMENT MARKERS, STRIPING AND MARKINGS AS REQUIRED BY SECTION(S) 629 AND 755.05 OF THE "2005 HAWAII STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", AND AS AMENDED. TO ENSURE PROPER LANE WIDTHS AND THE SAFE FLOW OF TRAFFIC, TEMPORARY STRIPING SHALL BE INSTALLED AS CLOSELY AS POSSIBLE TO THE FINAL STRIPING PLAN, BUT NOT IN A MANNER THAT WOULD OBSTRUCT PERMANENT STRIPING LAYOUT OPERATIONS.
- THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL TRAFFIC SIGNS AND MARKINGS FOR ALL PROJECT-RELATED TEMPORARY TRAFFIC CONTROL PLANS. THE CONTRACTOR SHALL COORDINATE AND HIRE SPECIAL DUTY POLICE OFFICER(S) AS NEEDED TO PROVIDE TRAFFIC CONTROL WHILE WORKING WITHIN THE COUNTY RIGHT OF WAY.
- THE CONTRACTOR SHALL INFORM THE TRAFFIC DIVISION AT LEAST SIX (6) WORKING DAYS PRIOR TO ANY WORK ON PAVEMENT MARKINGS OPERATIONS AND/OR SIGN INSTALLATIONS TO SCHEDULE A REVIEW AND APPROVAL OF THE STRIPING LAYOUT AND/OR SIGNING PLANS.
- THE APPROVED STRIPING PLAN SHALL BE LAID OUT USING MARKING PAINT OR OTHER APPROVED METHODS. FIELD ADJUSTMENTS SHALL BE MADE AS DIRECTED BY THE INSPECTOR BEFORE THE FINAL MARKINGS ARE APPLIED.
- ALL PAVEMENT MARKINGS THAT BECOME INAPPLICABLE SHALL BE REMOVED BY THE CONTRACTOR AT HIS OWN EXPENSE. REMOVAL SHALL BE BY ERADICATION OR BY OTHER METHODS APPROVED BY THE INSPECTOR BEFORE THE NEW PAVEMENT MARKINGS ARE APPLIED. EXCESSIVE GOUGING OF THE PAVEMENT SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE.
- ALL PAVEMENT STRIPING SHALL BE WITH ALKYD BASED REFLECTIVE THERMOPLASTIC COMPOUND PAVEMENT MARKING AS SPECIFIED IN SECTION(S) 629 AND 755.05 OF THE HAWAII STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, 2005 EDITION, AND AS AMENDED, ON ALL ROADWAYS. THE CONTRACTOR SHALL SUBMIT CERTIFICATE OF COMPLIANCE CERTIFYING THAT THE THERMOPLASTIC MATERIALS TO BE USED MEET THE CURRENT AASHTO M-247 (FOR GLASS BEADS) AND AASHTO M-249 (FOR STRIPING) SPECIFICATIONS.

FOR CROSSWALKS AND STOP LINES, THE CONTRACTOR SHALL APPLY HIGH SKID-RESISTANT WHITE CORUNDUM OR APPROVED EQUAL.

TRAFFIC NOTES CON'T.

- ON CONCRETE PAVEMENTS, PRE-STRIPE APPLICATION AREA WITH BINDER MATERIAL, PRIMER, OR PRIME SEAL COAT RECOMMENDED BY PAVEMENT MARKER MANUFACTURER.
- HEAT APPLIED PRE-FORMED THERMOPLASTIC PAVEMENT MARKING TAPE WITH VISIBLE TEMPERATURE INDICATORS, OR AN EQUAL PAVEMENT MARKING TAPE THAT IS APPROVED BY THE TRAFFIC DIVISION SHALL BE USED FOR ALL BIKE LANE SYMBOLS AND LEGENDS PER TRAFFIC STANDARD DETAIL TR-111, AND MAY BE USED FOR CROSSWALKS, STOP LINES, PAVEMENT ARROWS, ALPHABETS, AND SYMBOLS IN LIEU OF THERMOPLASTIC COMPOUND.

HEAT APPLIED PRE-FORMED THERMOPLASTIC PAVEMENT MARKING TAPE FOR BIKE LANE SYMBOLS AND LEGENDS PER TRAFFIC STANDARD DETAIL TR-111, CROSSWALKS AND STOP LINES SHALL BE MADE OF A DURABLE, HIGH SKID-RESISTANT MATERIAL.

- REFLECTORIZED RAISED PAVEMENT MARKERS (RPM'S) SHALL BE THE REGULAR SIZED MARKERS WITH APPROXIMATE DIMENSIONS OF 4"x4"x0.7". THE CONTRACTOR SHALL SUBMIT CERTIFICATE OF COMPLIANCE CERTIFYING THAT THE RPM'S TO BE USED MEET OR EXCEED THE CURRENT STATE OF HAWAII, DEPARTMENT OF TRANSPORTATION SPECIFICATIONS.
- ALL TRAFFIC SIGNS AND POSTS SHALL MEET THE REQUIREMENTS OF THE COUNTY OF HAWAII STANDARD DETAIL T-1 EXCEPT THAT FLANGED CHANNEL POSTS AND OCTAGONAL POSTS WILL NOT BE ACCEPTABLE. SIGNS SHALL BE ON ALUMINUM SHEETING OF 0.080-INCH MINIMUM THICKNESS. SIGN POSTS SHALL BE 2" SQUARE TELES PAR TUBING NO. 20 F 12 OR EQUIVALENT WITH 2 1/4" SQUARE TELES PAR ANCHOR POST.

FOR ALL COUNTY DEDICATED STREETS, THE CONTRACTOR SHALL PLACE A TRAFFIC DIVISION MAINTENANCE STICKER ON THE BACK OF EACH SINGLE-SIDED SIGN. STICKERS ARE TO BE ACQUIRED AT THE TRAFFIC DIVISION.

- ALL TRAFFIC SIGNS SHALL BE HIGH INTENSITY RETROREFLECTIVE SHEETING, WITH TYPE IV FOR REGULATORY, WARNING, AND DIRECTIONAL SIGNS AND TYPE IX (FLUORESCENT YELLOW GREEN SHEETING) FOR PEDESTRIAN, SCHOOL, AND BICYCLE CROSSING SIGNS.
- THE 2 1/4" SQUARE ANCHOR POST FOR SIGNS SHALL BE DRIVEN INTO THE GROUND, A.C. PAVEMENT OR CONCRETE SIDEWALK IN ACCORDANCE WITH THE PLANS. ALL DAMAGES TO THE SURROUNDING AREA SHALL BE REPAIRED TO ITS ORIGINAL CONDITION OR BETTER. BEFORE DRIVING INTO CONCRETE, A NEAT HOLE OF APPROXIMATELY 3 INCH DIAMETER SHALL BE DRILLED THROUGH THE CONCRETE PRIOR TO THE INSTALLATION OF THE ANCHOR POST. IF DRIVING INTO THE CONCRETE OR A.C. PAVEMENT IS NOT POSSIBLE WITHOUT DAMAGE TO THE SURROUNDING CONCRETE OR A.C. PAVEMENT, A 12" BY 12" SQUARE SHALL BE SAW-CUT AND REMOVED PRIOR TO THE INSTALLATION OF THE ANCHOR POST AND THEN PATCHED, WITH HOT MIX TO MATCH THE EXISTING A.C. PAVEMENT, OR CONCRETE TO MATCH THE EXISTING CONCRETE SIDEWALK.

- UPON COMPLETION OF ALL CONSTRUCTION WORK, INCLUDING, BUT NOT LIMITED TO THE FINAL PAVING OF THE ENTIRE PROJECT AREA AND OFF-SITE CONSTRUCTION, THE CONTRACTOR SHALL RESTRIPE ALL PAVEMENT MARKINGS WITHIN AND IN THE VICINITY OF THE CONSTRUCTION AREA AS APPROVED BY THE TRAFFIC DIVISION AND IN ACCORDANCE WITH ITEM 6 OF THE CURRENT STANDARD TRAFFIC NOTES. THE CONTRACTOR SHALL MAINTAIN ALL TEMPORARY PAVEMENT MARKINGS, PERMANENT PAVEMENT MARKINGS, AND ALL TRAFFIC SIGNS AND POSTS UNTIL THE PROJECT IS ACCEPTED BY THE COUNTY OF HAWAII.

ALL TRAFFIC SIGNS AND POSTS WITHIN AND IN THE VICINITY OF THE CONSTRUCTION AREA THAT HAVE BEEN DAMAGED, REMOVED, OR ADVERSELY AFFECTED BY THE CONSTRUCTION WORK SHALL BE REPLACED BY THE CONTRACTOR ACCORDING TO ITEM(S) 10, 11, AND 12 OF THE CURRENT STANDARD TRAFFIC NOTES AT NO COST TO THE COUNTY.

- ALL DEDICATED STREETS MUST HAVE STREET NAMES WHICH HAVE BEEN APPROVED BY RESOLUTION BEFORE ACCEPTANCE OF THE STREET BY THE COUNTY OF HAWAII.

UNLESS OTHERWISE APPROVED BY THE TRAFFIC DIVISION, ALL STREET NAME SIGNS SHALL HAVE AN UPPERCASE FIRST LETTER/LOWERCASE FORMAT AND THE PROPER HAWAIIAN SPELLING FOR THE STREET NAMES AS APPROVED BY THE COUNTY OF HAWAII PLANNING DEPARTMENT.

PRIOR TO STREET NAME SIGN FABRICATION, STREET NAME SIGN SUBMITTALS SHALL BE REVIEWED AND APPROVED BY THE TRAFFIC DIVISION.


- INSTALL "PRIVATE ROAD" SIGN(S) ON ALL PRIVATE ROAD(S). SIGN SHALL BE ON 18" WIDE BY 12" HIGH ALUMINUM PLATE WITH 4" BLACK LETTERING ON WHITE REFLECTORIZED SHEETING WITH BORDER.

- ALL SIGNS & MARKINGS FOR PRIVATE ROADWAYS SHALL BE MAINTAINED BY THE PRIVATE OWNERS.

COMPACTION TESTING

THE DEPARTMENT OF HAWAIIAN HOME LANDS SHALL HIRE AN INDEPENDENT TESTING LAB TO CONDUCT COMPACTION TESTS. COMPACTION TESTS SHALL BE TAKEN IN ACCORDANCE WITH THE SPECIFICATIONS FOR INSTALLATION OF MISCELLANEOUS IMPROVEMENTS WITHIN STATE HIGHWAYS. COMPACTION TESTS SHALL BE TAKEN ACCORDING TO SECTION 207.1, SPECIAL INSTRUCTIONS OF FIELD COMPACTION TESTING, HDOT TECHNICAL MANUAL ON MATERIAL QUALITY CONTROL, AS FOLLOWS:

- SUBBASE: ONE (1) COMPACTION TEST PER LIFT, PER 300 LINEAR FEET.
- BASE COURSE: ONE (1) COMPACTION TEST PER LIFT, PER 200 LINEAR FEET.
- ONE (1) COMPACTION TEST PER LIFT, PER 500 LINEAR FEET OF TRENCH.



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOPUA VILLAGE 4 SUBDIVISION PHASE 2 – HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CONSTRUCTION NOTES 2			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

FILE	POCKET	FOLDER	NO.
------	--------	--------	-----



G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Construction Notes 3.DWG  
Last Save by: LRS  
Last Saved: 10/25/2019  
Plotted on: 3/9/2020

WASTEWATER COLLECTION SYSTEM NOTES:

GENERAL REQUIREMENTS:

1.

THE GENERAL REQUIREMENTS AND COVENANTS OF THE DEPARTMENT OF PUBLIC WORKS, COUNTY OF HAWAI'I (JULY 1972): THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (APPLICABLE NON-WASTEWATER SECTIONS, SEPTEMBER 1986), THE STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION, DEPARTMENT OF PUBLIC WORKS, COUNTY OF HAWAI'I (APPLICABLE NON-WASTEWATER SECTIONS, SEPTEMBER 1984), WASTEWATER SYSTEM DESIGN STANDARDS, CITY AND COUNTY OF HONOLULU (JULY 2017), WASTEWATER SYSTEM STANDARD DETAILS, CITY AND COUNTY OF HONOLULU (JULY 2017) AND THE COUNTY OF HAWAI'I, DEPARTMENT OF ENVIRONMENTAL MANAGEMENT, WASTEWATER DIVISION (WWD) STANDARD DETAILS (WW-1 THRU WW-9, CURRENT VERSION) SHALL BE APPLICABLE AND INCORPORATED HEREIN UNLESS OTHERWISE NOTED.

2.

BASIS OF BEARING (HORIZONTAL CONTROL):EXIST. STREET MONUMENT ALONG KEANALEHU DRIVE

3.

BASIS OF ELEVATION (VERTICAL CONTROL):EXIST. STREET MONUMENT ALONG KEANALEHU DRIVE (388.24)

4.

SURVEY CONTROL AND LAYOUT WHEN REQUIRED SHALL BE PERFORMED BY, OR UNDER THE DIRECT SUPERVISION OF, A PROFESSIONAL LAND SURVEYOR LICENSED IN THE STATE OF HAWAI'I.

5.

THE CONTRACTOR SHALL PROCURE AND CONFORM TO ALL PERMITS AND LICENSES REQUIRED, PAY ALL ASSOCIATED CHARGES AND FEES AND GIVE ALL NOTICES NECESSARY AND INCIDENTAL TO THE DUE AND LAWFUL PROSECUTION OF THE WORK.

A.

THE CONTRACTOR SHALL PROCURE AND CONFORM TO A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT FROM THE STATE OF HAWAI'I, DEPARTMENT OF HEALTH, CLEAN WATER BRANCH FOR ANY PROJECT WHERE CONSTRUCTION ACTIVITIES WILL DISTURB ONE (1) ACRE OR MORE OF TOTAL LAND AREA OR WHERE DEWATERING IS REQUIRED.

B.

ALL STORMWATER POLLUTION PREVENTION MEASURES SHALL BE INSTALLED SO AS TO PREVENT STORMWATER RUNOFF, CONSTRUCTION WATER, FUELS, CHEMICALS, OR OTHER LIQUIDS BEING DIRECTED INTO OR ONTO ANY SANITARY SEWER FACILITIES WITHIN THE PROJECT LIMITS. BEST MANAGEMENT PRACTICES (BMPS) MAY INCLUDE, BUT SHALL NOT BE LIMITED TO, USE OF RAINSTOPPER MANHOLE INSERTS.

6.

A MINIMUM HORIZONTAL SEPARATION OF 8 FEET BETWEEN WATER AND SEWER LINES ARE REQUIRED. IF NOT POSSIBLE, SECTION 2.4.12.B OF THE "WASTEWATER SYSTEM DESIGN STANDARDS, CITY AND COUNTY OF HONOLULU, JULY 2017" APPLIES.

7.

A MINIMUM OF 18 INCH VERTICAL CLEARANCE AT WATER AND SEWER MAIN CROSSINGS WITH SEWER UNDERNEATH THE WATER IS REQUIRED. IF NOT POSSIBLE, SECTION 2.4.12.B OF THE "WASTEWATER SYSTEM DESIGN STANDARDS, CITY AND COUNTY OF HONOLULU, JULY 2017" APPLIES.

8.

THE CONTRACTOR SHALL FURNISH ALL LABOR, MATERIALS, AND EQUIPMENT REQUIRED FOR THE COMPLETE INSTALLATION OF THE SUBJECT WORK UNLESS SPECIFICALLY NOTED OTHERWISE ON THE PLANS APPROVED BY THE WWD.

9.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO PERFORM ALL WORK NECESSARY TO COMPLETE CONSTRUCTION PER THE APPROVED PLANS AND SPECIFICATIONS AND SUCH INCIDENTALS AS MAY BE NECESSARY TO MEET APPLICABLE AGENCY REQUIREMENTS INCLUDING, BUT NOT LIMITED TO, OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) REGULATIONS, AND PROVIDE A COMPLETED PROJECT. ONLY PLANS APPROVED BY WWD SHALL BE USED FOR CONSTRUCTION OF, OR CONNECTION TO, THE COUNTY'S PUBLIC WASTEWATER SYSTEM. ANY ADDITIONS, DELETIONS, OR CHANGES TO THE WASTEWATER SYSTEM SHALL MEET THE WRITTEN APPROVAL OF THE COUNTY OF HAWAII, DEPARTMENT OF ENVIRONMENTAL MANAGEMENT, WASTEWATER DIVISION PRIOR TO STARTING THE REVISED WORK.

A.

THE CONTRACTOR SHALL MAINTAIN ONE COMPLETE SET OF APPROVED PLANS ON THE CONSTRUCTION SITE AT ALL TIMES WHERE HE SHALL RECORD THE SIZES, MATERIALS, STATION LOCATIONS AND ELEVATIONS OF ALL EXISTING UTILITIES ENCOUNTERED. THESE FIELD RECORD DRAWINGS SHALL BE KEPT CONTINUOUSLY UP TO DATE AND SHALL BE AVAILABLE FOR INSPECTION BY THE WWD ON REQUEST.

10.

INSPECTIONS SHALL BE REQUIRED FOR ALL WORK WHICH INVOLVES THE WWD'S SEWER MAINS, LATERALS, CLEANOUTS, AND ALL NEW SEWER CONSTRUCTION TO BE DEDICATED TO THE COUNTY OF HAWAII. CALL THE WASTEWATER DIVISION AT (808) 961-8338 DURING NORMAL BUSINESS HOURS (7:00 AM TO 3:30 PM, MONDAY THROUGH FRIDAY, EXCEPT COUNTY OF HAWAI'I HOLIDAYS) AT LEAST TWO (2) WORKING DAYS IN ADVANCE TO SCHEDULE AN INSPECTION.

A.

WWD INSPECTION SHALL BE PERFORMED PRIOR TO BACKFILLING OR COVERING THE PIPE AND ASSOCIATED APPURTENANCES IN PUBLIC EASEMENTS OR RIGHTS-OF-WAY, BEFORE PRIVATE SEWER OR LATERALS ARE CONNECTED TO THE PUBLIC SEWER SYSTEM, AND AFTER ALL ASSOCIATED PLUMBING WORK ON PRIVATE PROPERTY IS COMPLETE, IN ACCORDANCE WITH THE PLUMBING PERMIT.

B.

WHEN WWD DETERMINES THROUGH INSPECTION THAT MATERIAL, EQUIPMENT OR WORKMANSHIP DO NOT MEET THE REQUIREMENTS, THE CONTRACTOR WILL BE GIVEN WRITTEN NOTICE OF NONCOMPLIANCE. IMMEDIATE CORRECTION OF THE DEFICIENCIES SHALL BE ADDRESSED BY THE CONTRACTOR WITH THE WWD ENGINEER AND/OR THEIR REPRESENTATIVE.

C.

ANY INSPECTION BY WWD, HAWAII COUNTY OR OTHER AGENCIES SHALL NOT, IN ANY WAY, RELIEVE THE CONTRACTOR FROM ANY OBLIGATION TO PERFORM THE WORK IN STRICT COMPLIANCE WITH APPLICABLE REGULATIONS, CODES, CONTRACT DOCUMENTS, PLANS, SPECIFICATIONS OR GOVERNING AGENCY REQUIREMENTS.

11.

SEWER WORK SHALL BE SCHEDULED SUCH THAT WORK SHALL NOT BE PERFORMED ON SATURDAYS, SUNDAYS OR COUNTY OF HAWAI'I HOLIDAYS. IF SUCH WORK DICTATES PERFORMANCE ON THESE NON-WORK DAYS, OR AFTER NORMAL HOURS OF OPERATION (3:30 PM TO 7:00 AM), THE CONTRACTOR SHALL BE RESPONSIBLE FOR PAYMENT OF OVERTIME CHARGES TO THE WWD.

12.

THE CONTRACTOR SHALL NOTIFY THE HAWAI'I ONE CALL CENTER OF ANY PLANNED EXCAVATION ON PUBLIC OR PRIVATE PROPERTY AT LEAST FIVE WORKING DAYS, BUT NOT MORE THAN TWENTY-EIGHT CALENDAR DAYS, PRIOR TO COMMENCING SUCH EXCAVATION (IN ACCORDANCE WITH HRS 269 E-7). CALL 1-866-423-7287 (OR 811). ERRORS IN ONE CALL'S SANITARY SEWER LOCATES SHALL BE REPORTED IMMEDIATELY TO THE WWD AT (808) 961-8338.

13.

LOCATIONS AND DESCRIPTIONS OF EXISTING UTILITIES SHOWN ON THE PLANS ARE COMPILED FROM AVAILABLE RECORDS AND/OR FIELD SURVEY. THE ENGINEER AND UTILITY PROVIDERS DO NO GUARANTEE THE ACCURACY OR COMPLETENESS OF SUCH RECORDS. THE CONTRACTOR SHALL FIELD VERIFY LOCATIONS, SIZES, MATERIALS AND DEPTHS OF ALL EXISTING UTILITIES WHERE PROPOSED FACILITIES CROSS.
- GENERAL REQUIREMENTS (CON'T):
14.

THE CONTRACTOR SHALL FIELD VERIFY EXISTING SANITARY SEWER LOCATIONS, ELEVATIONS, AND MATERIALS WITHIN THE PROJECT LIMITS PRIOR TO CONSTRUCTION. POT-HOLING MAY BE REQUIRED FOR SUCH VERIFICATION.

15.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR EXPOSING POTENTIAL UTILITY CONFLICTS FAR ENOUGH AHEAD OF CONSTRUCTION TO MAKE NECESSARY LINE AND GRADE MODIFICATIONS WITHOUT DELAYING THE WORK.

16.

ALL EXISTING UTILITIES EXCEPT THOSE SPECIFICALLY DESIGNATED FOR ABANDONMENT OR REMOVAL ON THE APPROVED PLANS, INCLUDING WASTEWATER LINE(S), WHETHER OR NOT SHOWN ON THE PLANS , SHALL BE PROTECTED AND REPAIRED BY THE CONTRACTOR IF DAMAGED DURING CONSTRUCTION. THE CONTRACTOR SHALL LEAVE EXISTING FACILITIES IN AN EQUAL TO OR BETTER THAN ORIGINAL CONDITION. THE CONTRACTOR SHALL PAY ALL ASSOCIATED EXPENSES: IN THE EVENT OF DAMAGE TO EXISTING UTILITY FACILITIES OTHER THAN SANITARY SEWER, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE UTILITY SERVICE PROVIDER. IN THE EVENT OF DAMAGE TO EXISTING SANITARY SEWER FACILITIES, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE WWD AT (808) 961-8338.

17.

THE CONTRACTOR SHALL NOTIFY AND COORDINATE WITH PRIVATE UTILITIES FOR ADJUSTMENT TO OR RELOCATION OF POWER POLES, VAULTS, ETC. TO AVOID CONFLICT WITH COUNTY SEWER STRUCTURES, LINES AND ASSOCIATED APPURTENANCES.

18.

EXPOSED ENDS OF SEWER LINES THAT ARE ABANDONED OR TO BE ABANDONED IN PLACE SHALL BE CAPPED OR PLUGGED WITH CONCRETE FOR A MINIMUM LENGTH EQUAL TO TWO TIMES THE DIAMETER OF THE ABANDONED PIPE AND INTERFERING PORTIONS REMOVED BY THE CONTRACTOR TO THE EXTENT NECESSARY TO ACCOMPLISH THE WORK, UNLESS OTHERWISE SPECIFIED.

19.

THE CONTRACTOR SHALL MAINTAIN ACCESS TO ALL SANITARY SEWER STRUCTURES AND MANHOLES AT ALL TIMES.

20.

BYPASSING OR SPILLING OF SEWAGE TO THE GROUND, DRAINAGE SYSTEM OR STATE WATERS IS PROHIBITED. IN SUCH CASES, THE CONTRACTOR SHALL IMMEDIATELY CALL THE WWD AT (808) 961-8338, TAKE IMMEDIATE ACTION TO CONTAIN THE SEWAGE, AND PAY PENALTIES, INCLUDING LEGAL FEES AND OTHER COSTS RELATED TO THE BYPASS AND/OR SPILL.

21.

THE CONTRACTOR SHALL BE IN PERSON ON THE JOB SITE OR BE REPRESENTED ON THE JOB SITE BY A RESPONSIBLE AGENT WITH AUTHORITY TO ACT FOR THE CONTRACTOR IN CONNECTION WITH THIS PROJECT AT ALL TIMES.

22.

THE CONTRACTOR SHALL, AT ALL TIMES DURING THE WORK, KEEP THE PREMISES CLEAN AND ORDERLY. PUBLIC STREETS AND RIGHTS-OF-WAY SHALL BE KEPT CLEAN OF MUD, DUST AND DEBRIS. THE CONTRACTOR SHALL ADEQUATELY WATER DISTURBED AREAS ON-SITE FOR DUST ABATEMENT, AS NEEDED. UPON COMPLETION OF THE WORK, THE CONTRACTOR SHALL REPAIR ALL DAMAGE CAUSED BY EQUIPMENT AND LEAVE THE PROJECT FREE OF RUBBISH AND EXCESS MATERIALS OF ANY KIND. DROPPING OR WASHING DEBRIS OR RUBBISH OF ANY KIND INTO THE SANITARY SEWER SYSTEM IS PROHIBITED.

SEWER SYSTEM REQUIREMENTS:

GRAVITY MAINS

1.

SEWER MAIN PIPE AND FITTINGS:

A.

ALL SANITARY SEWER PIPE AND FITTINGS SHALL BE WWD STANDARD APPROVED MATERIAL, UNLESS OTHERWISE NOTED ON THE APPROVED PLANS.

B.

LAYING OF PIPE SHALL GENERALLY COMMENCE AT THE LOWEST POINT, THE BELL END FACING UPSTREAM, REGARDLESS OF THE STATIONING SHOWN ON THE PLANS. PIPE SHALL BE FITTED TOGETHER AND MATCHED WITH GASKETS PROPERLY SEATED SO THAT WHEN LAID IT WILL FORM A UNIFORM AND SMOOTH INVERT.

C.

REFER TO THE DRAWINGS FOR DETAILED REQUIREMENTS FOR ALL CONNECTIONS TO EXISTING SANITARY SEWER PIPE. DETAILS SHALL BE PROVIDED TO AND APPROVED BY WWD.

D.

THE INTERIOR OF THE SEWER PIPE SHALL BE CLEARED OF ALL DEBRIS AND FOREIGN MATERIALS AS THE WORK PROGRESSES. BEFORE LEAVING THE WORKPLACE FOR THE NIGHT, EXPOSED ENDS OF SEWER PIPE SHALL BE CLOSED WITH TEMPORARY COVERS TO PREVENT EARTH AND DEBRIS FROM ENTERING THE PIPE.

E.

BECAUSE OF THE NATURE OF PLASTIC PIPE AND FITTINGS, THE CONTRACTOR IS CAUTIONED TO EXERCISE CARE IN HANDLING, LOADING, UNLOADING, AND STORING TO AVOID DAMAGE.

I.

KEEP PIPE AND GASKETS CLEAN, AWAY FROM OIL, GREASE, EXCESSIVE HEAT AND ELECTRIC MOTORS, WHICH PRODUCE OZONE, AND PROTECTED FROM DIRECT SUNLIGHT AND TEMPERATURE CHANGES IN PROLONGED EXPOSURE TO AVOID CRACKING.

II.

HEAVY IMPACT MAY CAUSE A SLIGHT LONGITUDINAL INDENTATION ON THE OUTSIDE OF THE PIPE AND A CRACK ON THE INSIDE. THIS WILL RESULT IN A SPLIT AS SOON AS THE PIPE IS PLACED UNDER LOADING. ANY PIPE THAT HAS BEEN IMPACTED SHALL BE EXAMINED CLOSELY FOR THIS TYPE OF DAMAGE.

2.

TRENCH, PIPE BEDDING, AND BACKFILL:

A.

THE CONTRACTOR SHALL HAVE APPROPRIATE EQUIPMENT ON-SITE TO PRODUCE A DRY, FIRM, SMOOTH, UNDISTURBED SUBGRADE AT THE TRENCH BOTTOM THAT IS TRUE TO LINE AND GRADE. THE TRENCH BOTTOM SHALL BE FREE OF LOOSE MATERIALS OR TOOTH GROOVES FOR THE ENTIRE TRENCH WIDTH PRIOR TO PLACING PIPE BEDDING MATERIAL.

B.

THE CONTRACTOR SHALL FURNISH AND INSTALL SUFFICIENT TRENCH BOXES, SHORING, SHEETING OR BRACING TO INSURE THE SAFETY OF WORKMEN AND THE PUBLIC, PROTECT THE WORK, AND PROTECT EXISTING FACILITIES.

I.

SHORING, SHEETING, AND BRACING SHALL COMPLY WITH OSHA RULES, ORDERS AND REGULATIONS.

II.

WHERE REQUIRED BY OSHA, THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE DRAWINGS AND/OR CALCULATIONS FOR SPECIALLY DESIGNED BRACING AND SHORING, PREPARED AND STAMPED BY A HAWAI'I REGISTERED PROFESSIONAL ENGINEER, TO THE WWD A MINIMUM OF FIVE (5) WORKING DAYS PRIOR TO BEGINNING ASSOCIATED EXCAVATION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE ADEQUACY OF ALL SHEETING, SHORING AND BRACING AND COMPLIANCE WITH THE LAW. FAILURE OF THE INSPECTOR TO SUSPEND THE WORK OR NOTIFY THE CONTRACTOR OF ANY INADEQUACY OF SHEETING, SHORING OR BRACING OR NONCOMPLIANCE WITH THE LAW SHALL NOT RELIEVE THE CONTRACTOR OF THIS RESPONSIBILITY.

III.

THE CONTRACTOR SHALL FURNISH AND MAINTAIN SHORING, SHEETING AND BRACING UNTIL AFTER THE PIPELINE AND APPURTENANCES HAVE BEEN INSTALLED AND THE INSPECTOR HAS APPROVED THE PLACEMENT OF SUFFICIENT BACKFILL. THE CONTRACTOR SHALL PROVIDE ADEQUATE SAFETY MEASURES TO ALLOW FOR ACCESS BY THE INSPECTOR OR TESTING PERSONNEL TO PERFORM COMPACTION TESTING AND INSPECTION OF THE LIFTS OF BACKFILL PLACED.

C.

NO TRENCHES IN THE ROADS OR DRIVEWAYS SHALL BE LEFT OPEN OVERNIGHT, ALL SUCH TRENCHES SHALL BE PLATED OR CLOSED AND NORMAL TRAFFIC FLOW RESTORED BEFORE THE END OF EACH WORK DAY.

I.

THE STEEL TRENCH PLATES SHALL BE CAPABLE OF SUPPORTING HS-20 LOADING.

II.

THE PLATES MUST EXTEND BEYOND THE EDGE OF THE TRENCH WALL FAR ENOUGH TO ADEQUATELY SUPPORT HS-20 TRAFFIC LOADS. IN NO CASE SHALL THE PLATES EXTEND LESS THAN TWELVE (12) INCHES BEYOND THE TRENCH WALL.

III.

EACH PLATE MUST BE FULLY SUPPORTED AROUND ITS' PERIMETER TO PREVENT WOBBLING OR ROCKING.

VI.

THE PLATES SHALL BE SECURED TO PREVENT ANY MOVEMENT.

V.

TRENCHES AND EXCAVATIONS BENEATH THE PLATES SHALL BE ADEQUATELY SHORED AND BRACED TO WITHSTAND HS-20 TRAFFIC LOADS.

VI.

TEMPORARY PAVING OR COLD MIX ASPHALTIC CONCRETE (OUTBACK) SHALL BE PLACED AND CONTINUOUSLY MAINTAINED AROUND ALL OUTSIDE EDGES OF THE TRENCH PLATES UNTIL THEY ARE REMOVED.

D.

TRENCHES SHALL BE PROPERLY BACKFILLED AND COMPACTED AS SHOWN ON THE APPROVED PLAN.

E.

PIPE BEDDING SHALL BE CLASS B 3/4" AGGREGATE BASE COURSE PLACED WITHIN THE DRY TRENCH, AT NOT LESS THAN 4 INCHES BUT NOT MORE THAN 5 INCHES IN COMPACTED THICKNESS. BEDDING SHALL BE COMPACTED TO 95 PERCENT MAXIMUM DRY DENSITY, UNLESS OTHERWISE NOTED ON PLANS, TO AVOID STRESS CONCENTRATIONS AND ASSOCIATED IRREGULAR PIPE DEFORMATIONS. RECESSES CONSTRUCTED IN THE BEDDING, FOLLOWED BY HAND COMPACTION OF BACKFILL AROUND THE BELLS, WILL PROVIDE CONTINUOUS LONGITUDINAL SUPPORT AND UNIFORM BEARING BELOW THE PIPE JOINTS.

F.

THE REMAINDER OF THE PIPE EMBEDMENT SHALL ALSO BE CLASS B 3/4" AGGREGATE BASE COURSE PROPERLY PLACED, IN LIFTS NOT TO EXCEED 6", AROUND THE PIPE HAUNCHES AND EXTENDING TO A MINIMUM OF 12" COMPACTED THICKNESS OVER THE TOP OF THE PIPE. PIPE ZONE EMBEDMENT SHALL BE COMPACTED TO A 95 PERCENT MAXIMUM DRY DENSITY, UNLESS OTHERWISE NOTED ON PLANS, TO PROVIDE ADEQUATE SIDE SUPPORT AND ENSURE THE PIPE'S FULL STRENGTH IS ACHIEVED WHILE AVOIDING PIPE DEFLECTION, VERTICAL AND LATERAL DISPLACEMENT.

G.

CONTROLLED LOW-STRENGTH MATERIAL (CLSM) SHALL BE USED AS THE FINAL BACKFILL UNLESS OTHERWISE NOTED ON THE PLAN OR APPROVED IN WRITING BY THE WWD ENGINEER.

H.

COMPACTION TESTING FOR BEDDING AND EMBEDMENT MATERIALS FOR SEWER MAIN INSTALLATION SHALL BE PERFORMED BY AN INDEPENDENT TESTING AND QUALITY CONTROL LABORATORY. COMPACTION TEST FREQUENCY SHALL BE A MINIMUM OF ONE (1) TEST PER 150 LINEAL FEET PER LIFT OR A FRACTION THEREOF ON ALTERNATING SIDES OF THE PIPE OR STRUCTURE. THE ENGINEER RESERVES THE RIGHT TO INCREASE OR DECREASE THE FREQUENCY OF COMPACTION TESTING TO MATCH FIELD CONDITIONS. TEST RESULTS SHALL BE SUBMITTED TO THE WWD ENGINEER FOR EVALUATION AS PART OF THE FINAL ACCEPTANCE PROCESS.

3.

SEWER MANHOLES AND APPURTENANCES:

A.

ALL PRECAST CONCRETE SEWER MANHOLES SHALL CONFORM TO THE LATEST VERSION OF ASTM C478.

B.

ALL SEWER MANHOLE BASE, SECTIONS, CONE, FLAT TOP, BENCHES, AND CHANNELS SHALL INCLUDE A CONCRETE WATERPROOFING, PROTECTION, AND IMPROVEMENT ADMIXTURE. ADMIXTURE SHALL BE XYPEX ADMIX C-1000 OR APPROVED EQUAL PRODUCT. DOSAGE SHALL BE PER MANUFACTURER'S INSTRUCTION AND SHALL NOT BE LESS THAN 3% OF THE WEIGHT OF THE PORTLAND CEMENT FRACTION OF THE MIX.

C.

ALL DROP SEWER MANHOLES, TRANSITIONAL SEWER MANHOLE (RECEIVING MANHOLE AND THE NEXT TWO MANHOLES DOWNSTREAM FROM THE DISCHARGE OF A FORCE MAIN), AND SEWER MANHOLE(S) WITH CONNECTING PIPES GREATER THAN OR EQUAL TO 12 INCHES NOMINAL DIAMETER SHALL ALSO BE LINED WITH A PVC LINER, DURA-PLATE OR AN APPROVED EQUAL PRODUCT.

CHIEF, WASTEWATER DIVISION

DATE

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IŌPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CONSTRUCTION NOTES 3			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.

SHEET 4 OF 68 SHEETS



Last Save by: MLUM  
Last Saved: 10/25/2019  
Plotted on: 3/9/2020  
G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Construction Notes 4.dwg

SEWER SYSTEM REQUIREMENTS (CON'T):

- I.

ALL CONSTRUCTED (CAST-IN-PLACE) SEWER MANHOLE BENCHES AND CHANNELS SHALL BE COATED USING XYPEX MEGAMIX I OR AN APPROVED EQUAL PRODUCT.

II.

SEWER MANHOLE CHANNELS, INCLUDING THOSE AT CONNECTIONS TO EXISTING MANHOLES, SHALL PROVIDE A SMOOTH TRANSITION BETWEEN INLET AND OUTLET SEWERS. THE ANGLE BETWEEN THE INLET AND OUTLET SHALL BE A MINIMUM OF 90 DEGREES.

III.

UNLESS OTHERWISE APPROVED OR NOTED, ALL MANHOLES FOR CONNECTING SEWER LINES LESS THAN OR EQUAL TO 12-INCH NOMINAL DIAMETER SHALL BE PROVIDED WITH "ECCENTRIC" CONE SECTION WITH TYPE SA FRAMES AND COVERS (STD. DETAIL S-22).

IV.

UNLESS OTHERWISE APPROVED OR NOTED, ALL MANHOLES WITH CONNECTING SEWER LINES GREATER THAN 12-INCH NOMINAL DIAMETER OR LESS THAN 5 FEET DEEP SHALL BE PROVIDED WITH A FRAME AND COVER WITH A MINIMUM 48" CLEAR OPENING. THE 52-INCH COVER SHALL HAVE A SMALLER 25-5/16-INCH COVER INSTALLED FOR ROUTINE MAINTENANCE AND INSPECTION. THE SMALLER COVER SHALL BE PROVIDED WITH RECESSED STAINLESS STEEL BOLTS TO ALLOW SECURING. PERMANENT ALIGNMENT MARKS (MATCH MARKS) SHALL BE PROVIDED FOR THE BOLTS TO FACILITATE REINSTALLATION OF THE COVER. THE FRAME AND COVER SHALL BE AN ECCENTRIC CONFIGURATION, D&L FOUNDRY & SUPPLY; MODEL A-1428 OR APPROVED EQUAL.

V.

A FLEXIBLE PIPE TO MANHOLE CONNECTOR SHALL BE USED WHENEVER A PIPE PENETRATES INTO A PRECAST CONCRETE MANHOLE OR STRUCTURE. CONNECTIONS SHALL BE WATER-TIGHT AND SHALL PROVIDE FOR SMOOTH FLOW INTO AND THROUGH THE MANHOLE WITH NO PONDING.

VI.

NEW SEWER PIPE CONNECTIONS TO NEW MANHOLES SHALL BE WITH AN APPROVED CAST-IN-PLACE MANHOLE PIPE ADAPTER (A-LOK, ECONOSEAL, OR APPROVED EQUAL PRODUCT).

VII.

EXISTING SEWER PIPE CONNECTIONS TO NEW MANHOLES SHALL BE WITH AN APPROVED MANHOLE PIPE ADAPTER (A-LOK FIELD SLEEVE OR APPROVED EQUAL PRODUCT).

VIII.

SEWER PIPE CONNECTIONS TO EXISTING MANHOLES SHALL BE WITH AN APPROVED MANHOLE PIPE ADAPTER (A-LOK FIELD SLEEVE OR APPROVED EQUAL PRODUCT). OPENINGS FOR NEW CONNECTIONS TO EXISTING MANHOLES SHALL BE CORE-DRILLED AND SURFACE ROUGHENED. SMALL CHIPPING HAMMERS OR SIMILAR LIGHT TOOLS MAY BE USED TO ENLARGE EXISTING OPENINGS OR SHAPE CHANNELS IN EXISTING MANHOLES. USE OF PNEUMATIC JACKHAMMERS OR OTHER HEAVY TOOLS WHICH COULD DAMAGE OR CRACK THE MANHOLE BASE IS PROHIBITED.

IX.

ONE HAND GRAB RUNG AT THE TOP OF THE MANHOLE SHALL BE STAINLESS STEEL TYPE "SA" PER DPW STANDARD DETAIL S-42. SEWER MANHOLE RUNGS SHALL BE TYPE "SP" COPOLYMER POLYPROPYLENE PLASTIC, BOWCO INDUSTRIES INC./MEADOW BURKE PART NO. 93810R IN ACCORDANCE WITH WASTEWATER STANDARD DETAIL WW-7.

X.

RUNGS AND ECCENTRIC CONES OR COVERS SHALL NOT BE ALIGNED ABOVE FLOW LINES. THEY SHALL BE PLACED ON THE SIDE OF THE MANHOLE WITH THE LARGEST SHELF.

XI.

SEWER MANHOLES LOCATED IN UNPAVED AREAS SHALL BE PROVIDED A REINFORCED 3000 PSI CLASS "A" CONCRETE COLLAR. THE REINFORCED CONCRETE COLLAR SHALL BE A MINIMUM OF 12" THICK, AND EXTEND A MINIMUM OF 12" BEYOND THE FRAME AND COVER. REINFORCEMENT SHALL CONSIST OF AT LEAST ONE (1) #4 BAR PLACED AT LEAST 3" CLEAR FROM THE EDGE OF CONCRETE AND WRAPPED AROUND THE MANHOLE TOP SECTION (WITH AT LEAST 15" LAP), CENTERED VERTICALLY IN THE COLLAR.

XII.

ALL MANHOLE SECTIONS SHALL BE JOINED USING RAM-NEK RN103 OR APPROVED EQUAL.

I.

SEWER LATERAL PIPE AND FITTINGS:

II.

NEW SEWER LATERALS AND CLEANOUTS SHALL BE 6" DIAMETER, WWD STANDARD PIPE AND FITTINGS.

III.

SEWER CLEANOUTS SHALL BE LOCATED IN THE COUNTY RIGHT-OF-WAY OR EASEMENT WITHIN ONE FOOT OF THE PROPERTY LINE OR BOUNDARY. THE CLEANOUT SHALL BE EASILY ACCESSIBLE (I.E. NOT BE BURIED OR LOCATED UNDER OR CLOSE TO ROCK WALLS, FENCES OR OTHER OBSTRUCTIONS.)

IV.

NEW HIGH FLOW AND/OR HIGH FOG (FAT, OIL, AND GREASE) POTENTIAL DISCHARGERS SHALL INSTALL A SEWER MANHOLE IN LIEU OF A CLEANOUT AT THE PROPERTY LINE.

V.

SEWER LATERAL CONNECTIONS TO AN EXISTING SEWER MAIN SHALL BE MADE WITH A WYE CONFIGURED FLEXIBLE SADDLE (FERNCO TSW-6 OR APPROVED EQUAL) ROTATED 45 DEGREES ABOVE THE MAIN SPRING LINE UNLESS OTHERWISE DIRECTED BY THE WWD.

VI.

SEWER LATERAL SADDLE CONNECTIONS AND CORED SEWER MAIN ENTRY, WHEN DIRECTED BY THE WWD, SHALL PROVIDE A SMOOTH TRANSITION AND UNOBSTRUCTED FLOW TO THE MAIN. SADDLES SHALL COMPLETELY OVERLAY THE CORED AREA ON THE MAIN. SADDLES SHALL BE SECURED TO THE MAIN WITH STAINLESS STEEL STRAPS AND JACKETED WITH CLASS B REINFORCED CONCRETE IN ACCORDANCE WITH DPW STANDARD DETAIL S-5. THE REINFORCED CONCRETE JACKET SHALL COMPLETELY ENCASE THE EXISTING SEWER MAIN, BE A MINIMUM OF 6" THICK, AND EXTEND A MINIMUM OF 6" EACH WAY BEYOND THE SADDLE.

I.

SEWER LINE ACCEPTANCE TESTS:

II.

THE CONTRACTOR SHALL PROVIDE AND PAY FOR ALL MATERIALS, EQUIPMENT, AND FACILITIES NECESSARY FOR TESTING ALL UTILITY BACKFILL, PIPE AND STRUCTURES IN ACCORDANCE WITH THESE PLANS AND COUNTY STANDARD SPECIFICATIONS AND REQUIREMENTS.

III.

ALL NEWLY INSTALLED SEWER MAINS AND LATERALS ARE SUBJECT TO LEAKAGE TESTING-AND CCTV INSPECTION PRIOR TO FINAL ACCEPTANCE AS DIRECTED BY THE WWD.

IV.

LEAKAGE TESTING SHALL BE ACCOMPLISHED IN ACCORDANCE WITH SECTION 21.3 D OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, SEPTEMBER 1986. ALL COSTS FOR SUCH TESTING SHALL BE BORNE BY THE CONTRACTOR.

V.

DEFLECTION TESTING WHEN REQUIRED BY WWD, SHALL BE ACCOMPLISHED IN ACCORDANCE WITH SECTION 21.3 E OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, SEPTEMBER 1986. ALL COSTS FOR SUCH TESTING SHALL BE BORNE BY THE CONTRACTOR.
- I.

AN INITIAL CCTV INSPECTION WILL BE PERFORMED BY THE COUNTY AT NO COST TO THE CONTRACTOR SUBJECT TO THE CONDITIONS BELOW.

II.

THE CONTRACTOR SHALL OBTAIN A COPY OF THE SEWER LINE ACCEPTANCE TEST CRITERIA FROM THE WWD PRIOR TO REQUESTING OR SCHEDULING A CCTV INSPECTION.

III.

THE CONTRACTOR SHALL ASSIST THE COUNTY IN THE PERFORMANCE OF THE CCTV INSPECTION, SHALL BE RESPONSIBLE FOR ALL TRAFFIC CONTROL REQUIREMENTS DURING CCTV INSPECTION, AND SHALL BE RESPONSIBLE FOR CLEANING AND REMOVING ALL DIRT, GRIT, ROCK, DEBRIS AND FOREIGN MATERIALS FROM THE PIPES AND MANHOLES PRIOR TO CCTV INSPECTION. IN THE EVENT THAT PIPES OR MANHOLES ARE FOUND TO HAVE BEEN INADEQUATELY CLEANED, THE COUNTY WILL TERMINATE THE CCTV INSPECTION. THE COST OF SUBSEQUENT CCTV INSPECTION(S) WILL BE CHARGED TO THE CONTRACTOR.

IV.

THE CONTRACTOR SHALL HAVE A SUPERVISORY REPRESENTATIVE PRESENT DURING PERFORMANCE OF THE CCTV INSPECTION.

V.

IF THE CCTV INSPECTION REVEALS CONDITIONS SUCH AS DENTS, OUT-OF-ROUND, ETC. THE WORK SHALL BE CONSIDERED DEFECTS AND SUBJECT TO REPAIR.

VI.

IF THE CCTV INSPECTION REVEALS PIPE SAGS EXCEEDING THE SEWER LINE ACCEPTANCE TEST CRITERIA BELOW THEY SHALL BE CONSIDERED DEFECTS SUBJECT TO CORRECTION OR A DEDUCTIVE PAYMENT FOR THE ENTIRE RUN OF THE PIPING FROM STRUCTURE-TO-STRUCTURE ACCORDING TO THE FOLLOWING TABLE:
- | SAG TOLERANCES |                |                            |                           |                         |
|----------------|----------------|----------------------------|---------------------------|-------------------------|
| PIPE SLOPE     | NOM. PIPE SIZE | COMPLIES W/ SPECIFICATIONS | 50% PAYMENT OF BID AMOUNT | RECONSTRUCTION REQUIRED |
| < 0.4%         | 6"             | < 1/2"                     | 1/2"-1"                   | > 1"                    |
|                | 8"             | < 1/2"                     | 1/2"-1"                   | > 1"                    |
|                | 10"            | < 1"                       | 1" - 1-1/2"               | > 1-1/2"                |
|                | 12"            | < 1"                       | 1" - 1-1/2"               | > 1-1/2"                |
|                | > 12"          | < 1"                       | 1" - 1-1/2"               | > 1-1/2"                |
| 0.4% TO 0.7%   | 6"             | < 1/2"                     | 1/2" - 1-1/2"             | > 1-1/2"                |
|                | 8"             | < 1/2"                     | 1/2" - 1-1/2"             | > 1-1/2"                |
|                | 10"            | < 1"                       | 1" - 2"                   | 2"                      |
|                | 12"            | < 1"                       | 1" - 2"                   | 2"                      |
|                | > 12"          | < 1"                       | 1" - 2"                   | 2"                      |
| >0.7%          | 6"             | < 1"                       | 1" - 1-1/2"               | > 1-1/2"                |
|                | 8"             | < 1"                       | 1" - 2"                   | > 2"                    |
|                | 10"            | < 1-1/2"                   | 1-1/2" - 2"               | > 2"                    |
|                | 12"            | < 1-1/2"                   | 1-1/2" - 2-1/2"           | > 2-1/2"                |
|                | >12"           | < 1-1/2"                   | 1-1/2" - 3"               | 3"                      |
- VI.

CCTV INSPECTIONS WILL BE RECORDED. IN THE EVENT THAT THE CONTRACTOR REQUESTS A COPY OF THE CCTV INSPECTION, THE CONTRACTOR WILL BE CHARGED FOR THE COPY AT A RATE OF \$25.00.

I.

FINAL PROJECT SUBMITTALS:

II.

A. "AS-BUILT" PLANS AND CERTIFIED EASEMENTS RECORDED WITH THE BUREAU OF CONVEYANCES, IF APPLICABLE ARE REQUIRED FOR FINAL CONTRACT ACCEPTANCE OF SEWER CONSTRUCTION BY WWD. UPON FINAL PROJECT INSPECTION AND DECLARATION OF SATISFACTORY COMPLETION BY THE WASTEWATER DIVISION CHIEF, SUBMIT TO WWD ONE (1) SET OF FIELD RECORD DRAWINGS AND ONE (1) SET OF "AS-BUILT" PLANS ONE (1) ELECTRONIC SET IN AUTOCAD 2009 OR NEWER VERSION AND ONE (1) ELECTRONIC SET IN ADOBE PDF FORMAT.

III.

B. IT IS MANDATORY THAT THE "AS-BUILT" PLANS SHOW CORRECTLY IDENTIFIED PROPERTY TMK NUMBERS, LOCATION OF SEWER MANHOLES, LATERALS, CLEANOUTS AND ALL OTHER MAJOR COMPONENTS OF THE WASTEWATER COLLECTION SYSTEM INCLUDING RIM AND INVERT ELEVATIONS AT ALL SEWER MANHOLES, LATERAL CONNECTIONS AT THE MAIN, AND LATERAL ELEVATIONS AT THE CLEANOUT. SUBMITTED DOCUMENTATION SHALL BE CERTIFIED BY A HAWAII LICENSED PROFESSIONAL LAND SURVEYOR ATTESTING TO THE LOCATION AND ELEVATIONS OF ALL MAJOR COMPONENTS OF THE WASTEWATER COLLECTION SYSTEM AS SHOWN ON THE AS-BUILT PLANS.
- EXISTING CONDITION ASSESSMENT:
- I.

THE CONTRACTOR SHALL KEEP ALL PROJECT ACTIVITIES WITHIN THE PROJECT AREA. IN THE EVENT THAT A PREVIOUSLY UNKNOWN ARCHAEOLOGICAL FEATURE, HISTORIC PROPERTY, OR HUMAN REMAINS (INCLUDING HUMAN SKELETAL REMAINS, CREMATIONS, CEREMONIAL OBJECTS, FUNERARY OBJECTS, BURIAL GOODS, ETC.) ARE EXPOSED BY CONSTRUCTION, THE CONTRACTOR SHALL CEASE WORK IN THE VICINITY IMMEDIATELY AND NOTIFY THE WWD, STATE OF HAWAI'I HISTORIC PRESERVATION DIVISION (SHPD), THE APPROPRIATE MEDICAL EXAMINER OR CORONER, AND THE APPROPRIATE POLICE DEPARTMENT, OF THE DISCOVERY. THE CONTRACTOR SHALL PROTECT THE AREA OF THE REMAINS WITH AN APPROPRIATE MATERIAL. THE CONTRACTOR SHALL COOPERATE WITH THE POLICE OR DEPARTMENT OF LAND AND NATURAL RESOURCES IN THE INVESTIGATION, RECORDING, PRESERVATION AND SALVAGE.
- CONCRETE NOTES
- I.

DESIGN AND CONSTRUCTION SHALL CONFORM TO THE LATEST "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE" OF THE AMERICAN CONCRETE INSTITUTE.

II.

ALL CONCRETE SHALL DEVELOP A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT THE AGE OF 28 DAYS UNLESS NOTED OTHERWISE.

III.

ALL REINFORCING SHALL BE ASTM A-615 GRADE 60.

IV.

ARRANGEMENT AND DETAILS OF REINFORCING STEEL, INCLUDING BAR SUPPORTS AND SPLICES, SHALL BE IN ACCORDANCE WITH THE LATEST ACI 315 DETAIL MANUAL.

V.

ALL SLAB REINFORCING SHALL HAVE A MINIMUM EXTENSION INTO THE SUPPORT IN ACCORDANCE WITH THE LATEST ACI CODE. IF SUCH EXTENSION IS NOT POSSIBLE, BARS SHOULD TERMINATE IN STANDARD HOOKS.

VI.

ALL REINFORCING SHALL LAP A MINIMUM OF 1.76 Ld AT SPLICES UNLESS OTHERWISE SHOWN. FOR TOP BARS INCREASE LAP BY A FACTOR OF 1.4.

BAR SIZE

TENSION DEVELOPMENT LENGTH

#3

12-INCHES

#4

12-INCHES

#5

15-INCHES

#6

19-INCHES

#7

26-INCHES

#8

35-INCHES

II.

WHEREVER IT IS NECESSARY TO SPLICE REINFORCEMENT OTHERWISE THAN IS SHOWN ON THE CONTRACT DRAWINGS, THE CHARACTER OF THE SPLICE SHALL BE AS SPECIFIED BY THE ENGINEER. SPLICING SHALL BE STAGGERED.

III.

HOOK BARS AT OPENINGS.

IV.

ALL EXPOSED EDGES AND CORNERS OF CONCRETE SHALL BE CHAMFERED 3/4-INCH UNLESS OTHERWISE NOTED.

V.

UNLESS OTHERWISE SHOWN, THE MINIMUM COVER FOR REINFORCING STEEL SHALL BE AS FOLLOWS:

CONCRETE CAST AGAINST THE EARTH

3 INCHES

CONCRETE EXPOSED TO EARTH OR WEATHER

2-1/2 INCHES

CONCRETE EXPOSED TO INTERIOR TANK ATMOSPHERE

2 INCHES

ALL OTHER EXPOSURES

1-1/2 INCHES

VI.

ALL REINFORCING MARKED CONTINUOUS (CONT.) ON THE PLANS SHALL BE LAPPED AS REQUIRED, UNDER NOTE NO. 6, AT ALL SPLICES, LAPS, CORNERS AND INTERSECTIONS.
- CHIEF, WASTEWATER DIVISION DATE
- 
- THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22
- |   |             |         |          |
|---|-------------|---------|----------|
|   |             |         |          |
| REVISION DATE   | DESCRIPTION | MADE BY | APPROVED |
| DEPARTMENT OF HAWAIIAN HOME LANDS<br>LA'I'OPUA VILLAGE 4 SUBDIVISION<br>PHASE 2 — HEMA<br>TAX MAP KEY: (3) 7-4-21:12 (PORTION)<br>KAILUA-KONA, NORTH KONA, HAWAII |             |         |          |
| CONSTRUCTION NOTES 4  |             |         |          |
| Approved:   |             |         |          |
| COUNTY ENGINEER, DPW, COUNTY OF HAWAII  |             | DATE    |          |
| AKINAKA & ASSOCIATES, LTD.<br>CONSULTING ENGINEERS  |             |         |          |
- SHEET 5 OF 68 SHEETS
- |      |        |        |     |
|------|--------|--------|-----|
| FILE | POCKET | FOLDER | NO. |
|      |        |        |     |




G:\DHHL11-02 Laipoua Village  
4\ACAD\DHHL1102-Construction Notes 5.dwg

Last Save by: LRS  
Last Saved: 6/5/2019  
Plotted on: 3/9/2020

ABBREVIATIONS

A	AREA
AC	ASPHALTIC CONCRETE
ACS	ACRES
ARV	AIR RELIEF VALVE
BC	BOTTOM OF CURB
BM	BENCHMARK
BMP	BEST MANAGEMENT PRACTICES
BV	BOTTOM VERTICAL
BVC	BEGIN VERTICAL CURVE
℄	CENTER LINE
CB	CATCH BASIN
CFS	CUBIC FEET PER SECOND
CLR	CLEARANCE
CO	CLEANOUT
CONC	CONCRETE
CONN	CONNECTION
DIA	DIAMETER
DPP	DEPARTMENT OF PLANNING AND PERMITTING
DPW	DEPARTMENT OF PUBLIC WORKS
DW	DRYWELL
ELEV	ELEVATION
EP	EDGE OF PAVEMENT
EPA	ENVIRONMENTAL PROTECTION AGENCY
EVC	END VERTICAL CURVE
EXIST	EXISTING
FE	FLANGE END
FG	FINISH GRADE
FH	FIRE HYDRANT
FIN	FINISH
FT	FEET
GV	GATE VALVE
H/HORIZ	HORIZONTAL
HECO	HAWAIIAN ELECTRIC COMPANY
HGL	HYDRAULIC GRADE LINE
HP	HIGH POINT
HT	HEIGHT
HTCO/HTEL	HAWAIIAN TELCOM
ID	INNER DIAMETER
INV	INVERT
IPT	IRON PIPE THREAD
LAT	LATERAL
LC	LENGTH OF CURVE
LF	LINEAR FOOT/FEET
LT	LEFT
MAX	MAXIMUM
MH	MANHOLE
MIN	MINIMUM
MJ	MECHANICAL JOINT
NGPC	NOTICE OF GENERAL PERMIT COVERAGE
NO.	NUMBER
NPDES	NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM
NTS	NOT TO SCALE
O/S	OFFSET
OC	ON CENTER
OSHA	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
℄	PROPERTY LINE
PAVT	PAVEMENT
PC	POINT ON CURVE
PE	PLAIN END
PI	POINT OF INTERSECTION
POC	POINT OF CONNECTION
PT	POINT, POINT ON TANGENT

PVC	POLYVINYL CHLORIDE
PVI	POINT OF VERTICAL INTERSECTION
Q	FLOW
R	RADIUS OF CURVE
R/W	RIGHT-OF-WAY
REINF	REINFORCED
RT	RIGHT
S	SOUTH, SEWER, SLOPE
SF	SQUARE FOOT
SHT	SHEET
SMH	SEWER MANHOLE
STA.	STATION
STD	STANDARD
STRUCT	STRUCTURAL
T	TOP
TC	TOP OF CURB
TEMP	TEMPORARY
THK	THICK
T.M.K.	TAX MAP KEY
TV	TOP VERTICAL
TYP	TYPICAL
V/VERT	VERTICAL
VB	VALVE BOX
W	WATER, WEST
W/	WITH
WL	WATER LINE
WSS	WATER SYSTEM STANDARD
WWD	WASTEWATER DIVISION




THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 – HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
ABBREVIATIONS			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

FILE	POCKET	FOLDER	NO.

Last Save by: MLUM  
Last Saved: 9/6/2019  
Plotted on: 3/9/2020  
G:\DHHL1-02 Laipua Village  
4\ACAD\DHHL1102-General Layout Plan.DWG





LEGEND

- E/W8- EXIST. WATER LINE
- W8- NEW WATER LINE
- E/D24- EXIST. DRAIN LINE
- D24- NEW DRAIN LINE
- e- EXIST. UTILITY/ELECT. LINE
- E/S8- EXIST. SEWER LINE
- S8- NEW SEWER LINE
- DOUBLE SERVICE SEWER LATERAL
- SINGLE SERVICE SEWER LATERAL
- FIRE HYDRANT
- 1 1/2" DOUBLE SERVICE WATER LATERAL W/ TYPE C CONNECTION FOR TWO 5/8" METERS
- 1" SINGLE SERVICE WATER LATERAL W/ TYPE A CONNECTION FOR ONE 5/8" METER
- LOT NUMBER
- AKAU/HEMA BOUNDARY LINE/PROJECT LIMITS
- TRANSFORMER
- NEW PRIVACY FENCE & GUARDRAIL
- NEW RETAINING WALL

NOTES:

- ALL LOTS TO BE SERVICED BY GRAVITY SEWER.
- WATER AND SEWER LATERALS FOR LOTS 85-108 MAY BE INSTALLED UNDER AN ADDITIVE ALTERNATE. HOWEVER, LOTS WILL NOT BE SERVICED UNTIL WATER IS AVAILABLE.
- IF LAVA TUBES ARE ENCOUNTERED DURING TRENCH EXCAVATION FOR SEWER LINES, CONTRACTOR SHALL NOTIFY AND COORDINATE WITH WWD.
- DUE TO LIMITED WATER AVAILABILITY, BASE BID WILL INCLUDE THE CONSTRUCTION OF UTILITIES AND ROADWAYS FOR OHEMAKAI ST EXT, ILIE'E PL, KOAIA ST, AND PUAKALA PL. KAWELU PL (LOTS 88 TO 108) WILL BE CONSTRUCTED UNDER THE FOLLOWING ADDITIVE ALTERNATIVE BID ITEMS:
  - BASE BID - GRADE LOTS, BLAST AND HAMMER UTILITY TRENCHES. BACKFILL WITH 6" MINUS.
  - ALTERNATE 1 - INSTALLATION OF SEWER AND DRAINAGE SYSTEM.
  - ALTERNATE 2 - INSTALLATION OF WATER MAIN. WATER LATERALS WILL NOT BE INSTALLED UNDER THIS PROJECT.
  - ALTERNATE 3 - INSTALLATION OF ELECTRICAL SYSTEM, ROADWAY, SIDEWALKS, AND SIGNAGE.


GENERAL LAYOUT PLAN  
SCALE: 1" = 100'



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7—4—21:12 (PORTION) KAILUA—KONA, NORTH KONA, HAWAII			
GENERAL LAYOUT PLAN			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			



Last Save by: MLUM  
Last Saved: 9/6/2019  
Plotted on: 3/9/2020  
G:\DHHL1-02 Laipua Village  
4\ACAD\DHHL1102-Utility Plan 1.DWG




### LEGEND

- E/W8- EXIST. WATER LINE
- W8- NEW WATER LINE
- E/D24- EXIST. DRAIN LINE
- D24- NEW DRAIN LINE
- E- EXIST. UTILITY/ELECT. LINE
- E/S8- EXIST. SEWER LINE
- S8- NEW SEWER LINE
- DOUBLE SERVICE SEWER LATERAL
- SINGLE SERVICE SEWER LATERAL
- FIRE HYDRANT
- 1 1/2" DOUBLE SERVICE WATER LATERAL W/ TYPE C CONNECTION FOR TWO 5/8" METERS
- 1" SINGLE SERVICE WATER LATERAL W/ TYPE A CONNECTION FOR ONE 5/8" METER
- TRANSFORMER
- LOT NUMBER
- SEWER FLOW DIRECTION
- AKAU/HEMA BOUNDARY LINE/PROJECT LIMITS

CHIEF, WASTEWATER DIVISION

DATE



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			


### UTILITY PLAN

Approved:	DATE
COUNTY ENGINEER, DPW, COUNTY OF HAWAII	
AKINAKA & ASSOCIATES, LTD.	
CONSULTING ENGINEERS	

FILE	POCKET	FOLDER	NO.





G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Erosion & Dust Control  
Plan.DWG  
Last Save by: LRS  
Last Saved: 12/17/2019  
Plotted on: 3/9/2020



- GRADING NOTES**
- 1 PROVIDE SILT FENCE AT BOTTOM OF SLOPE  
SEE DETAIL  $\frac{2}{10}$
  - 2 PROVIDE DUST SCREEN  
SEE DETAIL  $\frac{3}{10}$
  - 3 PROVIDE CATCH BASIN SEDIMENT CONTROL DEVICE  
SEE DETAIL  $\frac{1}{10}$
  - 4 PROVIDE 20' WIDE x 50' LONG GRAVEL INGRESS/EGRESS FOR VEHICULAR ACCESS  
8" THICK #3 GRAVEL

- LEGEND**
- EXIST. CONTOURS
  - FINISH CONTOUR LINES
  - SILT FENCE
  - x DUST SCREEN
  - - - FUTURE LOT LINE
  - 17 LOT NUMBER
  - FLOW ARROW


**EROSION & DUST CONTROL PLAN**  
SCALE: 1" = 80'




REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
<b>EROSION &amp; DUST CONTROL PLAN</b>			
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.




G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Erosion Control  
Details.DWG  
Last Save by: LRS  
Last Saved: 2/17/2015  
Plotted on: 3/9/2020



1  
10 SEDIMENT CONTROL DEVICE  
FOR CATCH BASINS  
NOT TO SCALE



2  
10 SILT FENCE INSTALLATION  
NOT TO SCALE




NOTE:

DUST SCREEN SHALL BE MAINTAINED FOR  
DURATION OF CONSTRUCTION AND  
REMOVED UPON ITS COMPLETION.

3  
10 DUST SCREEN DETAIL  
NOT TO SCALE



NOTES TO CONTRACTOR:

- CONTRACTOR SHALL MAINTAIN SEDIMENT BARRIERS AND/OR TRAPS.
- CONTRACTOR SHALL MAINTAIN ALL TEMPORARY BMP MEASURES UNTIL THE ENTIRE AREA IS COMPLETELY STABILIZED. ALL BMP MEASURES SHALL BE REMOVED IMMEDIATELY AFTER THE AREA IS COMPLETELY STABILIZED.




REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
EROSION CONTROL DETAILS			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.


Last Save by: LRS  
Last Saved: 8/22/2017  
Plotted on: 3/9/2020  
G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Grading Details.DWG



**A**  
11  
TYPICAL LOT GRADING DETAIL  
NOT TO SCALE



**B**  
11  
TYPICAL LONGITUDINAL SECTION OF PROPERTY  
NOT TO SCALE





THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
TYPICAL LOT GRADING DETAILS			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD.			
CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.




Last Save by: LRS  
Last Saved: 6/25/2019  
Plotted on: 3/9/2020  
G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Typical Sections.DWG



CHIEF, WASTEWATER DIVISION

DATE




THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
TYPICAL SECTIONS			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

4' 0 4' 8'


SCALE: 1/4" = 1'-0"



- LEGEND**
- 440 --- EXIST. CONTOURS
  - 440 --- FINISH CONTOUR LINES
  - FUTURE LOT LINE
  - ① 7 LOT NUMBER
  - 442.94 FINISH SPOT GRADE
  - eg/ts EXISTING GROUND/TOP OF SIDEWALK
  - NEW 2:1 SLOPE
  - FLOW DIRECTION
  - SWALE

FOR CONTINUATION SEE SHEET 14

**GRADING PLAN 1**  
SCALE: 1" = 40'




**EARTHWORK QUANTITIES**

EXC. = 38,880 CU. YDS.  
EMB. = 31,300 CU. YDS.  
AREA TO BE GRADED = 27.3 ACS.

**NOTES:**

1. EARTHWORK QUANTITIES ARE FOR GRADING PERMIT PURPOSES.
2. QUANTITIES DO NOT INCLUDE SHRINKAGE AND GRUBBING LOSSES.
3. CONTRACTOR SHALL VERIFY EXIST SITE CONDITIONS PRIOR TO BID.
4. SEE TYPICAL LOT GRADING DETAILS, SHEET 11 FOR SWALE DETAILS.




THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA—KONA, NORTH KONA, HAWAII			
GRADING PLAN 1			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			



Last Save by: LRS  
Last Saved: 8/22/2017  
Plotted on: 3/9/2020  
G:\DHHL1-02 Laipua Village  
4\ACAD\DHHL1102-Grading Plan 2.DWG

TRUE NORTH  
SCALE: 1" = 40'



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOPIUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
GRADING PLAN 2			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.




TRUE NORTH  
SCALE: 1" = 40'

LEGEND

- 440 --- EXIST. CONTOURS  
--- 440 --- FINISH CONTOUR LINES  
--- FUTURE LOT LINE  
(17) LOT NUMBER  
442.94 FINISH SPOT GRADE  
eg/ts/tb EXISTING GROUND/TOP OF SIDEWALK/TOP OF BANK  
TW/FF/BF/BW TOP WALL/FRONT FACE/BOTTOM FACE/BOTTOM WALL  
YY NEW 2:1 SLOPE  
--- FLOW DIRECTION  
--- SWALE


NOTE:  
SEE TYPICAL LOT GRADING DETAILS, SHEET 11 FOR  
SWALE DETAILS.

FOR CONTINUATION SEE SHEET 14



GRADING PLAN 3  
SCALE: 1" = 40'



40' 0 40' 80'  
SCALE: 1" = 40'-0"



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IO'UA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
GRADING PLAN 3			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.



Last Save by: LRS  
Last Saved: 6/26/2019  
Plotted on: 3/9/2020  
G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Plan & Profile-Road B-1  
1.DWG






Last Save by: LRS  
 Last Saved: 6/26/2019  
 Plotted on: 3/9/2020  
 G:\DHHL11-02 Laiopua Village  
 4\ACAD\DHHL1102-Plan & Profile-Road B-1  
 2.DWG


G:\DHHL11-02 Laioopua Village  
4\ACAD\DHHL1102-Plan & Profile-Road B-1  
3.DWG  
Last Save by: LRS  
Last Saved: 6/27/2019  
Plotted on: 3/9/2020

TRUE NORTH  
SCALE: 1" = 20'






CHIEF, WASTEWATER DIVISION

DATE



**NOTES:**



- SEWER LATERAL SLOPES SHALL BE 1% MIN, 2% MAX. FOR SEWER LATERALS DEEPER THAN 6 FEET AT THE LOT BOUNDARY, ADVANCED RISER CONNECTIONS SHALL BE INSTALLED PER DETAIL 6/41
- ALL SEWER CLEANOUT FRAMES AND COVERS SHALL BE TRAFFIC RATED.
- ALL SEWER LINES ARE GRAVITY LINES.




REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
PLAN & PROFILE OHEMAKAI ST EXTENSION (ROAD "B-1") STA. 10+00 TO END			
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____ AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			




G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Plan & Profile-Road G-1  
1.DWG  
Last Save by: LRS  
Last Saved: 10/23/2019  
Plotted on: 3/9/2020




Last Save by: LRS  
Last Saved: 6/26/2019  
Plotted on: 3/9/2020  
G:\DHHL1-02 Laioopua Village  
4\ACAD\DHHL1102-Plan & Profile-Road G-1  
2.DWG



PLAN - KOAI'A ST 5+00 TO END  
SCALE: 1" = 20'



PROFILE - KOAI'A ST 5+00 TO END  
SCALE: 1" = 20' (HORIZ.)  
1" = 4' (VERT.)



REVISION DATE	DESCRIPTION	MADE BY	APPROVED

DEPARTMENT OF HAWAIIAN HOME LANDS  
LA'IOPIUA VILLAGE 4 SUBDIVISION  
PHASE 2 - HEMA  
TAX MAP KEY: (3) 7-4-21:12 (PORTION)  
KAILUA-KONA, NORTH KONA, HAWAII



**PLAN & PROFILE**  
**KOAI'A ST (ROAD "G-1")**  
**STA. 5+00 TO END**

Approved: \_\_\_\_\_  
COUNTY ENGINEER, DPW, COUNTY OF HAWAII  
DATE: \_\_\_\_\_  
AKINAKA & ASSOCIATES, LTD.  
CONSULTING ENGINEERS

FILE	POCKET	FOLDER	NO.



G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Plan & Profile-Road H-1  
1.DWG  
Last Save by: KNL  
Last Saved: 4/4/2019  
Plotted on: 3/9/2020










TRUE NORTH  
SCALE: 1" = 20'



PLAN - KAWELU PL 5+00 TO END

SCALE: 1" = 20'

ALT BID 2  
SEWER NOTES

- S1 STA 6+32.06 O/S 5' RT C KAWELU PL  
CONSTRUCT SMH "F-4"  
TOP=497.60  
INV=491.47 (6" IN, 8" OUT)

ALT BID 3  
WATER NOTES

- W1 STA 5+50 O/S 11' LT @ KAWELU PL  
DEFLECT PIPE
- W2 STA 6+86.05 O/S 11' LT @ KAWELU PL  
CONN NEW 8" PIPE TO EXIST 8" PIPE  
REMOVE & SALVAGE:  
1 - 8" CAP  
1 - 2" CO & BOX  
1 - CONC BLOCK  
INSTALL:  
1 - 8" SLEEVE, 12" LONG  
TEMP FOR TESTING:  
1 - 8" CAP, TAPPED FOR 2" IPT  
1 - 2" CO  
1 - CONC BLOCK

ALT BID 4  
ROAD NOTES


- R1 STA 6+86.05 @ KAWELU PL  
END KAWELU PL  
REMOVE EXIST CONC HEADER AND  
END ROAD BARRIER W/MARKERS
- R2 STA 6+86.05 @ KAWELU PL  
MATCH NEW CURB, GUTTER AND  
SIDEWALK TO EXIST
- R3 STA 6+88.05 @ KAWELU PL  
PROVIDE SMOOTH RIDING CONNECTION  
SEE DETAIL SHT 41
- R4 EXIST ST MON  
STA 7+31.05 @ KAWELU PL  
= STA 9+88.65 @ KO'OKO'OLAU ST  
TOP OF PIN EL=498.49

NOTES:

1. DUE TO LIMITED WATER AVAILABILITY, BASE BID WILL INCLUDE THE CONSTRUCTION OF UTILITIES AND ROADWAYS FOR OHEMAKAI ST EXT, ILIE'E PL, KOAIA ST, AND PUAkala PL. KAWELU PL (LOTS 88 TO 108) WILL BE CONSTRUCTED UNDER THE FOLLOWING ADDITIVE ALTERNATIVE BID ITEMS:  
BASE BID       — GRADE LOTS, BLAST AND HAMMER UTILITY TRENCHES. BACKFILL WITH 6" MINUS.  
ALTERNATE 1 — INSTALLATION OF SEWER AND DRAINAGE SYSTEM.  
ALTERNATE 2 — INSTALLATION OF WATER MAIN. WATER LATERALS WILL NOT BE INSTALLED UNDER THIS PROJECT.  
ALTERNATE 3 — INSTALLATION OF ELECTRICAL SYSTEM, ROADWAY, SIDEWALKS, AND SIGNAGE.
2. ALL SEWER LINES ARE GRAVITY LINES.


CHIEF, WASTEWATER DIVISION

DATE \_\_\_\_\_



## PROFILE – KAWELU PL

SCALE: 1" = 20' (HORIZ.)  
1" = 4' (VERT.)




REVISION	DATE	DESCRIPTION	MADE BY
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA—KONA, NORTH KONA, HAWAII			
PLAN & PROFILE KAWELU PL (ROAD "F") STA. 5+00 TO END			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII	DATE		
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

FILE	POCKET	FOLDER	NO.

Last Save by: LRS  
 Last Saved: 1/9/2020  
 Plotted on: 3/9/2020




Last Save by: LRS  
Last Saved: 6/27/2019  
Plotted on: 3/9/2020




**PUAKALA PL**  
SCALE: 1" = 20'

TRUE NORTH  
SCALE: 1" = 20'




**OHEMAKAI ST / KOAI'A ST**  
SCALE: 1" = 20'

TRUE NORTH  
SCALE: 1" = 20'





**OHEMAKAI ST / KAWELU PL**  
SCALE: 1" = 20'

TRUE NORTH  
SCALE: 1" = 20'



**OHEMAKAI ST / PUAKALA PL**  
SCALE: 1" = 20'

NOTE: ELEVATIONS SHOWN ARE BOTTOM OF CURB.





THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CURB RETURN GRADES			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.




G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Knuckle Detail.DWG  
Last Save by: LRS  
Last Saved: 2/26/2015  
Plotted on: 3/9/2020




CURB RAMP AND SIDEWALK NOTES:

1. THESE TYPICAL DETAILS ARE INTENDED AS CURB RAMP GUIDELINES FOR DESIGN AND CONSTRUCTION.
2. A 2% MAXIMUM CROSS SLOPE SHALL BE MAINTAINED IN THE DIRECTION OF PEDESTRIAN TRAFFIC.
3. SUBJECT TO FIELD CONDITIONS, THE ENGINEER SHALL DETERMINE THE FINAL LOCATION OF CURB RAMPS. WHEN NECESSITATED BY EXISTING PHYSICAL CONDITIONS, ALTERNATE CURB RAMPS MAY BE USED SUBJECT TO THE ENGINEER'S APPROVAL.
4. ALL PULLBOXES SHALL BE INSTALLED AWAY FROM THE CURB RAMP AND WITHIN THE SIDEWALK/UNPAVED AREA TO THE MAXIMUM EXTENT FEASIBLE.
5. WHERE NECESSARY, EXISTING PULLBOXES, HANDHOLES, MANHOLES, ETC. SHALL BE ADJUSTED TO MATCH CURB RAMP GRADE. ADJUSTMENTS SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO THE VARIOUS CURB RAMP ITEMS UNLESS INDICATED OTHERWISE.
6. TRANSITIONS FROM RAMPS TO GUTTERS AND ROADWAYS SHALL BE FLUSH.
7. CURB RAMPS AND SIDEWALKS SHALL BE CONSTRUCTED TO ELIMINATE PONDING TO THE MAXIMUM EXTENT FEASIBLE.
8. FOR AN EXISTING SIDEWALK, ENTIRE SIDEWALK BETWEEN NEAREST SCORE LINES SHALL BE REMOVED. FOR CURBS > 6" HIGH, FLARES SHALL BE CONSTRUCTED AT A MAX. RATIO OF 12H:1V. HOWEVER, IF "X" >= 48", FLARES SHALL BE CONSTRUCTED AT A MAX. RATIO OF 10H:1V.
9. THE MAXIMUM SLOPES OF ADJOINING GUTTERS OR ROAD SURFACE IMMEDIATELY FRONTING THE CURB RAMP SHALL NOT EXCEED 5%.
10. THERE SHALL BE A 30"x48" LEVEL GROUND SURFACE (2% MAX. CROSS SLOPE, BOTH DIRECTIONS) FOR A FORWARD OR SIDE APPROACH, AS APPROPRIATE, TO A PEDESTRIAN PUSH BUTTON.
11. CONSTRUCTION JOINTS ARE REQUIRED TO JOIN CURB RAMPS WITH SIDEWALKS.
12. UNLESS OTHERWISE NOTED, NEW GUTTERS ARE REQUIRED AS SHOWN.
13. ALL CURB RAMPS SHALL BE REINFORCED WITH 6X6 W1.4/W1.4 WELDED WIRE FABRIC.
14. SURFACE OF SIDEWALKS AND CURB RAMPS SHALL BE FIRM, STABLE, AND SLIP-RESISTANT. THIS INCLUDES THE SURFACES OF PULLBOXES, VALVE COVERS, MANHOLE COVERS, ETC.
15. BED COURSE MATERIAL IS REQUIRED FOR CURB RAMPS, SIDEWALKS, AND GUTTERS.
16. ALL SIDEWALKS SHALL PROVIDE A MINIMUM CLEAR WIDTH OF 3'-0" (EXCLUDING CURB) FOR PEDESTRIAN CIRCULATION. IF THIS CANNOT BE MET, A MINIMUM 32-INCH CLEAR WIDTH IS ALLOWED FOR A DISTANCE OF 24-INCHES.
17. PASSING SPACES ALONG NEW SIDEWALKS WITH LESS THAN 5' CLEAR WIDTH SHALL BE PROVIDED AT MAXIMUM 200' INTERVALS AS REQUIRED BY ADA GUIDELINES. THE PASSING AREA SHALL BE A MINIMUM 5' WIDE BY 5' LONG AS FEASIBLE.
18. IF POSSIBLE, INSTALL UTILITY POLES, FIRE HYDRANTS, LIGHT POLES, SIGN POSTS, PULLBOXES, ETC. OFF OF SIDEWALK BUT WITHIN THE RIGHT-OF-WAY.
19. OBJECTS PROTRUDING FROM UTILITY POLES AND WALLS ADJACENT TO THE SIDEWALKS (I.E. WALL MOUNTED FIRE HYDRANTS, TELEPHONES, METERS ON POLES, ETC.) SHALL BE MOUNTED TO MEET THE 2010 STANDARDS FOR ACCESSIBLE DESIGN SECTION 307 AND WILL BE SUBJECT TO ENGINEER'S APPROVAL.
20. IF A CURB RAMP IS NOT CONSTRUCTED ACCORDING TO THE PLANS, THE CONTRACTOR SHALL RECONSTRUCT THE CURB RAMP AT NO COST TO THE STATE. CONSTRUCTION TOLERANCE FOR PORTLAND CEMENT CONCRETE SHALL BE BASED ON 1/4 INCH PER 10 FT. (±0.2%). REMEDIAL MEASURES WILL NOT BE ACCEPTED.
21. ADDITIONAL INFORMATION IS AVAILABLE FROM:
  - A) AMERICAN WITH DISABILITIES ACT AND ARCHITECTURAL BARRIERS ACT ACCESSIBILITY GUIDELINES, JULY 23, 2004, UNITED STATES ACCESS BOARD.
  - B) ACCESSIBLE RIGHTS-OF-WAY: A DESIGN GUIDE, NOV. 1999, THE ACCESS BOARD.
  - C) DESIGNING SIDEWALKS AND TRAILS FOR ACCESS, PART 1, JULY 1999, FHWA.
  - D) DESIGNING SIDEWALKS AND TRAILS FOR ACCESS, PART 2, JULY 2001, FHWA.




\* SEE CURB RAMP AND SIDEWALK NOTE NO. 9.

\*\*THE SLOPE OF THE RAMP SHALL TAKE PRECEDENCE OVER THE LENGTH OF THE RAMP. IF THE MAXIMUM SLOPE OF A RAMP CANNOT BE MET WITHIN A LENGTH OF 15 FEET, THEN THE SLOPE OF THE RAMP SHALL BE SET WHEN THE LENGTH OF THE RAMP IS SET AT THE MAXIMUM OF 15 FEET.




PLAN



ELEVATION

1 CURB RAMP - TYPE "B" MODIFIED  
28 SIDEWALK WIDTH 6'-0" OR GREATER  
BUT LESS THAN 15'-0" WIDTH







THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA—KONA, NORTH KONA, HAWAII			
CURB RAMP DETAILS 1			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

FILE	POCKET	FOLDER	NO.
------	--------	--------	-----



Last Save by: MLUM  
Last Saved: 9/9/2019  
Plotted on: 3/9/2020  
G:\DHHL11-02 Laipuna Village  
4\ACAD\DHHL1102-Curb Ramp Details 3.DWG



CURVE DATA						
CURVE	①	②	③	④	⑤	⑥
Δ	44°27'24"	19°49'47"	11°02'06"	26°26'28"	32°48'14"	38°55'18"
Δ/2	22°13'42"	9°54'54"	5°31'03"	13°13'14"	16°24'07"	19°27'39"
R	26.00	26.00	26.00	26.00	26.00	26.00
T	10.63	4.55	2.51	6.11	7.65	9.19
C	19.67	8.95	5.00	11.89	14.68	17.32
Lc	20.17	9.00	5.00	12.00	14.89	17.66

CURVE DATA						
CURVE	⑦	⑧	⑨	⑩	⑪	⑫
Δ	43°02'57"	23°38'44"	32°50'31"	37°30'18"	44°48'20"	37°17'08"
Δ/2	21°31'28.5"	11°49'22"	16°25'16"	18°45'09"	22°24'10"	18°38'34"
R	26.00	26.00	26.00	26.00	26.00	20.00
T	10.26	5.44	7.66	8.83	10.72	6.75
C	19.08	10.65	14.70	16.72	19.82	12.79
Lc	19.54	10.73	14.90	17.02	20.33	13.02


CURVE DATA						
CURVE	⑬	⑭	⑮	⑯	⑰	⑱
Δ	31°34'12"	40°10'45"	45°42'	17°01'34"	18°25'19"	14°21'41"
Δ/2	15°47'06"	20°05'23"	22°51'	8°30'47"	9°12'40"	7°10'51"
R	26.00	26.00	26.00	26.00	20.00	20.00
T	7.35	9.51	10.96	5.44	3.24	2.52
C	14.15	17.86	20.19	10.65	6.40	5.00
Lc	14.33	18.23	20.74	10.73	6.43	5.01

CURVE DATA						
CURVE	⑲	⑳	㉑	㉒	㉓	㉔
Δ	23°35'53"	35°56'37"	20°21'43"	38°31'27"	23°39'22"	22°02'15"
Δ/2	11°47'57"	17°58'19"	10°10'52"	19°15'44"	11°49'41"	11°01'08"
R	20.00	20.00	20.00	20.00	20.00	26.00
T	4.18	6.49	3.59	7.00	4.19	5.06
C	8.18	12.34	7.07	13.20	8.20	9.94
Lc	8.24	12.55	7.11	13.45	8.26	10.00

GRAPHIC SCALE:



SCALE: 1" = 10'



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
<b>CURB RAMP DETAILS 2</b>			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
DATE: _____			


G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Driveway Details.DWG  
Last Save by: KNL  
Last Saved: 9/9/2019  
Plotted on: 3/9/2020

DRIVEWAY TIES		
LOT NUMBER	DRIVEWAY  STA.	DRIVEWAY WIDTH*
1	0+82.98 OHEMAKAI ST	16'
2	1+36.34 OHEMAKAI ST	16'
3	1+89.69 OHEMAKAI ST	16'
4	2+43.05 OHEMAKAI ST	16'
5	2+96.40 OHEMAKAI ST	16'
6	3+49.76 OHEMAKAI ST	16'
7	4+03.11 OHEMAKAI ST	16'
8	4+57.46 OHEMAKAI ST	16'
9	5+12.08 OHEMAKAI ST	16'
10	5+66.14 OHEMAKAI ST	16'
11	6+20.48 OHEMAKAI ST	16'
12	6+70.84 OHEMAKAI ST	16'
13	7+29.17 OHEMAKAI ST	16'
14	7+83.51 OHEMAKAI ST	16'
15	8+37.85 OHEMAKAI ST	16'
16	8+92.35 OHEMAKAI ST	16'
17	9+48.81 OHEMAKAI ST	13'
18	10+02.31 OHEMAKAI ST	16'
19	10+58.31 OHEMAKAI ST	14'
20	11+01.31 OHEMAKAI ST	16'
21	11+67.31 OHEMAKAI ST	16'
22	12+22.31 OHEMAKAI ST	16'
23	12+76.55 OHEMAKAI ST	16'
24	13+12.49 OHEMAKAI ST	16'
25	13+67.66 OHEMAKAI ST	16'
26 & 27	13+95.53 OHEMAKAI ST	24.40'
28	0+18.78 'ILIE'E PL	16.65'
29	0+71.37 'ILIE'E PL	16'
30	1+30.37 'ILIE'E PL	14'
31	1+91.37 'ILIE'E PL	16'
32	2+50.88 'ILIE'E PL	16'
33	3+09.77 'ILIE'E PL	16'
34	3+68.73 'ILIE'E PL	16'
35	4+24.21 'ILIE'E PL	16'
36	4+86.57 'ILIE'E PL	16'
37	5+40.58 'ILIE'E PL	16'
38	5+96.59 'ILIE'E PL	12'
39	6+48.61 'ILIE'E PL	16'
40	7+02.67 'ILIE'E PL	16'
41	7+54.66 'ILIE'E PL	16'
42	8+06.94 'ILIE'E PL	16'
43	8+52.27 'ILIE'E PL	16'
44	9+13.94 'ILIE'E PL	14'
45	9+48.94 'ILIE'E PL	16'
46	9+46.96 'ILIE'E PL	16'
47	9+10.96 'ILIE'E PL	16'
48	8+54.96 'ILIE'E PL	16'


\* DRIVEWAY WIDTHS EXCLUDE  
STANDARD DROP CURB WIDTHS

DRIVEWAY TIES		
LOT NUMBER	DRIVEWAY  STA.	DRIVEWAY WIDTH*
49	7+98.95 'ILIE'E PL	16'
50	7+38.17 'ILIE'E PL	16'
51	6+74.64 'ILIE'E PL	16'
52	6+05.74 'ILIE'E PL	16'
53	5+47.58 'ILIE'E PL	16'
54	4+84.05 'ILIE'E PL	16'
55	4+09.64 'ILIE'E PL	16'
56	3+32.16 'ILIE'E PL	16'
57	2+68.96 'ILIE'E PL	16'
58	1+96.41 'ILIE'E PL	16'
59	1+37.41 'ILIE'E PL	16'
60	0+75.41 'ILIE'E PL	16'
61	0+69.41 KOAI'A ST	16'
62	1+28.41 KOAI'A ST	16'
63	1+87.91 KOAI'A ST	16'
64	2+50.78 KOAI'A ST	16'
65	2+96.60 KOAI'A ST	16'
66	3+64.07 KOAI'A ST	16'
67	4+25.60 KOAI'A ST	16'
68	4+85.17 KOAI'A ST	16'
69	5+45.72 KOAI'A ST	16'
70	6+00.41 KOAI'A ST	16'
71	6+53.16 KOAI'A ST	16'
72	7+04.03 KOAI'A ST	14'
73	7+53.03 KOAI'A ST	16'
74	7+93.03 KOAI'A ST	16'
75	8+07.62 KOAI'A ST	16'
76	7+66.62 KOAI'A ST	16'
77	7+16.62 KOAI'A ST	16'
78	6+66.62 KOAI'A ST	16'
79	6+10.72 KOAI'A ST	16'
80	5+50.32 KOAI'A ST	16'
81	4+80.92 KOAI'A ST	16'
82	4+15.32 KOAI'A ST	16'
83	3+35.71 KOAI'A ST	16'
84	2+64.32 KOAI'A ST	16'
85	1+91.04 KOAI'A ST	16'
86	1+31.56 KOAI'A ST	14'
87	0+70.56 KOAI'A ST	16'
88	0+80.84 KAWELU PL	16'
89	1+38.72 KAWELU PL	16'
90	2+01.35 KAWELU PL	16'
91	2+61.36 KAWELU PL	16'
92	3+18.36 KAWELU PL	16'
93	3+81.16 KAWELU PL	16'
94	4+37.19 KAWELU PL	16'
95	4+91.09 KAWELU PL	16'

DRIVEWAY TIES		
LOT NUMBER	DRIVEWAY  STA.	DRIVEWAY WIDTH*
96	5+47.02 KAWELU PL	16'
97	6+03.02 KAWELU PL	16'
98	6+47.02 KAWELU PL	16'
99	6+54.05 KAWELU PL	16'
100	6+18.05 KAWELU PL	16'
101	5+68.05 KAWELU PL	16'
102	5+18.05 KAWELU PL	16'
103	4+54.45 KAWELU PL	16'
104	3+78.98 KAWELU PL	16'
105	2+96.85 KAWELU PL	16'
106	2+20.53 KAWELU PL	16'
107	1+39.36 KAWELU PL	16'
108	0+83.36 KAWELU PL	16'
109	0+79.07 PUAkala PL	16'
110	1+40.32 PUAkala PL	16'
111	1+96.83 PUAkala PL	16'
112	2+53.34 PUAkala PL	16'
113	3+07.97 PUAkala PL	16'
114	3+45.23 PUAkala PL	12'
115	4+22.09 PUAkala PL	16'
116	4+42.05 PUAkala PL	16'
117	4+17.75 PUAkala PL	16'
118	3+46.96 PUAkala PL	16'
119	3+09.60 PUAkala PL	16'
120	2+08.32 PUAkala PL	16'
121	0+99.06 PUAkala PL	16'
122	2+80.65 OHEMAKAI ST	16'
123	2+05.00 OHEMAKAI ST	16'
124	1+46.88 OHEMAKAI ST	16'
125	0+84.95 OHEMAKAI ST	16'
CBU LOT	4+44.14 PUAkala PL	23.21'




PLAN  
SCALE: 1" = 10'




ELEVATION  
SCALE: 1" = 4'


DRIVEWAY APRON DETAIL



SECTION A-A  
SCALE: 1" = 4'



ALTERNATE DETAIL  
SCALE: 1" = 4'



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7—4—21:12 (PORTION) KAILUA—KONA, NORTH KONA, HAWAII			
DRIVEWAY DETAILS			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			DATE
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

FILE	POCKET	FOLDER	NO.
------	--------	--------	-----




G:\DHHL11-02 Laioopua Village  
4\ACAD\DHHL1102-DRIVEWAY LAYOUT PLAN  
1.DWG  
Last Save by: MLUM  
Last Saved: 9/9/2019  
Plotted on: 3/9/2020

TRUE NORTH  
SCALE: 1" = 40'




DRIVEWAY LAYOUT PLAN 1  
SCALE: 1" = 40'



THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22


REVISION	DATE	DESCRIPTION	MADE BY      APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 – HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
DRIVEWAY LAYOUT PLAN 1			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

TRUE NORTH  
SCALE: 1" = 40'



G:\DHHL1-02 Laiopua Village  
4\ACAD\DHHL1102-DRIVEWAY LAYOUT PLAN  
2.DWG  
Last Save by: LRS  
Last Saved: 9/9/2019  
Plotted on: 3/9/2020

DRIVEWAY LAYOUT PLAN 2  
SCALE: 1" = 40'



THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
DRIVEWAY LAYOUT PLAN 2			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.



TRUE NORTH  
SCALE: 1" = 40'

FOR CONTINUATION SEE SHEET 32

FOR CONTINUATION  
SEE SHEET 32

KO'OKO'OLAU ST  
(BY OTHERS)

AKAU SUBDIVISION  
(BY OTHERS)

DRIVE

KEANALEHU

OHEMAKAI ST EXT

LIE'E



PLACE

STREET

MANAWALE'A


### DRIVEWAY LAYOUT PLAN 3

SCALE: 1" = 40'



THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
DRIVEWAY LAYOUT PLAN 3			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			



## TYPICAL INSTALLATIONS

HEIGHT & LATERAL LOCATION OF SIGN  
LOCATION FOR STOP SIGNS  
INTERSECTION DETAIL FOR STRIPING  
STRIPING DETAILS  
STREET NAME & SIGN DETAIL

DEPARTMENT OF  
PUBLIC WORKS  
COUNTY OF HAWAII'S  
STANDARD DETAIL

T-2  
T-3  
T-9  
T-10  
T-1


NOTE:

NOTE:

1. ALL REGULATORY SIGNS SHALL BE REFLECTORIZED WITH TYPE IV HIGH INTENSITY RETROREFLECTIVE SHEETING.
2. SEE TRAFFIC NOTES ON SHEET 3


REFERENCE:

MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR  
STREETS AND HIGHWAYS OF THE U.S. DEPARTMENT OF  
TRANSPORTATION, FEDERAL HIGHWAYS ADMINISTRATION,  
LATEST EDITION.



**NOTE:**  
SEE S  
REFER  
ADDIT  
STRIPI


### TYPICAL LOCAL STREET INTERSECTION STRIPING



## TYPICAL STOP LINE STRIPING

- 1 BLUE REFLECTIVE MARKER
- 2 INSTALL CROSS WALK, STOP LINE AND CENTERLINE STRIPING
- 3 INSTALL STOP LINE AND CENTERLINE STRIPING
- 4 INSTALL STOP LINE

Last Save by: LRS  
 Last Saved: 12/17/2019 G:\DHHL1-02 Laiopua Village  
 Plotted on: 3/9/2020 4\ACAD\DHHL1102-Signing and Striping.DWG



SCOTT A. KUNIOKA  
LICENSED  
PROFESSIONAL  
ENGINEER  
No. 7257-C  
HAWAII, U.S.A.

*Scott A. Kunioka*


THIS WORK WAS PREPARED  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF  
PROJECT WILL BE UNDER  
OBSERVATION  
LICENSE EXPIRES 4/30/2008

THIS WORK WAS PREPARED  
ME OR UNDER MY SUPERV  
AND CONSTRUCTION OF  
PROJECT WILL BE UNDER  
OBSERVATION  
LICENSE EXPIRES 4/30/

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA—KONA, NORTH KONA, HAWAII			
<h2 style="text-align: center;">SIGNING AND STRIPING</h2>			
<p>Approved:</p> <div style="display: flex; justify-content: space-between;"> <div>COUNTY ENGINEER, DPW, COUNTY OF HAWAII</div> <div>DATE</div> </div> <div style="text-align: center; margin-top: 20px;"> <b>AKINAKA &amp; ASSOCIATES, LTD.</b>  CONSULTING ENGINEERS </div>			


FILE	POCKET	FOLDER	NO.
------	--------	--------	-----






TYPICAL CROSSWALK STRIPING  
AT DIAGONAL CURB RAMP

CROSSWALK STRIPING DETAIL  
SCALE: NOT TO SCALE







OHEMAKAI STREET AND KOAI'A STREET  
INTERSECTION STRIPING DETAIL  
SCALE: NOT TO SCALE

Last Save by: LRS  
Last Saved: 12/17/2019  
Plotted on: 3/9/2020  
G:\DHHL11-02 Laiohua Village  
4\ACAD\DHHL1102-Curb Ramp Details 1.DWG






THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CURB RAMP STRIPING DETAILS			
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.



G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Sight Distance Details  
1.DWG  
Last Save by: KNL  
Last Saved: 3/12/2019  
Plotted on: 3/9/2020






GRAPHIC SCALE:  
50' 0 50' 100'  
SCALE: 1" = 50'-0"

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
SIGHT DISTANCE DETAILS 2			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.

SCOTT A. KUNIOKA  
LICENSED PROFESSIONAL ENGINEER  
No. 7257-C  
HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/22




**KO'OKO'OLAU ST / KOAI'A ST**  
SCALE: 1" = 50'

**KO'OKO'OLAU ST &  
KOAI'A ST  
SIGHT DISTANCE**  
(REF. AASHTO - A POLICY ON GEOMETRIC  
DESIGN OF HIGHWAYS AND STREETS 2004  
SECTION 9 - INTERSECTION CONTROL)

POSTED SPEED: 25 MPH  
DESIGN SPEED: 30 MPH

	D <sub>L</sub>	D <sub>R</sub>
REQUIRED	335	290
ACTUAL	N/A	290




**KO'OKO'OLAU ST / ILIE'E PL**  
SCALE: 1" = 50'

**KO'OKO'OLAU ST &  
ILIE'E PL  
SIGHT DISTANCE**  
(REF. AASHTO - A POLICY ON GEOMETRIC  
DESIGN OF HIGHWAYS AND STREETS 2004  
SECTION 9 - INTERSECTION CONTROL)


POSTED SPEED: 25 MPH  
DESIGN SPEED: 30 MPH

	D <sub>L</sub>	D <sub>R</sub>
REQUIRED	335	N/A
ACTUAL	335	N/A

GRAPHIC SCALE:



SCALE: 1" = 50'-0"




THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
SIGHT DISTANCE DETAILS 3			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD.			
CONSULTING ENGINEERS			





FILE	POCKET	FOLDER	NO.




Last Save by: KNL  
Last Saved: 4/4/2019  
Plotted on: 3/9/2020  
G:\DHHL11-02 Laipoua Village  
4\ACAD\DHHL1102-Water Details.DWG



- NOTES:
- SEE TABLE 300-1, PAGE 302-3, WATER SYSTEM STANDARDS 2002.
  - LOCAL MATERIAL MAY BE USED OUTSIDE SHOULDER AREA.
  - SEE TABLE 100-3, PAGE 102-4, WATER SYSTEM STANDARDS, 2002.
  - DRIVEWAY RESTORATION
    - WHERE EXISTING DRIVEWAY IS CONCRETE, 4" CONCRETE REINFORCED WITH 6x6x10/10 WMM ON 4" BASE COURSE SHALL BE USED IN LIEU OF THE ABOVE SECTION.
    - WHERE AN EXISTING DRIVEWAY IS UNPAVED, THE DRIVEWAY SHALL BE RESTORED TO A CONDITION EQUAL OR BETTER THAN THE EXISTING DRIVEWAY.
    - WHERE EXISTING DRIVEWAY IS PAVED, THE DRIVEWAY SHALL BE RESTORED AS SHOWN ABOVE.
    - CONTRACTOR SHALL NOTIFY THE OWNER OF THE DRIVEWAY 48 HOURS BEFORE THE COMMENCEMENT OF ANY WORK.




REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
WATER DETAILS			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			




PLAN - PRESSURE REDUCING VALVE STATION


SCALE: 1/2" = 1'-0"



A 40 SECTION SCALE: 1/2" = 1'-0"





"CHS2" HEAVY DUTY H-20 RATED INSULATED ALUMINUM HATCH - 60"x68" COVER PLAN SCALE: 1/2" = 1'-0"



TYPICAL WALL SECTION SCALE: 3/4" = 1'-0"

MATERIAL SCHEDULE	
ITEM	DESCRIPTION
1	4" PIPE, CUT-TO-FIT
2	4" 90° BEND, MJ WITH JOINT RESTRAINT
3	4" NIPPLE, CUT-TO-FIT
4	4" GATE VALVE, 150#, MJ
5	4" PIPE, PE, CUT-TO-FIT
6	4" FLANGED COUPLING ADAPTER
7	4" PRESSURE REDUCING/SUSTAINING VALVE, FE, CLA-VAL MODEL 92G-01 BYSP KCX X101
8	4" PIPE, FE x PE, 4'-0" LONG
9	4" x 2" DOUBLE STRAP SERVICE SADDLE
10	2" x 2 1/2" CORP STOP
11	2 1/2" FEMALE ADAPTER, C-F
12	2 1/2" PIPE, CUT-TO-FIT
13	2 1/2" MALE ADAPTER, C-M
14	2 1/2" BALL VALVE, SE
15	2 1/2" x 2" BUSHING
16	2" MALE ADAPTER, C-M
17	2" PIPE, 8" LONG
18	2" FORD LOCK PACK No. CF35-77
19	2" METER FLANGES, FORD No. CF31-77
20	2" CLOSE NIPPLE
21	2" PRESSURE REDUCING VALVE, SE, CLA-VAL MODEL 90G-01 ABS KCX X101
22	2 1/2" 90° ELBOW
23	4" x 1 1/2" DOUBLE STRAP SERVICE SADDLE
24	1 1/2" x 2" CORP STOP
25	2" UNION
26	2" x 2" x 1" TEE W/1" HOSE BIBB
27	2" STREET ELBOW
28	2" BALL VALVE, SE
29	2" PRESSURE RELIEF VALVE, SE, CLA-VAL MODEL 50G-01 BP KCX X101
30	2" PIPE, CUT-TO-FIT
31	2" ELBOW, C-C
32	1" AIR RELIEF VALVE
33	8" GATE VALVE, 150# MJ




- NOTES:
- CLAYTON VALVES SHALL BE EQUIPPED WITH EPOXY COATING INTERNALLY AND EXTERNALLY.
  - PRESSURE REDUCER SETTINGS: 4" = 50 PSI 2" = 55 PSI
  - CRD RANGE: 15 TO 75 PSI CRL RANGE: 20 TO 200 PSI



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOPIUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
PRESSURE REDUCING VALVE DETAILS			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			









**NOTES:**

1. CONCRETE JACKET MAY EXTEND TO TRENCH WALL FOR NARROW TRENCH. TRENCH WALL SHALL BE CUT VERTICAL AND NEAT.
2. FORMS SHALL BE USED FOR CONSTRUCTION OF CONCRETE JACKET IN WIDE TRENCH WITH CRUSHED ROCK BEDDING BACKFILL. FORMS SHALL BE REMOVED.

REINFORCED CONCRETE JACKET FOR  
PIPES 12-INCH AND SMALLER  
NOT TO SCALE



TYP. CHANNELIZATION OF  
SEWER MANHOLE

---

NOT TO SCALE

CHIEF, WASTEWATER DIVISION DATE

DEPARTMENT OF HAWAIIAN HOME LANDS  
LA'IOPIA VILLAGE 4 SUBDIVISION  
PHASE 2 - HEMA  
TAX MAP KEY: (3) 7-4-21:12 (PORTION)  
KAILUA-KONA, NORTH KONA, HAWAII

## SEWER DETAILS


Approved:	<div style="border-bottom: 1px solid black; height: 1.2em; margin-bottom: 5px;"></div> <div style="display: flex; justify-content: space-between; padding: 0 10px;"> <span>COUNTY ENGINEER, DPW, COUNTY OF HAWAII</span> <span>DATE</span> </div> <div style="text-align: center; padding: 10px 0;"> <b>AKINAKA &amp; ASSOCIATES, LTD.</b>  <b>CONSULTING ENGINEERS</b> </div>
-----------	--

SHEET 42 OF 68 SHEETS

FILE	POCKET	FOLDER	NO.


Last Save by: LRS  
 Last Saved: 6/25/2019  
 Plotted on: 3/9/2020






1  
43 DRYWELL DETAIL  
NOT TO SCALE


- NOTE:
1. CONTRACTOR SHALL TEST DRAINAGE CAPACITY OF DRYWELLS. TESTING SHALL CONFORM WITH CURRENT DOH STANDARDS AND RESULTS TO BE SUBMITTED TO ENGINEER AND DPW. TESTING RESULTS SHALL BE CERTIFIED BY A LICENSED GEOLOGIST IN THE STATE OF HAWAII.
  2. CONTRACTOR SHALL CONSTRUCT DRY WELL TO SPECIFIED DEPTH AND TEST EACH DRYWELL TO VERIFY CAPACITY OF 2 CFS. IF ADDITIONAL CAPACITY REQUIRED, CONTRACTOR SHALL DRILL 36" DIA CORING TO DEPTH REQUIRED TO PROVIDE 2 CFS CAPACITY.
  3. RING FOOTING TO BE USED IF WELL IS OVEREXCAVATED OR IF IN COMPRESSIBLE SOIL CONDITION.
  4. LEVELING GROUT (AT THE RING BASE ONLY) MAY BE USED ONLY WHEN ON SOLID ROCK.




2  
43 DRYWELL FOOTING DETAIL  
NOT TO SCALE




5  
43 SMOOTH RIDING CONNECTION DETAIL  
NOT TO SCALE



JOINT DETAIL




SECTION-C




ELEVATION

3  
43 PRECAST REINF. CONC. RING DETAILS  
SCALE: 1/2" = 1'-0"




PLAN

LOT #	APPROX. WALL HT.
3	10"
7	18"
13	18"
19	18"
24	18"
30	26"
35	30"
38	18"
43	10"
63	26"
70	20"
72	10"
110	26"
114	10"



SECTION A-A

4  
43 CMU WALL DETAIL FOR ELEC PAD  
NOT TO SCALE



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
MISCELLANEOUS DETAILS			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			



G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Grading Sections Key  
Map.DWG  
Last Save by: LRS  
Last Saved: 5/6/2019  
Plotted on: 3/9/2020



- LEGEND**
- 440--- EXIST. CONTOURS
  - 440--- FINISH CONTOUR LINES
  - FUTURE LOT LINE
  - (17) LOT NUMBER

**GRADING SECTION KEY MAP**

SCALE: 1" = 80'







THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
GRADING SECTION KEY MAP			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.






G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Grading Sections 1.DWG  
Last Save by: KNL  
Last Saved: 3/12/2019  
Plotted on: 3/9/2020



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CROSS SECTIONS STA 0+00 TO STA 1+50			
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____ AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.

G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Grading Sections 2.DWG  
Last Save by: KNL  
Last Saved: 3/12/2019  
Plotted on: 3/9/2020






REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CROSS SECTIONS STA 2+00 TO STA 2+50			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.



Last Save by: KNL  
Last Saved: 3/12/2019  
Plotted on: 3/9/2020





G:\DHHL11-02 Laiopua Village  
4\ACAD\DHHL1102-Grading Sections 3.DWG



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CROSS SECTIONS STA 3+00 TO STA 3+50			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.

Last Save by: KNL  
Last Saved: 3/12/2019  
Plotted on: 3/9/2020

G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Grading Sections 4.DWG







REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CROSS SECTIONS STA 4+00 TO STA 5+50			
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.













Last Save by: LRS  
Last Saved: 6/5/2019  
Plotted on: 3/9/2020

G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Grading Sections 5.DWG



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CROSS SECTIONS STA 6+00 TO STA 7+50			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.

G:\DHHL11-02 Laipua Village  
4\ACAD\DHHL1102-Grading Sections 6.DWG  
Last Save by: LRS  
Last Saved: 6/5/2019  
Plotted on: 3/9/2020



THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/22

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
CROSS SECTIONS STA 8+00 TO STA 11+50			
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____ AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.



GENERAL:

- A. WORKMANSHIP AND MATERIALS SHALL CONFORM TO THE BUILDING CODE OF THE COUNTY OF HAWAII (AMENDED IBC, 2006 EDITION). HOWEVER, WHERE REFERENCE IS MADE TO PERFORMANCE CONFORMING TO OTHER STANDARDS THE MORE STRINGENT SHALL APPLY.
- B. THE CONTRACTOR SHALL COMPARE ALL THE CONTRACT DOCUMENTS WITH EACH OTHER AND REPORT IN WRITING TO THE ENGINEER ALL INCONSISTENCIES AND OMISSIONS.
- C. THE CONTRACTOR SHALL TAKE FIELD MEASUREMENTS AND VERIFY FIELD CONDITIONS AND SHALL COMPARE SUCH FIELD MEASUREMENTS AND CONDITIONS WITH THE DRAWINGS BEFORE COMMENCING WORK. REPORT IN WRITING TO THE ENGINEER ALL INCONSISTENCIES AND OMISSIONS.
- D. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE WORK OF ALL TRADES.
- E. THE CONTRACTOR SHALL BE RESPONSIBLE FOR METHODS OF CONSTRUCTION, WORKMANSHIP AND JOB SAFETY. THE CONTRACTOR SHALL PROVIDE TEMPORARY SHORING AND BRACING AS REQUIRED FOR STABILITY OF STRUCTURAL MEMBERS AND SYSTEMS.
- F. CONSTRUCTION LOADING SHALL NOT EXCEED DESIGN LIVE LOAD UNLESS SPECIAL SHORING IS PROVIDED. ALLOWABLE LOADS SHALL BE REDUCED IN AREAS WHERE THE STRUCTURE HAS NOT ATTAINED FULL DESIGN STRENGTH.
- G. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTION OF THE ADJACENT PROPERTIES, STRUCTURES, STREETS AND UTILITIES DURING THE CONSTRUCTION PERIOD.
- H. DETAILS NOTED AS TYPICAL ON THE STRUCTURAL DRAWINGS SHALL APPLY IN ALL CONDITIONS UNLESS SPECIFICALLY SHOWN OR NOTED.

DESIGN CRITERIA:

- A. BASIC WIND SPEED AND EXPOSURE \_\_\_\_\_ 105 MPH, EXPOSURE C
- B. ALLOWABLE FOUNDATION BEARING CAPACITIES
- a. DEAD LOAD + LIVE LOAD \_\_\_\_\_ 3,000 PSF
- b. DEAD LOAD + LIVE LOAD + WIND OR SEISMIC \_\_\_\_\_ 4,000 PSF

FOUNDATION:

- A. CONTRACTOR SHALL PROVIDE FOR DE-WATERING OF EXCAVATION FROM SURFACE WATER, GROUND WATER OR SEEPAGE, AND OBTAIN NPDES PERMIT, IF REQUIRED.
- B. CONTRACTOR SHALL PROVIDE FOR DESIGN AND INSTALLATION OF ALL CRIBBING, SHEETING, AND SHORING NECESSARY TO PRESERVE EXCAVATIONS AND EARTH BANKS.
- C. FOOTINGS SHALL BEAR ON UNDISTURBED IN-SITU FIRM SOILS. BOTTOM OF FOOTINGS SHALL BE COMPACTED TO PROVIDE A RELATIVELY FIRM AND SMOOTH BEARING SURFACE PRIOR TO PLACEMENT OF REINFORCING STEEL AND CONCRETE. IF SOFT AND/OR LOOSE MATERIALS ARE ENCOUNTERED AT THE BOTTOM OF FOOTING EXCAVATIONS, THEY SHALL BE OVER-EXCAVATED TO EXPOSE THE UNDERLYING FIRM MATERIALS. THE OVER-EXCAVATED AREAS SHALL BE BACKFILLED WITH SELECT GRANULAR MATERIAL COMPACTED TO A MINIMUM OF 95% RELATIVE COMPACTION OR THE FOOTING BOTTOM MAY BE EXTENDED DOWN TO THE UNDERLYING COMPETENT MATERIAL.

CONCRETE:

- A. CONCRETE CONSTRUCTION SHALL CONFORM TO AMERICAN CONCRETE INSTITUTE ACI 318.
- B. CONCRETE SHALL BE REGULAR WEIGHT HARD ROCK CONCRETE AND SHALL HAVE THE FOLLOWING MINIMUM 28 DAY COMPRESSIVE STRENGTHS:
- a. FOOTINGS \_\_\_\_\_ 4,000 PSI
- b. FENCE POST FOOTING \_\_\_\_\_ 3,000 PSI
- c. CATCH BASIN \_\_\_\_\_ 4,000 PSI
- d. P/C DRYWELL \_\_\_\_\_ SEE CIVIL DWGS
- e. WALL \_\_\_\_\_ 4,000 PSI
- f. ALL OTHER CONCRETE \_\_\_\_\_ 3,000 PSI
- C. CONCRETE DELIVERY TICKETS SHALL RECORD ALL FREE WATER IN THE MIX: AT BATCHING BY PLANT, FOR CONSISTENCY BY DRIVER, AND ANY ADDITIONAL REQUEST BY CONTRACTOR IF PERMITTED BY THE MIX DESIGN.
- D. ALL INSERTS, ANCHOR BOLTS, PLATES, AND OTHER ITEMS TO BE CAST IN THE CONCRETE SHALL BE HOT-DIPPED GALVANIZED ACCORDING TO ASTM A153 UNLESS OTHERWISE NOTED.
- E. REINFORCING BARS, ANCHOR BOLTS, INSERTS, AND OTHER ITEMS TO BE CAST IN THE CONCRETE SHALL BE SECURED IN POSITION PRIOR TO PLACEMENT OF CONCRETE.
- F. CONDUITS, PIPES, AND SLEEVES PASSING THROUGH A SLAB OR FOOTING AND NOT CONFORMING TO TYPICAL DETAILS SHALL BE LOCATED AND SUBMITTED TO THE ENGINEER FOR APPROVAL.

CONCRETE (CONT):

- G. CONDUITS, PIPES, AND SLEEVES EMBEDDED WITHIN A SLAB OR WALL (OTHER THAN THOSE MERELY PASSING THROUGH) SHALL BE:
- a. NO LARGER IN OUTSIDE DIMENSIONS THAN ONE THIRD THE OVERALL SLAB OR WALL THICKNESS IN WHICH THEY ARE EMBEDDED.
- b. PLACED IN THE MIDDLE ONE THIRD OF SLAB OR WALL THICKNESS
- c. SPACED NO CLOSER THAN THREE DIAMETERS OR WIDTHS ON CENTER.
- H. THE CONTRACTOR SHALL LOCATE CONSTRUCTION JOINTS SO AS NOT TO IMPAIR THE STRENGTH OF THE STRUCTURE AND TO MINIMIZE SHRINKAGE STRESSES. SUBMIT LOCATION OF CONSTRUCTION JOINTS TO THE ENGINEER FOR APPROVAL, UNLESS OTHERWISE NOTED.
- I. NON-SHRINK GROUT SHALL BE A PREMIXED NON-METALLIC FORMULA, CAPABLE OF DEVELOPING A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI IN 1 DAY AND 5,000 PSI IN 28 DAYS.

REINFORCING STEEL:

- A. REINFORCING STEEL SHALL BE DEFORMED BARS CONFORMING TO ASTM A615, GRADE 60.
- B. CLEAR CONCRETE COVER FOR REINFORCING BARS SHALL BE AS FOLLOWS, UNLESS OTHERWISE NOTED:
- a. FOOTINGS, GRADE BEAMS, ETC. CAST AGAINST EARTH \_\_\_\_\_ 3"
- b. FOOTINGS, GRADE BEAMS, ETC. FORMED AND EXPOSED TO EARTH OR WEATHER \_\_\_\_\_ 2"
- c. BEAMS AND COLUMNS PRIMARY REINFORCEMENT, STIRRUPS, TIES AND SPIRALS \_\_\_\_\_ 1 1/2"
- C. REINFORCING STEEL SHALL BE SPLICED WHERE INDICATED ON PLANS. PROVIDE LAP SPLICE LENGTH PER TYPICAL DETAILS AND SCHEDULE, UNLESS OTHERWISE NOTED.
- D. MECHANICAL SPLICE CONNECTORS SHALL DEVELOP IN TENSION 125 PERCENT OF THE SPECIFIED MINIMUM YIELD STRENGTH OF REINFORCING BARS.

- E. BAR BENDS AND HOOKS SHALL BE "STANDARD HOOKS" IN ACCORDANCE WITH ACI 318.

STRUCTURAL STEEL:


- A. FABRICATION AND ERECTION OF STRUCTURAL STEEL SHALL CONFORM TO THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION MANUAL OF STEEL CONSTRUCTION, 14th EDITION.
- B. STRUCTURAL STEEL SHALL CONFORM TO ASTM A36 UNLESS OTHERWISE NOTED.
- C. STEEL TUBES (HSS) SHALL CONFORM TO ASTM A500, GRADE B
- D. PLATES AND BARS SHALL CONFORM TO ASTM A36.
- E. WELDS AND WELDING PROCEDURES SHALL CONFORM TO THE STRUCTURAL WELDING CODE AWS D1.1 OF THE AMERICAN WELDING SOCIETY.
- F. WELDING SHALL BE PERFORMED BY WELDERS PREQUALIFIED FOR WELDING PROCEDURES TO BE USED.
- G. WELDING ELECTRODES SHALL BE E70XX.
- H. ALL ANCHOR BOLTS, PLATES, AND OTHER ITEMS TO BE CAST IN CONCRETE SHALL BE HOT-DIP GALVANIZED ACCORDING TO ASTM A153 UNLESS OTHERWISE NOTED.
- I. BOLTS SHALL CONFORM TO ASTM A307, GRADE A UNLESS OTHERWISE NOTED, AND SHALL BE HOT-DIP GALVANIZED ACCORDING TO ASTM A153.
- K. ALL STEEL SHALL BE HOT-DIP GALVANIZED AFTER FABRICATION ACCORDING TO ASTM A123.

MINIMUM SPLICE AND DEVELOPMENT LENGTHS										
BAR SIZE	CONCRETE STRENGTH = 3,000 PSI					CONCRETE STRENGTH = 4,000 PSI				
	LAP SPLICE		DEVELOPMENT			LAP SPLICE		DEVELOPMENT		
	TOP BARS	OTHER BARS	STRAIGHT TOP BARS	OTHER BARS	WITH STANDARD HOOK	TOP BARS	OTHER BARS	STRAIGHT TOP BARS	OTHER BARS	WITH STANDARD HOOK
#3	28"	22"	22"	18"	10"	26"	20"	20"	16"	8"
#4	38"	30"	30"	22"	12"	34"	26"	26"	20"	10"
#5	48"	36"	36"	28"	14"	42"	32"	32"	24"	12"
#6	56"	44"	44"	34"	18"	50"	38"	38"	30"	16"
#7	82"	64"	64"	48"	20"	72"	54"	54"	42"	18"
#8	94"	72"	72"	56"	22"	82"	62"	62"	48"	20"
#9	106"	82"	82"	62"	26"	92"	70"	70"	54"	22"
#10	118"	92"	92"	70"	28"	102"	80"	80"	62"	26"
#11	132"	102"	102"	78"	32"	114"	88"	88"	68"	28"


NOTES:

1. LENGTHS ARE FOR CONCRETE WITH REBAR SPACED AT 6 BAR DIAMETERS MINIMUM. INCREASE LENGTHS BY 25% FOR BARS SPACED LESS THAN 6 BAR DIAMETERS.
2. "TOP BARS" ARE HORIZONTAL BARS WITH 12" OR MORE OF CONCRETE CAST BELOW.


D = 6d<sub>b</sub> FOR #8 AND SMALLER  
D = 8d<sub>b</sub> FOR #9 TO #11




90° BEND



135° BEND



180° BEND




BAR LAP

1

S-1

TYPICAL REBAR SPLICE AND DEVELOPMENT LENGTH SCHEDULE

NOT TO SCALE




ADDED REINFORCING AT PIPE OPENINGS

2

S-1

NOT TO SCALE




TYPICAL CONSTRUCTION JOINT DETAIL

3

S-1

NOT TO SCALE




TYPICAL CORNER BEND DETAIL

4

S-1

NOT TO SCALE




THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION  
LICENSE EXPIRES 4/30/20


REVISION	DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII				
GENERAL NOTES AND TYPICAL DETAILS				
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____				
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS				
FILE	POCKET	FOLDER	NO.	

S-1


SHEET 51 OF 68 SHEETS



1 PLAN - CATCH BASIN (MODIFIED TYPE A)  
SCALE: 1/2" = 1'-0"





2 TOP SLAB REINFORCEMENT LAYOUT  
SCALE: 1/2" = 1'-0"



3 SECTION  
SCALE: 1/2" = 1'-0"


- NOTES:
- REFERENCE CIVIL DRAWINGS FOR THE ELEVATION OF CATCH BASINS, AND LOCATIONS, NUMBER AND SIZE OF PIPES. OPENING OF OUTLET PIPE SHALL BE ROUNDED WITH MINIMUM RADIUS OF 0.15 TIMES PIPE DIAMETER.
  - PROVIDE 2 CUBIC FEET OF CRUSHED ROCK, ASTM SIZE #9 ROCK SAND AT WEEP HOLE.
  - CATCH BASIN FOOTING BASE SHALL BE COMPACTED TO A MINIMUM OF 95% RELATIVE DENSITY BEFORE CASTING FOOTING.



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
MODIFIED TYPE "A" CATCH BASIN			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			
FILE	POCKET	FOLDER	NO.







REVISION	DATE	DESCRIPTION	MADE BY APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 — HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
PRIVACY FENCE			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			DATE _____
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

FILE	POCKET	FOLDER	NO.

P:\1551-1600\1597.04 DHHL - Laiopua Villages 4 Retaining Wall\Drawings\Structural\AutoCAD\_format


Plotted on: 9/17/2019

Wall\Drawings\Struct

S-4.dwg



P:\1551-1600\1597.04 DHHL - Laiopua Villages 4 Retaining Wall\Drawings\Structural\AutoCAD\_format\2019-04-05\_1597-04\1597\_S-5.dwg  
Last Save by: BLUM  
Last Saved: 4/4/2019  
Plotted on: 9/17/2019



RETAINING WALL SCHEDULE																	
WALL HEIGHT "H"	WALL STEM					FOUNDATION					SHEAR KEY						
	"T <sub>T</sub> "	"T <sub>B</sub> "	"A" BARS	"B" BARS	"C" BARS	"B <sub>F</sub> "	"B <sub>T</sub> "	"T <sub>F</sub> "	"D" BARS	"E" BARS	"H <sub>K</sub> "	"T <sub>K</sub> "	"B <sub>K1</sub> "	"B <sub>K2</sub> "	"F" BARS	"G" BARS	"K" BARS
8'-1" ≤ 12'-0"	1'-0"	2'-0"	#4 AT 12"	#6 AT 6"	#6 AT 12"	12'-0"	6'-0"	2'-0"	#6 AT 12"	#4 AT 12"	3'-0"	1'-6"	7'-3"	3'-3"	#6 AT 12"	#4 AT 12"	#4 AT 12"
4'-1" ≤ 8'-0"	1'-0"	1'-6"	#4 AT 12"	#5 AT 6"	#5 AT 12"	8'-0"	4'-0"	1'-6"	#5 AT 12"	#4 AT 12"	2'-6"	1'-4"	3'-4"	3'-4"	#5 AT 12"	#4 AT 12"	#4 AT 12"
≤ 4'-0"	0'-8"	0'-10"	#4 AT 12"	#4 AT 12"	#4 AT 12"	4'-0"	2'-0"	1'-0"	#4 AT 12"	#4 AT 12"	2'-0"	1'-0"	1'-6"	1'-6"	#4 AT 12"	#4 AT 12"	#4 AT 12"


1

RETAINING WALL SECTION

S-5

SCALE: NTS


- NOTES:
- REFERENCE CIVIL DRAWINGS FOR LOCATIONS AND HEIGHTS OF RETAINING WALLS.
  - FOUNDATION OF RETAINING WALLS SHALL BE EMBEDDED A MINIMUM OF 6" INTO THE EXISTING INTACT BASALT ROCK. BOTTOM OF FOUNDATION EXCAVATION SHALL BE CLEANED OUT OF ALL LOOSE MATERIAL PRIOR TO PLACEMENT OF REINFORCEMENT OR CONCRETE.



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
RETAINING WALL (ALTERNATIVE ONE)			
Approved: _____			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
AKINAKA & ASSOCIATES, LTD. CONSULTING ENGINEERS			

FILE	POCKET	FOLDER	NO.

1. REFERENCE CIVIL DRAWINGS FOR LOCATIONS AND HEIGHTS OF RETAINING WALLS.
2. FOUNDATION OF RETAINING WALLS SHALL BE EMBEDDED A MINIMUM OF 6" INTO THE EXISTING INTACT BASALT ROCK. BOTTOM OF FOUNDATION EXCAVATION SHALL BE CLEANED OUT OF ALL LOOSE MATERIAL PRIOR TO PLACEMENT OF REINFORCEMENT OR CONCRETE.
3. EXCAVATION FOR THE WALL SHALL RESULT IN A VERTICAL OR NEAR-VERTICAL INTACT ROCK FACE. THE EXCAVATION WORK SHALL BE OBSERVED AND APPROVED BY A GEOTECHNICAL ENGINEER LICENSED IN THE STATE OF HAWAII.



KEN KAZUO HAYASHIDA

LICENSED  
PROFESSIONAL  
ENGINEER

No. 6818-S

HAWAII, U.S.A.

THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION  
AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY  
OBSERVATION  
LICENSE EXPIRES 4/30/20


FILE	POCKET	FOLDER	NO.




1. PROVIDE 5' MINIMUM CLEAR BETWEEN STREET LIGHT POLES & SEWER LATERALS.
2. PROVIDE 3' MINIMUM CLEAR BETWEEN PULLBOXES & SEWER LATERALS.
3. PROVIDE 6' MINIMUM CLEAR BETWEEN TRANSFORMER PADS & SEWER LATERALS (DO NOT STRADDLE).
4. PROVIDE 3' MINIMUM CLEAR BETWEEN DUCTLINES & SEWER LINES.
5. CONTRACTOR SHALL VERIFY SEWER LATERAL LOCATIONS WITH CIVIL SHEETS.
6. PROVIDE 8' MINIMUM HORIZONTAL CLEAR & 18" VERTICAL CLEAR BETWEEN WATER LINES & ALL ELECTRICAL SYSTEMS.
7. CONTRACTOR SHALL BE RESPONSIBLE TO ARRANGE WITH THE GENERAL CONTRACTOR TO IDENTIFY THE LOCATIONS OF CIVIL SITE UTILITIES, DRIVEWAYS, ETC. PRIOR TO ELECTRICAL CONTRACTORS LAYOUT OF ELECTRIC, TELEPHONE, STREET LIGHT, TRAFFIC SIGNAL, AND CATV SYSTEMS.

[illegible]

- a. THE LOCATION OF OVERHEAD AND UNDERGROUND FACILITIES SHOWN ON THE PLANS ARE FROM EXISTING RECORDS WITH VARYING DEGREES OF ACCURACY AND ARE NOT GUARANTEED AS SHOWN. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHENEVER CONSTRUCTION CROSSES OR IS IN PROXIMITY OF UNDERGROUND LINES AND SHALL MAINTAIN ADEQUATE CLEARANCE WHEN OPERATING EQUIPMENT UNDER ANY OVERHEAD LINES.
- b. THE CONTRACTOR IS TO COMPLY WITH THE DIRECTIONS OF THE STATE OF HAWAII OCCUPATIONAL SAFETY AND HEALTH LAW (HOSH).
- c. WHEN TRENCH EXCAVATION IS ADJACENT TO EXISTING STRUCTURES OR FACILITIES, THE CONTRACTOR IS REQUIRED TO PROPERLY SHEETING AND BRACING THE EXCAVATION AND STABILIZING THE EXISTING GROUND TO RENDER IT SAFE AND SECURE FROM POSSIBLE SLIDES, CAVE-INS AND SETTLEMENT, AND FOR PROPERLY SUPPORTING EXISTING STRUCTURES AND FACILITIES WITH BEAMS, STRUTS OR UNDERPINNING TO FULLY PROTECT IT FROM DAMAGE.
- d. AS REQUIRED BY THE COUNTY OF HAWAII, THE CONTRACTOR SHALL PROVIDE OFF-DUTY POLICE OFFICERS TO CONTROL THE FLOW OF TRAFFIC.
- e. WHERE PEDESTRIAN WALKWAYS EXIST, SUCH WALKWAYS SHALL BE MAINTAINED IN PASSABLE CONDITION OR OTHER FACILITIES FOR PEDESTRIANS SHALL BE PROVIDED. PASSAGE BETWEEN WALKWAYS AT INTERSECTIONS SHALL LIKEWISE BE PROVIDED.
- f. DRIVEWAYS SHALL BE KEPT OPEN UNLESS THE OWNERS OF THE PROPERTY USING THESE RIGHT-OF-WAYS ARE OTHERWISE PROVIDED FOR SATISFACTORILY.
- g. THE UNDERGROUND PIPES, CABLES OR DUCTLINES KNOWN BY THE ENGINEER TO EXIST FROM HIS SEARCH OF RECORDS ARE INDICATED ON THE PLANS. THE CONTRACTOR SHALL VERIFY THE LOCATION AND DEPTH OF THE FACILITIES AND EXERCISE PROPER CARE IN EXCAVATING THE AREA. WHEREVER CONNECTIONS OF NEW UTILITIES TO EXISTING UTILITIES ARE SHOWN ON THE PLANS, THE CONTRACTOR SHALL EXPOSE THE EXISTING LINES AT THE PROPOSED CONNECTIONS TO VERIFY THEIR LOCATIONS AND DEPTHS PRIOR TO EXCAVATION FOR THE NEW LINES.
- h. FOR CONSTRUCTION OF HELCO FACILITIES, CONTRACTOR TO REFER TO HELCO DRAWING \_\_\_\_-\_\_\_\_. CONTACT KELLY IKEDA AT HELCO (1-808-327-0515) FOR ANY QUESTIONS OR COMMENTS OF HELCO FACILITIES.

REVISION	DATE	DESCRIPTION	MADE BY
<p>DEPARTMENT OF HAWAIIAN HOME LANDS</p> <p>LA'IOPIUA VILLAGE 4 SUBDIVISION</p> <p>PHASE 2 - HEMA</p> <p>TAX MAP KEY: (3) 7-4-21:12 (PORTION)</p> <p>KAILUA-KONA, NORTH KONA, HAWAII</p>			
<p>SYMBOL LIST</p>			
<p>Approved: _____</p>			
<p>COUNTY ENGINEER, DPW, COUNTY OF HAWAII</p>			<p>DATE _____</p>
<p>          Ronald N.S. Ho &amp; Associates, Inc.          Electrical Engineers          2153 North King Street, Suite 201          Honolulu, Hawaii 96813       </p>			



FILE	POCKET	FOLDER	NO.



HAWAII ELECTRIC LIGHT COMPANY (HELCO) NOTES

1. LOCATION OF HELCO FACILITIES

THE LOCATION OF HELCO'S OVERHEAD AND UNDERGROUND FACILITIES SHOWN ON THE PLANS ARE FROM EXISTING RECORDS WITH VARYING DEGREES OF ACCURACY AND ARE NOT GUARANTEED AS SHOWN. THE CONTRACTOR SHALL VERIFY IN THE FIELD THE LOCATIONS OF THE FACILITIES AND SHALL EXERCISE PROPER CARE IN EXCAVATING AND WORKING IN THE AREA. WHEREVER CONNECTIONS OF NEW UTILITIES TO EXISTING UTILITIES AND UTILITY CROSSINGS ARE SHOWN, THE CONTRACTOR SHALL EXPOSE THE EXISTING LINES AT THE PROPOSED CONNECTIONS AND CROSSINGS TO VERIFY THE DEPTHS PRIOR TO EXCAVATION FOR THE NEW LINES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGES TO HELCO'S FACILITIES WHETHER SHOWN OR NOT SHOWN ON THE PLANS.

2. COMPLIANCE WITH HAWAII OCCUPATIONAL SAFETY AND HEALTH LAWS

THE CONTRACTOR SHALL COMPLY WITH THE STATE OF HAWAII'S OCCUPATIONAL SAFETY AND HEALTH LAWS AND REGULATIONS, INCLUDING WITHOUT LIMITATION, THOSE RELATED TO WORKING ON OR NEAR EXPOSED OR ENERGIZED ELECTRICAL LINES AND EQUIPMENT.

3. EXCAVATION PERMIT

THE CONTRACTOR SHALL OBTAIN AN EXCAVATION PERMIT FROM THE COUNTY TWO WEEKS PRIOR TO STARTING CONSTRUCTION. PLEASE REFER TO OUR REQUEST NUMBER AT THAT TIME.

4. CAUTION!!! ELECTRICAL HAZARD!!!

EXISTING HELCO OVERHEAD AND UNDERGROUND LINES ARE ENERGIZED AND WILL REMAIN ENERGIZED DURING CONSTRUCTION UNLESS PRIOR SPECIAL ARRANGEMENTS HAVE BEEN MADE WITH HELCO. ONLY HELCO PERSONNEL ARE TO HANDLE THESE ENERGIZED LINES AND ERECT TEMPORARY GUARDS TO PROTECT THESE LINES FROM DAMAGE. THE CONTRACTOR SHALL WORK CAUTIOUSLY AT ALL TIMES TO AVOID ACCIDENTS AND DAMAGE TO EXISTING HELCO FACILITIES, WHICH CAN RESULT IN ELECTROCUTION.

5. OVERHEAD LINES

STATE LAW REQUIRES THAT A WORKER AND THE LONGEST OBJECT HE OR SHE MAY CONTACT CANNOT COME CLOSER THAN A MINIMUM RADIAL CLEARANCE OF 10 FEET WHEN WORKING CLOSE TO OR UNDER ANY OVERHEAD LINES RATED 50KV AND BELOW. FOR EACH ADDITIONAL 1KV ABOVE 50KV, AN ADDITIONAL 0.4 INCH SHALL BE ADDED TO THE 10-FOOT CLEARANCE REQUIREMENT. THE PRECEDING INFORMATION ON LINE CLEARANCE REQUIREMENTS IS PROVIDED AS A CONVENIENCE AND IT IS THE CONTRACTOR'S RESPONSIBILITY TO BE INFORMED OF AND COMPLY WITH ANY REVISIONS OR AMENDMENTS TO THE LAW.

SHOULD THE CONTRACTOR ANTICIPATE THAT HIS WORK WILL RESULT IN THE NEED TO ENCROACH WITHIN THE MINIMUM REQUIRED CLEARANCE AT ANY TIME, THE CONTRACTOR SHALL NOTIFY HELCO AT LEAST FOUR (4) WEEKS PRIOR TO THE PLANNED ENCROACHMENT SO THAT, IF FEASIBLE, THE NECESSARY PROTECTIONS (E.G. RELOCATE, DE-ENERGIZE, OR BLANKET HELCO LINES) CAN BE PUT IN PLACE. HELCO'S COST OF SAFEGUARDING ITS LINES WILL BE CHARGED TO THE CONTRACTOR.

CONTACT HELCO'S CUSTOMER INSTALLATIONS DEPARTMENT AT 969-6666 FOR ASSISTANCE IN IDENTIFYING AND SAFEGUARDING OVERHEAD POWER LINES.

REFER TO SECTION X OF HELCO'S ELECTRIC SERVICE INSTALLATION MANUAL FOR ADDITIONAL GUIDELINES WHEN WORKING AROUND HELCO'S FACILITIES. A COPY MAY BE OBTAINED FROM HELCO'S CUSTOMER INSTALLATIONS DEPARTMENT.

6. POLE BRACING

A MINIMUM CLEARANCE OF 10 FEET MUST BE MAINTAINED WHEN EXCAVATING AROUND UTILITY POLES AND/OR THEIR ANCHOR SYSTEM TO PREVENT WEAKENING OR POLE SUPPORT FAILURE. SHOULD WORK REQUIRE EXCAVATING WITHIN 10 FEET OF A POLE AND/OR ITS ANCHOR SYSTEM, THE CONTRACTOR SHALL PROTECT, SUPPORT, SECURE, AND TAKE ALL OTHER PRECAUTIONS TO PREVENT DAMAGE TO OR LEANING OF THESE POLES. THE CONTRACTOR IS RESPONSIBLE FOR ALL ASSOCIATED COSTS TO BRACE, REPAIR, OR STRAIGHTEN POLES. ALL MEANS OF STRUCTURAL SUPPORT FOR THE POLE PROPOSED BY THE CONTRACTOR SHALL FIRST BE REVIEWED BY HELCO BEFORE IMPLEMENTATION. FOR POLE BRACING INSTRUCTIONS, THE CONTRACTOR SHALL CALL THE HELCO CONSTRUCTION AND MAINTENANCE DEPT., SUPERINTENDENT A MINIMUM OF TWO (2) WEEKS IN ADVANCE.

7. UNDERGROUND LINES

THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHENEVER CONSTRUCTION CROSSES OR IS IN CLOSE PROXIMITY OF UNDERGROUND LINES. HELCO'S EXISTING ELECTRICAL CABLES ARE ENERGIZED AND WILL REMAIN ENERGIZED DURING CONSTRUCTION. ONLY HELCO PERSONNEL ARE TO BREAK INTO EXISTING HELCO FACILITIES, HANDLE THESE CABLES, AND ERECT TEMPORARY GUARDS TO PROTECT THESE CABLES FROM DAMAGE. THE COST OF HELCO'S ASSISTANCE IN PROVIDING PROPER SUPPORT AND PROTECTION OF ITS UNDERGROUND LINES WILL BE CHARGED TO THE CONTRACTOR. SPECIAL PRECAUTIONS ARE REQUIRED WHEN EXCAVATING NEAR HELCO'S 62KV UNDERGROUND LINES (SEE HELCO INSTRUCTIONS TO CONSULTANTS/CONTRACTORS ON "EXCAVATION NEAR HELCO'S UNDERGROUND 62KV LINES" FOR DETAILED REQUIREMENTS).

FOR VERIFICATION OF UNDERGROUND LINES, THE CONTRACTOR SHALL CALL ONE-CALL A MINIMUM OF 72 HOURS IN ADVANCE.

FOR ASSISTANCE IN PROVIDING PROPER SUPPORT AND PROTECTION OF THESE LINES, THE CONTRACTOR SHALL CALL HELCO'S CONSTRUCTION & MAINTENANCE DEPT., SUPERINTENDENT, A MINIMUM OF TWO (2) WEEKS IN ADVANCE.

8. UNDERGROUND FUEL PIPELINES

THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHENEVER CONSTRUCTION CROSSES OR IS IN CLOSE PROXIMITY OF HELCO'S UNDERGROUND FUEL OIL PIPELINES. SPECIAL PRECAUTIONS ARE REQUIRED WHEN EXCAVATING NEAR HELCO'S UNDERGROUND FUEL OIL PIPELINES (SEE HELCO INSTRUCTIONS TO CONSULTANTS/CONTRACTORS ON "EXCAVATION NEAR HELCO'S UNDERGROUND FUEL PIPELINES" FOR DETAILED REQUIREMENTS).

9. EXCAVATIONS

WHEN TRENCH EXCAVATION IS ADJACENT TO OR BENEATH HELCO'S EXISTING STRUCTURES OR FACILITIES, THE CONTRACTOR IS RESPONSIBLE FOR:

SHEETING AND BRACING THE EXCAVATION AND STABILIZING THE EXISTING GROUND TO RENDER IT SAFE AND SECURE AND TO PREVENT POSSIBLE SLIDES, CAVE-INS, AND SETTLEMENTS.

PROPERLY SUPPORTING EXISTING STRUCTURES OR FACILITIES WITH BEAMS, STRUTS, OR UNDER-PINNINGS TO FULLY PROTECT IT FROM DAMAGE.

BACKFILLING WITH PROPER BACKFILL MATERIAL INCLUDING SPECIAL THERMAL BACKFILL WHERE EXISTING (REFER TO ENGINEERING DEPARTMENT FOR THERMAL BACKFILL SPECIFICATIONS).

10. RELOCATION OF HELCO FACILITIES

ANY WORK REQUIRED TO RELOCATE OR MODIFY HELCO FACILITIES SHALL BE DONE BY HELCO, OR BY THE CONTRACTOR UNDER HELCO'S SUPERVISION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL COORDINATION, AND SHALL PROVIDE NECESSARY SUPPORT FOR HELCO'S WORK, WHICH MAY INCLUDE, BUT NOT BE LIMITED TO, EXCAVATION AND BACKFILL, PERMITS AND TRAFFIC CONTROL, BARRICADING, AND RESTORATION OF PAVEMENT, SIDEWALKS, AND OTHER FACILITIES.

ALL COSTS ASSOCIATED WITH ANY RELOCATION OR MODIFICATION (EITHER TEMPORARY OR PERMANENT) FOR THE CONVENIENCE OF THE CONTRACTOR, OR TO ENABLE THE CONTRACTOR TO PERFORM HIS WORK IN A SAFE AND EXPEDITIOUS MANNER IN FULFILLING HIS CONTRACT OBLIGATIONS SHALL BE BORNE BY THE CONTRACTOR.

11. CONFLICTS

ANY REDESIGN OR RELOCATION OF HELCO'S FACILITIES NOT SHOWN ON THE PLANS MAY BE CAUSE FOR LENGTHY DELAYS. THE CONTRACTOR ACKNOWLEDGES THAT HELCO IS NOT RESPONSIBLE FOR ANY DELAY OR DAMAGE THAT MAY ARISE AS A RESULT OF ANY CONFLICTS DISCOVERED OR IDENTIFIED WITH RESPECT TO THE LOCATION OR CONSTRUCTION OF HELCO'S ELECTRICAL FACILITIES IN THE FIELD, REGARDLESS OF WHETHER THE CONTRACTOR HAS MET THE REQUESTED MINIMUM ADVANCE NOTICES. IN ORDER TO MINIMIZE ANY DELAY OR IMPACT ARISING FROM SUCH CONFLICTS, HELCO SHOULD BE NOTIFIED IMMEDIATELY UPON DISCOVERY OR IDENTIFICATION OF SUCH CONFLICT.

12. DAMAGE TO HELCO FACILITIES

THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL HELCO SURFACE AND SUBSURFACE UTILITIES AND SHALL BE RESPONSIBLE FOR ANY DAMAGES TO HELCO'S FACILITIES AS A RESULT OF HIS OPERATIONS. THE CONTRACTOR SHALL IMMEDIATELY REPORT SUCH DAMAGES TO HELCO'S TROUBLE DISPATCHER. REPAIR WORK SHALL BE DONE BY HELCO OR BY THE CONTRACTOR UNDER HELCO'S SUPERVISION. ALL COSTS FOR DAMAGES TO HELCO'S FACILITIES SHALL BE BORNE BY THE CONTRACTOR.

IN CASE OF DAMAGE OR SUSPECTED DAMAGE TO HELCO'S FUEL PIPELINE, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY HELCO'S TROUBLE DESK (969-6666) (A 24-HOUR NUMBER) SO HELCO PERSONNEL CAN SECURE THE DAMAGED SECTION AND REPORT ANY OIL SPILLS TO THE PROPER AUTHORITIES. ALL COSTS ASSOCIATED WITH THE DAMAGE, REPAIR, AND OIL SPILL CLEANUP SHALL BE BORNE BY THE CONTRACTOR.

13. HELCO STAND-BY PERSONNEL

THE CONTRACTOR MAY REQUEST HELCO TO PROVIDE AN INSPECTOR TO STAND-BY DURING CONSTRUCTION NEAR HELCO'S FACILITIES. THE COST OF SUCH INSPECTION WILL BE CHARGED TO THE CONTRACTOR. THE CONTRACTOR SHALL CALL THE HELCO CONSTRUCTION AND MAINTENANCE DEPT., SUPERINTENDENT A MINIMUM OF 5 WORKING DAYS IN ADVANCE TO ARRANGE FOR HELCO STAND-BY PERSONNEL.

14. CLEARANCES

THE FOLLOWING CLEARANCES SHALL BE MAINTAINED BETWEEN HELCO'S DUCTLINE AND ALL ADJACENT STRUCTURES (CHARTED AND UNCHARTED) IN THE TRENCH:

STRUCTURE TYPE	MINIMUM CLEARANCE(INCHES)
WATER LINES, PARALLEL	36 (A)
WATER LINES, CROSSING	12 (B)
SEWER LINES, PARALLEL	36 (C)
SEWER LINES, CROSSING	24 (D)
DRAIN LINES, PARALLEL	12
DRAIN LINES, CROSSING	6 (E)
ELECTRICAL AND GAS LINES, PARALLEL	12
ELECTRICAL AND GAS LINES, CROSSING	12
TELEPHONE LINES, PARALLEL	6 (E)
TELEPHONE LINES, CROSSING	6 (E)
CHEVRON OIL LINES, PARALLEL	36
CHEVRON OIL LINES, CROSSING	48 BELOW OIL LINE (F)

- A. THE MINIMUM HORIZONTAL CLEARANCES TO WATER LINES PARALLEL TO ELECTRICAL DUCTLINES MUST BE INCREASED TO 60 INCHES IF THE WATER LINE IS GREATER THAN 16 INCHES IN DIAMETER
- B. THE MINIMUM VERTICAL CLEARANCES TO WATER LINES CROSSING ELECTRICAL DUCTLINES CAN BE REDUCED TO 6 INCHES IF THE ELECTRICAL DUCTLINE STRUCTURE IS CONCRETE ENCASED AND IS BELOW THE WATER LINE AND THE WATER LINE IS LESS THAN 16 INCHES IN DIAMETER.
- C. A MINIMUM HORIZONTAL CLEARANCE OF 36 INCHES IS REQUIRED BETWEEN NEW HANDHOLES AND EXISTING SEWER LATERALS.
- D. THE MINIMUM VERTICAL CLEARANCES TO SEWER PIPES CROSSING ELECTRICAL DUCTLINES CAN BE REDUCED TO 12 INCHES IF THE SEWER PIPE IS JACKETED IN CONCRETE.
- E. THE MINIMUM CLEARANCES SHALL BE INCREASED TO 12 INCHES IF THE ELECTRICAL DUCTLINE IS DIRECT BURIED.

- F. THE MINIMUM VERTICAL CLEARANCES TO OIL LINES CROSSING ELECTRICAL DUCTLINES CAN BE REDUCED TO 24 INCHES BELOW OIL LINES IF THE CROSSINGS ARE ENCASED IN 6 INCHES OF CONCRETE.
- G. THE CONTRACTOR SHALL NOTIFY THE CONSTRUCTION MANAGER & HELCO OF ANY HEAT SOURCES (POWER CABLE DUCT BANK, STEAMLINE, ETC.) ENCOUNTERED THAT ARE NOT PROPERLY IDENTIFIED ON THE DRAWING.

THE FOLLOWING CLEARANCE SHALL BE MAINTAINED BETWEEN HELCO'S FUEL OIL PIPELINES AND ALL ADJACENT STRUCTURES: 24-INCHES, PARALLEL OR CROSSING. THE MINIMUM CLEARANCE CAN BE REDUCED TO 12 INCHES (PARALLEL AND BELOW ONLY) IF THE STRUCTURE IS JACKETED IN CONCRETE.

15. INDEMNITY

THE CONTRACTOR SHALL INDEMNIFY, DEFEND AND HOLD HARMLESS HELCO FROM AND AGAINST ALL LOSSES, DAMAGES, CLAIMS, AND ACTIONS, INCLUDING BUT NOT LIMITED TO REASONABLE ATTORNEY'S FEES AND COSTS BASED UPON OR ARISING OUT OF DAMAGE TO PROPERTY OR INJURIES TO PERSONS, OR OTHER TORTIOUS ACTS CAUSED OR CONTRIBUTED TO BY CONTRACTOR OR ANYONE ACTING UNDER ITS DIRECTION OR CONTROL OR ON ITS BEHALF; PROVIDED CONTRACTOR'S INDEMNITY SHALL NOT BE APPLICABLE TO ANY LIABILITY BASED UPON THE SOLE NEGLIGENCE OF HELCO.

16. SCHEDULE

CONTRACTOR SHALL FURNISH HIS CONSTRUCTION SCHEDULE 22 WORKING DAYS PRIOR TO STARTING WORK ON HELCO FACILITIES. CONTRACTOR SHALL GIVE HELCO, IN WRITING 30 WORKING DAYS NOTICE TO PROCEED WITH HELCO'S PORTION OF WORK.

17. AUTHORITY

ALL CONSTRUCTION, RESTORATION WORK, AND INSPECTION SHALL BE SUBJECT TO WHICHEVER GOVERNMENTAL AGENCY HAS AUTHORITY OVER THE WORK.

18. SPECIFICATIONS CONSTRUCTION OF HELCO'S UNDERGROUND FACILITIES SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE LATEST REVISIONS OF HELCO SPECIFICATIONS CS7001, CS7003, CS7202, CS9301, AND CS9401 AND APPLICABLE HELCO STANDARDS.

19. CONSTRUCTION

CONTRACTOR SHALL FURNISH ALL LABOR, MATERIALS, EQUIPMENT, AND SERVICES TO PROPERLY PERFORM AND FULLY COMPLETE ALL WORK SHOWN ON THE CONTRACT, DRAWINGS, AND SPECIFICATIONS. ALL MATERIALS SHALL BE NEW AND MANUFACTURED IN THE UNITED STATES OF AMERICA. ALL MANHOLE, HANDHOLE, AND DUCTLINE INSTALLATIONS SHALL BE INSPECTED AND APPROVED BY HELCO PRIOR TO EXCAVATION AND PRIOR TO PLACING CONCRETE.

CONTRACTOR SHALL NOTIFY HELCO'S INSPECTION DIVISION AT 935-1171 AT LEAST 48 HOURS PRIOR TO PLACING CONCRETE. CONTRACTOR TO COORDINATE WORK TO BREAK INTO HELCO'S EXISTING ELECTRICAL FACILITIES WITH HELCO'S UNDERGROUND DIVISION AT 935-1171 AT LEAST 10 WORKING DAYS IN ADVANCE.

20. STAKEOUT

THE CONTRACTOR SHALL ARRANGE FOR TONEOUTS OF ALL UNDERGROUND FACILITIES AND SHALL STAKEOUT ALL PROPOSED HELCO FACILITIES WITHIN THE PROJECT AREA SO AS TO NOT CONFLICT WITH ANY UTILITY (EXISTING OR PROPOSED) AND ANY PROPOSED CONSTRUCTION OR IMPROVEMENT WORK FOR VERIFICATION BY HELCO BEFORE PROCEEDING WITH HELCO WORK.

21. DUCTLINES

ALL DUCTLINE INSTALLATIONS SHALL BE PVC SCHEDULE 40 ENCASED IN CONCRETE, UNLESS OTHERWISE NOTED. ALL COMPLETED DUCTLINES SHALL BE MANDREL TESTED BY THE CONTRACTOR IN THE PRESENCE OF HELCO'S INSPECTOR USING HELCO'S STANDARD PRACTICE. THE CONTRACTOR SHALL INSTALL A 1/8" POLYOLEFIN PULL LINE IN ALL COMPLETED DUCTLINES AFTER MANDREL TESTING IS COMPLETE.

22. JOINT POLE REMOVAL


THE LAST JOINT POLE OCCUPANT OFF THE POLES SHALL REMOVE THE POLES.

23. AS-BUILT PLANS

THE CONTRACTOR SHALL PROVIDE HELCO WITH TWO SETS OF AS-BUILT REPRODUCIBLE TRACINGS SHOWING THE OFFSETS, STATIONING, AND VERTICAL ELEVATION OF THE DUCT LINE(S) CONSTRUCTED.

APPROVED BY:

HAWAII ELECTRIC LIGHT COMPANY DATE



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
HELCO NOTES			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE			
Ronald N.S. Ho & Associates, Inc. Electrical Engineers 2101 North King Street, Suite 201 Honolulu, Hawaii 96819			

FILE	POCKET	FOLDER	NO.

SANDWICH ISLES COMMUNICATIONS' NOTES  
DECEMBER 9, 2016

GENERAL:

ALL WORK SHALL BE IN STRICT ACCORDANCE WITH SPECIFICATIONS AND REQUIREMENTS OF THE RURAL UTILITIES SERVICES (RUS) AND SANDWICH ISLES COMMUNICATIONS (SIC), WHICH COMPLIES WITH ALL APPLICABLE CITY, COUNTY, STATE AND FEDERAL REQUIREMENTS.

ALL MATERIALS USED MUST BE APPROVED AND (OR) ACCEPTED BY SANDWICH ISLES COMMUNICATIONS, INC.

CONTRACTOR MAY REFER TO THE RUS WEBSITE  
(HTTPS://WWW.RD.USDA.GOV/PUBLICATIONS/REGULATIONS-GUIDELINES) FOR REGULATIONS, BULLETINS, FORMS, ETC.

CONTACT THE HAWAII ONE CALL CENTER AT (866) 423-7287 FOR LOCATING EXISTING UNDERGROUND FACILITIES PRIOR TO BEGINNING ANY EXCAVATION.

THE CONTRACTOR SHALL PROCURE AND PAY FOR ALL LICENSES AND PERMITS AND SHALL GIVE ALL NOTICES NECESSARY FOR PROSECUTION OF THE WORK.

IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE WORK SCHEDULES WITH ALL UTILITY COMPANIES, COUNTY, OR STATE AGENCIES REQUIRED FOR THIS PROJECT. THIS IS TO INCLUDE COORDINATION OF ANY INSPECTION AND SPECIFICATIONS BY THOSE UTILITY COMPANIES, COUNTY, OR STATE AGENCIES.

THE CONTRACTOR SHALL VERIFY ALL CONDITIONS AND DIMENSIONS RELATING TO THIS PROJECT BEFORE COMMENCING THE REQUIRED WORK.

THE CONTRACTOR SHALL PROMPTLY NOTIFY THE ENGINEER OF ANY DISCREPANCIES AND/OR CONDITIONS WHICH WOULD PREVENT HIM FROM FULFILLING THE TERMS OF THIS CONTRACT.

ALL SIC PULLBOXES THAT THE CONTRACTOR ENTERS FOR INSTALLATION OF FACILITIES MUST BE CLEARED OF STANDING WATER AND DEBRIS. CONTRACTOR SHALL ORGANIZE EXISTING CABLE FACILITIES, TO INCLUDE ADDING CABLE RACKS AND TYING DOWN EXISTING CABLE, IN ORDER TO ACCOMMODATE NEW FACILITIES BEING PLACED. CLEANING AND ORGANIZING OF PULLBOXES SHALL BE DONE TO THE SATISFACTION OF THE PROJECT MANAGER.

THE CONTRACTOR SHALL SUBMIT AS-BUILT DRAWINGS TO THE OWNER AT COMPLETION OF THE PROJECT. AS-BUILT DRAWINGS REFER TO DOCUMENTS MAINTAINED AND ANNOTATED BY THE CONTRACTOR DURING CONSTRUCTION AND INCLUDE ANY CHANGES OR NEW INFORMATION FOUND OR ADDED THROUGHOUT CONSTRUCTION OF THE PROJECT.

CONDUITS:

- ALL UNDERGROUND PVC CONDUITS, SWEEPS, COUPLINGS, ADAPTERS AND BELL ENDS SHALL BE SCHEDULE 40, UNLESS OTHERWISE SPECIFIED.
- ALL HIGH DENSITY POLYETHYLENE CONDUITS SHALL BE SDR 11. TYPICAL 3-PACK UNIT INCLUDES THREE 1.5-INCH SDR 11 RATED CONDUITS IN THE COLORS OF BLACK, RED, AND ORANGE, UNLESS OTHERWISE SPECIFIED. ALL CONDUITS TO BE PRESSURE TESTED AT 120 PSI. FUSION SPLICING OF THE CONDUIT SHALL BE ACCEPTABLE ONLY WHEN PULLING JOINTS THROUGH BORES. ALL COUPLINGS SHALL BE DOUBLE E-LOC MANUFACTURED BY ETCO SPECIALTY PRODUCTS, INC.
- MAIN CONDUIT RUNS, EXCEPT RISER CONDUITS, SHALL BE CONSTRUCTED WITH MINIMUM 6-FOOT RADIUS CURVES, UNLESS OTHERWISE APPROVED BY THE PROJECT MANAGER.
- AFTER THE CONDUITS ARE INSTALLED, A ROUND SOLID MANDREL NOT LESS THAN 12-INCHES IN LENGTH AND HAVING A DIAMETER OF 1/4-INCH LESS THAN THE INSIDE DIAMETER OF THE CONDUIT SHALL BE PULLED THROUGH EACH CONDUIT. THE SIC PROJECT MANAGER SHALL BE PRESENT DURING ALL MANDREL TESTING. SUFFIXES LISTED IN RUS 515B FOR CONDUITS ARE APPLICABLE.
- INSTALL MULETAPE IN ALL PVC CONDUITS TWO (2) INCH DIAMETER AND LARGER. THE NEPTCO MULETAPE (OR APPROVED EQUAL) IS AVAILABLE IN 3,000FT., 6,500FT., AND 10,000FT. REELS FROM WESTINGHOUSE ELECTRIC SUPPLY COMPANY (WESCO), THE NEPTCO MULETAPE IS PRE-LUBRICATED AND PRINTED WITH SEQUENTIAL FOOTAGE MARKINGS. PVC CONDUITS WITH A DIAMETER OF 1.5-INCH OR LESS SHALL HAVE A POLY-LINE (P-LINE) INSTALLED. ALL DUCTS SHALL BE SEALED AFTER MULETAPE/P-LINE HAS BEEN INSTALLED, FOLLOWING THE SPECIFICATIONS BELOW.

- ALL CONDUITS AND DUCTS SHALL BE PROPERLY SEALED USING COMMSCOPE, JACKMOON DUCT SEALS, APPLICABLE BUSHING SLEEVES AND BLANK DUCT PLUGS. THE CONDUIT DIAMETER, INSIDE DIAMETER AND CABLE SIZE(S) SHALL BE TAKEN INTO CONSIDERATION WHEN ORDERING AND INSTALLING "JACKMOON" DUCT SEALS.

COMMSCOPE JACKMOON SEALS SHALL BE:  
2-INCH CONDUIT:                      TRIPLEX DUCT SEALS, SERIES 70  
3-INCH CONDUIT:                      TRIPLEX DUCT SEALS, SERIES 136  
3.5-INCH AND LARGER CONDUIT:      QUADPLEX DUCT SEALS, SERIES 136

ALL OTHER DUCTS SHALL HAVE COMMSCOPE, BLANK JACKMOON PLUGS TO KEEP THEM FREE OF WATER AND DEBRIS.

- CONDUIT STUBS FROM HANDHOLES TO INDIVIDUAL RESIDENTIAL LOTS SHALL BE SCHEDULE 40 PVC, 1-INCH DIAMETER AND EXTENDED 5-FEET BEYOND PROPERTY LINE. CAP AND SEAL END AND MARK LOCATIONS WITH ABOVE GROUND MARKER. CONDUITS WILL NOT BE LOCATED WITHIN THE DRIVEWAY AREA.
- ALL CONDUITS SHALL ENTER MANHOLES AT A 90 DEGREE ANGLE AND SHALL EXTEND INTO THE MANHOLE AS FOLLOWS: CONDUITS DESIGNATED FOR FIBER SHALL EXTEND 12-INCHES INTO THE MANHOLE. ALL OTHER CONDUITS SHALL BE FLUSH WITH THE INSIDE WALL AND INCLUDE BELL ENDS. ANY EXCEPTIONS SHALL ONLY BE PERMITTED WHEN SPECIFIED BY THE PROJECT MANAGER.
- ALL CONDUITS ENTERING MANHOLES OR HANDHOLES SHALL BE GROUTED BETWEEN THE CONDUITS AND SIDEWALL, INSIDE AND OUT. ALL CONDUITS WILL ENTER THE MANHOLES AND HANDHOLES ON THE PROPERTY SIDE AT ALL TIMES UNLESS OTHERWISE SPECIFIED BY THE PROJECT MANAGER.

- BACKFILL AND COMPACTION FOR DUCTLINE TRENCHES, MANHOLES AND HANDHOLES, SHALL BE IN ACCORDANCE WITH:

A.STATE HIGHWAY DEPARTMENT'S STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION WITH LATEST AMENDMENTS, IF CONSTRUCTION IS LOCATED UNDER A STATE STREET OR ROAD, OR LOCATED IN PRIVATE PROPERTY.

B.THE STANDARD SPECIFICATIONS FOR ROAD, BRIDGE AND PUBLIC WORKS CONSTRUCTION, DATED 1994, OF THE DEPARTMENT OF PUBLIC WORKS, CITY AND COUNTY OF HONOLULU, WITH LATEST AMENDMENTS; COUNTY OF KAUAI, MAUI, OR HAWAII, AS THE CASE MAY BE, IF CONSTRUCTION IS LOCATED UNDER COUNTY STREETS AND ROADS.

- BACKFILLING SHALL BE SUBJECT TO THE APPROVAL OF THE SIC PROJECT MANAGER, THE AUTHORIZED REPRESENTATIVE OF THE DEPARTMENT OF TRANSPORTATION, STATE OF HAWAII AND/OR DEPARTMENT OF PUBLIC WORKS, CITY AND COUNTY OF HONOLULU, COUNTY OF KAUAI, MAUI OR HAWAII, AS THE CASE MAY BE.
- A THIRD PARTY GEOTECHNICAL ENGINEER, LICENSED AND INSURED IN THE STATE OF HAWAII, MUST CERTIFY THAT THE EXCAVATED AREA MEETS THE GOVERNING AGENCIES AND/OR OWNERS STANDARDS FOR BACKFILL AND COMPACTION.
- EXCAVATED MATERIAL MAY BE REUSED AS BACKFILL, PROVIDING THAT IT CONFORMS TO REQUIREMENTS OF TYPE "A" AND TYPE "B" BACKFILL, AS REQUIRED WITHIN THE STANDARD SPECIFICATIONS. A WRITTEN SOILS REPORT OF CONFORMANCE BY A LICENSED THIRD PARTY GEOTECHNICAL ENGINEER IS NEEDED PRIOR TO BACKFILL USING THE EXCAVATED MATERIAL.

A.TYPE A BACKFILL IS DEFINED AS BEACH SAND, EARTH OR EARTH AND GRAVEL. MAXIMUM PARTICLE SIZE SHALL BE 1-INCH AND MIXTURE SHALL NOT CONTAIN MORE THAN 20% BY VOLUME OF ROCK PARTICLES.

B.TYPE B BACKFILL IS DEFINED AS BEACH SAND, EARTH OR EARTH AND GRAVEL. MAXIMUM PARTICLE SIZE SHALL BE 1/2-INCH AND MIXTURE SHALL NOT CONTAIN MORE THAN 20% BY VOLUME OF ROCK PARTICLES.

- ALL CONDUIT RUNS SHALL HAVE A 3-INCH NON-METALLIC WARNING TAPE PLACED 12-INCHES ABOVE THE CONDUIT RUN. THE TAPE SHALL READ "CAUTION BURIED FIBER OPTIC CABLE BELOW".

MANHOLES AND HANDHOLES:

- ALL MANHOLES SHALL HAVE HS20-44 TRAFFIC LOADING COVERS (UNLESS OTHERWISE NOTED). HANDHOLES SHALL HAVE 20K TRAFFIC LOAD RATED COVERS.
- ALL MANHOLE AND HANDHOLE COVERS SHALL HAVE COVER LOGO TO READ "SIC".
- ALL MANHOLE AND HANDHOLE COVER BOLTS SHALL BE STAINLESS STEEL 3/4-INCH PENTAHEAD, UNLESS OTHERWISE NOTED.
- ALL MANHOLES AND HANDHOLES ARE SPECIFIED AS FOLLOWS:

A.UM35 AND UM46 MANHOLE – CONSISTS OF A REINFORCED CONCRETE MANHOLE WITH CAST IRON LID AND RISERS (IF REQUIRED). ALL MANHOLES ARE UNDER MASTER PURCHASE AGREEMENT WITH HAWAII PRECAST, INC. LOCATED IN CAPTAIN COOK, HAWAII (808-326-7730).

B.UH35 AND UH46 HANDHOLE – CONSISTS OF A REINFORCED CONCRETE HANDHOLE WITH TRAFFIC RATED HINGED COVERS (UH35) OR SIX TRAFFIC RATED SLIP-NOT COVERS (UH46) AND RISERS (IF REQUIRED). ALL HANDHOLES ARE UNDER MASTER PURCHASE AGREEMENT WITH HAWAII PRECAST, INC. LOCATED IN CAPTAIN COOK, HAWAII (808-326-7730).

C.UHC30X48X33 HANDHOLE (PULLBOX) – CONSISTS OF A TWO-TIER ARMORCAST POLYMER CONCRETE BOX & COVER ASSEMBLY. PART NUMBER (A6001430TA-SIC4).

D.UHC13X24X30 HANDHOLE (PULLBOX) – CONSISTS OF AN ARMORCAST POLYMER CONCRETE BOX & COVER ASSEMBLY. PART NUMBER (A6001946TA-SIC1).

- ALL MANHOLES AND HANDHOLES TO BE ORDERED WITH ALL HARDWARE, INCLUDING CABLE RACKS, STEPS AND LOCKS.
- SET MANHOLE OR HANDHOLE ON A LEVEL AREA, IN THE BOTTOM OF THE EXCAVATION, ON A 4-INCH LAYER OF CRUSHED ROCK, FOR DRAINAGE PURPOSES.
- THE BASE OF ALL MANHOLES AND HANDHOLES WILL BE PLACED LEVEL. SOME MANHOLES HAVE ADJUSTABLE FRAMES. ALL VOIDS CREATED DURING INSTALLATION MUST BE FILLED WITH MORTAR MIX OR CONCRETE. THIS IS ESPECIALLY TRUE FOR MANHOLES AND HANDHOLES SET IN ROADWAYS.
- BEFORE BACKFILLING AND COMPACTING, MAKE SURE COVERS ARE IN PLACE AND SECURE. LAYER 6-INCHES TO 8-INCHES OF BACKFILL MATERIAL AROUND THE MANHOLE OR HANDHOLE. TAMP EACH INDIVIDUAL LAYER OF BACKFILL MATERIAL. CONTINUE THE LAYERING AND "TAMPING" UNTIL FINAL GRADE IS ACHIEVED.
- THE TOPS OF ALL MANHOLES AND HANDHOLES SHALL BE FLUSH TO GRADE IN PAVED AREAS OR 1-INCH ABOVE FINISH GRADE IN NON-PAVED AREAS, UNLESS OTHERWISE SPECIFIED BY PROJECT MANAGER.
- PROVIDE A 5/8-INCH DIAMETER X 8-FOOT COPPER CLAD GROUND ROD AT HANDHOLES AND MANHOLES AS SPECIFIED ON THE DRAWINGS OR AS DIRECTED BY THE PROJECT MANAGER.
- FIELD MODIFICATIONS ARE ACCOMPLISHED BY USING A FINE TOOTHED SAW. RACKS OR OTHER EQUIPMENT MAY BE SECURED TO THE SIDE OF THE VAULT BY USE OF TOGGLE BOLTS, MOLLY BOLTS, ETC. AND MUST BE APPROVED BY THE PROJECT MANAGER.

UTILITY POLE INSTALLATION:

- ALL AERIAL WORK SHALL BE IN STRICT ACCORDANCE WITH SPECIFICATIONS AND REQUIREMENTS OF THE RURAL UTILITIES SERVICES (RUS) BULLETIN 1753F-152.
- UTILITY POLES SHALL BE PRESERVED UTILIZING THE PENTACHLOROPHENOL (PENTA) TYPE TREATMENT.
- UTILITY POLES SHALL BE TERMITE PROTECTED UTILIZING TERMIMESH POLESOCK'S OR EQUIVALENT. POLESOCK'S SHALL EXTEND NO MORE THAN EIGHT INCHES ABOVE GROUND AND BE SECURED WITH STAINLESS STRAPPING. FOLLOW THE MANUFACTURER'S RECOMMENDATIONS FOR INSTALLATION.
- THE POLE HOLE SHALL BE OF SUFFICIENT DIAMETER TO PERMIT THE POLE TO SETTLE FREELY TO THE BOTTOM OF THE HOLE WITHOUT TRIMMING THE BUTT AND STILL HAVE SUFFICIENT SPACE BETWEEN THE POLE AND THE SIDE OF THE HOLE TO PERMIT PROPER TAMPING OF THE BACKFILL AT EVERY POINT AROUND THE POLE, AND THROUGHOUT THE ENTIRE DEPTH OF THE HOLE.
- THE POLE HOLE SHALL NOT EXCEED TWO TIMES THE DIAMETER OF THE POLES BUTT DIAMETER.
- BACKFILL SHALL BE THOROUGHLY TAMPED THE FULL DEPTH OF THE POLE HOLE. EARTH MUST BE BANKED AROUND THE POLE TO A MINIMUM HEIGHT OF SIX INCHES ABOVE GROUND LEVEL.
- POLES SHALL BE SET PLUMB EXCEPT AT CORNERS WHERE THEY SHALL BE SET AND RAKED AGAINST THE LOAD SO THAT THE POLE TOP WILL BE IN LINE AFTER THE LOAD IS APPLIED. THE RAKE POLE SHALL NOT EXCEED SIX INCHES FOR EACH TEN FEET OF POLE LENGTH AFTER THE CONDUCTORS ARE INSTALLED AT THE REQUIRED TENSION. DEADEND SHALL BE SET SO AS TO BE PLUMB AND IN LINE AFTER THE LOAD IS APPLIED.
- POLE LIGHTNING PROTECTION SHALL BE A #6 AWG BARE COPPER WIRE IN ACCORDANCE WITH SIC/RUS CONSTRUCTION PRACTICES.
- SUSPENSION STRAND/HARDWARE SHALL BE CLASS C GALVANIZED STEEL UTILITY GRADE FOR CORROSION AREAS.
- GUY GUARDS, YELLOW IN COLOR SHALL BE PLACED ON ALL DOWN GUYS.

APPROVED BY:

SANDWICH ISLES COMMUNICATIONS, INC. DATE

RONALD N. S. HO & ASSOCIATES, INC.  
Electrical Engineers

★

GEORGE D. TAKASE  
LICENSED  
PROFESSIONAL  
ENGINEER  
No. 13741-E  
HAWAII, U. S. A.


★



THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION

04/30/22

EXPIRATION DATE OF THE LICENSE

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
<div>DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII</div>			
SIC NOTES			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII		DATE	
<div>Ronald N.S. Ho &amp; Associates, Inc. Electrical Engineers 2101 North King Street, Suite 201 Honolulu, Hawaii 96819</div>			



FILE	POCKET	FOLDER	NO.



2020-09-21 11:04 AM Z:\Acad\PROJECTS\211048\EDA\_211048-Site



**ELECTRICAL SITE PLAN**  
SCALE: 1"=100'




APPROVED BY:  
SANDWICH ISLES COMMUNICATIONS, INC. DATE

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'IOHUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII ELECTRICAL SITE PLAN			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE			
Ronald N.S. Ho & Associates, Inc. Electrical Engineers 2102 North King Street, Suite 201 Honolulu, Hawaii 96819			
FILE	POCKET	FOLDER	NO.





2020-03-11 1:46 PM Z:\Acad\PROJECTS\211046\EDG\_211046-DBA2



NOTE(S):

- 1 BASE BID: CONDUITS GOING ONTO KAWELU PLACE TO BE MARKED AND STUBBED
- 2 HELCO AND SIC BOXES AND CONDUITS AS INDICATED  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
- 3 1-3" HELCO CONDUIT, 2-1" SIC CONDUITS FOR PROPERTY STUB  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
- 4 2" LIGHTING CONDUIT  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
- 5 STREET LIGHTING HANDHOLE  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
- 6 STREET LIGHT STANDARD  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE

APPROVED BY:

SANDWICH ISLES COMMUNICATIONS, INC. DATE




ELECTRICAL DISTRIBUTION II

SCALE: 1"=40'




SCALE:  
GRAPHIC SCALE



REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII DISTRIBUTION PLAN II			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE			
Ronald N.S. Ho & Associates, Inc. 2102 North King Street, Suite 201 Honolulu, Hawaii 96819			
FILE	POCKET	FOLDER	NO.






- NOTE(S):
- 1 HELCO AND SIC BOXES AND CONDUITS AS INDICATED  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
  - 2 1-3" HELCO CONDUIT, 2-1" SIC CONDUITS FOR PROPERTY STUB  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
  - 3 2" LIGHTING CONDUIT  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
  - 4 STREET LIGHTING HANDHOLE  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
  - 5 STREET LIGHT STANDARD  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH  
ALTERNATE 3: INSTALLATION OF ELECTRICAL INFRASTRUCTURE
  - 6 KO'OKO'OLAU STREET - MODIFYING EXISTING ROADWAY  
BASE BID: BLASTING AND HAMMERING OF UTILITY TRENCH, INSTALLATION OF ELECTRICAL INFRASTRUCTURE  
ALTERNATE 3: REMOVAL OF THIS PORTION OF WORK FROM BID

APPROVED BY: \_\_\_\_\_  
SANDWICH ISLES COMMUNICATIONS, INC. DATE


RONALD N. S. HO & ASSOCIATES, INC.  
Electrical Engineers  
GEORGE D. TAKASE  
LICENSED PROFESSIONAL ENGINEER  
No. 13741-E  
HAWAII, U.S.A.  
THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION  
04/30/22  
EXPIRATION DATE OF THE LICENSE

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII DISTRIBUTION PLAN III			
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE			
Ronald N.S. Ho & Associates, Inc. 2152 North King Street, Suite 201 Honolulu, Hawaii 96819			
FILE	POCKET	FOLDER	NO.

**ELECTRICAL DISTRIBUTION III**  
SCALE: 1"=40'







- NOTES:
- ELECTRICAL WARNING TAPE—HEAVY GAUGE 4 MIL, RED WITH BLACK LETTERING, 3" WIDE, "BURIED ELECTRIC LINE BELOW—CAUTION" @ DIRECT BURIED CONDUITS.
  - "CAUTION" WARNING TAPE REQUIRED OVER ENTIRE LENGTH OF ALL CONDUITS.
  - 3" SEPARATION REQUIRED BETWEEN ELECTRICAL AND TELEPHONE CONDUITS WITHIN CONCRETE ENCASEMENT.
  - CONTRACTOR TO MAINTAIN MIN. 8" SEPERATION FROM DUCTLINE TO PROPERTY LINE/EASEMENT.
  - SEE DISTRIBUTION PLANS FOR DUCT QUANTITY.
  - CONTRACTOR TO CONSTRUCT HELCO FACILITIES PER HELCO DRAWING \_\_\_\_ SEE E-1, NOTES FOR CONSTRUCTION, NOTE H.


BACKFILL NOTES:

- TYPE "A" BACKFILL — EARTH & GRAVEL. ROCK SIZE TO BE 1" MAX & THE MIXTURE TO CONTAIN NOT MORE THAN 50% BY VOLUME OF ROCK PARTICLES. THE MATERIAL SHALL BE NONEXPANSIVE. 95% COMPACTION.
- TYPE "B" BACKFILL — EARTH & GRAVEL. MIXTURE MUST PASS A 1/2" MESH SCREEN & CONTAIN NOT MORE THAN 20% BY VOLUME OF ROCK PARTICLES. 95% COMPACTION.

- NOTE — IF NORMAL MATERIAL AT BOTTOM OF TRENCH IS NOT TYPE "B", AN ADDITIONAL 3" SHALL BE EXCAVATED & TYPE "B" BACKFILL PROVIDED.
- CONCRETE — 3" ENCASEMENT, 2500 PSI COMPRESSIVE STRENGTH @ 28 DAYS. CONCRETE FOR STREET LIGHT DUCTS TO HAVE 3000 PSI COMPRESSIVE STRENGTH AT 28 DAYS.


TYPICAL DUCT SECTIONS I  
NOT TO SCALE

APPROVED BY: \_\_\_\_\_ DATE \_\_\_\_\_  
SANDWICH ISLES COMMUNICATIONS, INC.




REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I'OPUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
TYPICAL DUCT SECTIONS I			
Approved: _____ COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE _____			
Ronald N.S. Ho & Associates, Inc. 2152 Kono Kono Street, Suite 201 Honolulu, Hawaii 96819			


FILE	POCKET	FOLDER	NO.
------	--------	--------	-----




SECTION (R)




SECTION (S)




SECTION (T)




SECTION (U)




SECTION (V)



SECTION (W)



DRAIN CROSSING VERTICAL CLEARANCE



WATER CROSSING VERTICAL CLEARANCE

## TYPICAL DUCT SECTIONS II

NOT TO SCALE

### CONDUIT SCHEDULE

ITEM	DESCRIPTION	ITEM	DESCRIPTION
(2E)	HAWAII ELECTRIC LIGHT CO. 1-2"C	(8-1S)	SANDWICH ISLES COMM UD(4x2-1")
(2-2E)	HAWAII ELECTRIC LIGHT CO. 2-2"C	(6-1S)	SANDWICH ISLES COMM UD(3x2-1")
(4-2E)	HAWAII ELECTRIC LIGHT CO. 4-2"C	(4-1S)	SANDWICH ISLES COMM UD(2x2-1")
(6-2E)	HAWAII ELECTRIC LIGHT CO. 6-2"C	(2-1S)	SANDWICH ISLES COMM UD(1x2-1")
(3E)	HAWAII ELECTRIC LIGHT CO. 1-3"C	(2-4S)	SANDWICH ISLES COMM UD(1x2-4")
(2-3E)	HAWAII ELECTRIC LIGHT CO. 2-3"C	(4-4S)	SANDWICH ISLES COMM UD(2x2-4")
(2-5E)	HAWAII ELECTRIC LIGHT CO. 2-5"C	(6-4S)	SANDWICH ISLES COMM UD(3x2-4")
		(1L)	STREET LIGHT 1-1"C
		(2-2L)	STREET LIGHT 2-2"C

3D view of a 17'x30' Quazite Tier 22 Street Light Pullbox. Dimensions: 30 1/2" (775 mm) x 17 1/2" (445 mm) x 18" (457 mm). Features: 3/8-16 UNC STAINLESS STEEL PENTA HEAD BOLT W/ WASHER (2), 1/2" (13 mm) X 4" (102 mm) PULL SLOT, 0.5 COF SKID RESISTANT SURFACE, 4" (102 mm) X 4" (102 mm) MOUSEHOLES (2) PG2436BB, 28 1/2" (724 mm) x 15 1/2" (394 mm) internal dimensions, 19 1/4" (489 mm) x 32 1/4" (819 mm) external dimensions, 8 3/4" (219 mm) height, 2" (51 mm) base width, 27" (686 mm) total height, 2" (51 mm) base width, 1" (25 mm) base width.

**NOTE(S):**

- ALL CONDUITS SHALL ENTER VERTICALLY AT THE BOTTOM OF THE PULLBOXES.
- ALL DIMENSIONS AND LINES ARE APPROXIMATE.
- FIELD ADJUST PULLBOX LOCATIONS AND CONDUIT CLEARANCES AS REQUIRED.
- CONDUIT 90° BEND RADII SHALL BE 18"-24" TO ALLOWABLE TRENCHING DEPTH
- PULLBOX COVERS SHALL BE LABELED "STREET LIGHTS"
- INSTALL GROUND RODS IN EACH PULLBOX.
- ALL PULLBOXES WILL BE QUAZITE TYPE, TIER 22 RATING.
- APPROVED EQUAL PULLBOX MAY BE SUBMITTED FOR APPROVAL.

APPROVED BY: \_\_\_\_\_

SANDWICH ISLES COMMUNICATIONS, INC. \_\_\_\_\_ DATE \_\_\_\_\_

REVISION DATE DESCRIPTION MADE BY APPROVED

DEPARTMENT OF HAWAIIAN HOME LANDS  
LA'IOPIUA VILLAGE 4 SUBDIVISION  
PHASE 2 - HEMA  
TAX MAP KEY: (3) 7-4-21:12 (PORTION)  
KAILUA-KONA, NORTH KONA, HAWAII

TYPICAL DUCT SECTIONS (CONT.)

Approved: \_\_\_\_\_  
COUNTY ENGINEER, DPW, COUNTY OF HAWAII DATE \_\_\_\_\_







RONALD N. S. HO & ASSOCIATES, INC.  
Electrical Engineers  
George D. Takase  
LICENSED PROFESSIONAL ENGINEER  
No. 13741-E  
HAWAII, U. S. A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION  
04/30/22  
EXPIRATION DATE OF THE LICENSE

FILE POCKET FOLDER NO.

## A 17"X30" QUAZITE TIER 22 - STREET LIGHT PULLBOX

NOT TO SCALE



- STREET LIGHT NOTES:**
- NO CHANGES WILL BE ALLOWED OR ACCEPTED AFTER THE APPROVAL OF THE FINAL STREET LIGHT DESIGN WITHOUT VALID JUSTIFICATION FROM THE ENGINEERING DESIGN FIRM AND WITH APPROVAL OF THE COUNTY OF HAWAII, DPW, TRAFFIC DIVISION.
  - ALL STREET LIGHT IDENTIFICATION TAG NUMBERING FOR METAL POLES SHALL START WITH "1" AND CONTINUE NUMERICALLY FOR EACH STREET IN THE SUBDIVISION. ALL NEW TAGS NUMERAL HEIGHT SHALL BE A MINIMUM OF 3". ALL STREET LIGHT I.D. TAG NUMBERING FOR WOODEN POLES SHALL BE IN ACCORDANCE WITH HELCO'S NUMBERING SYSTEM.
  - THE CONTRACTOR SHALL PROVIDE ALL NECESSARY SECONDARY CIRCUIT EXTENSIONS TO THE NEAREST HELCO SECONDARY. IF THE STREET LIGHTS ARE INSTALLED BEFORE HELCO INSTALLS THEIR SECONDARY, THE CONTRACTOR IS RESPONSIBLE FOR COORDINATION AND INFORMING HELCO OF STREET LIGHT LOCATIONS AND POLE CONTACTS.
  - THE DEVELOPER/CONTRACTOR SHALL INFORM AND COORDINATE WITH THE COUNTY TRAFFIC DIVISION, STREET LIGHT INSPECTOR FOR INSPECTIONS OF STREET LIGHT SYSTEM INSTALLATIONS NO LATER THAN 5 WORKING DAYS PRIOR TO AN ON-SITE VISIT.
  - FOR FINAL INSPECTION APPROVAL: ANY SUBDIVISION WITH TWO (2) OR MORE STREET LIGHTS, THE DEVELOPER SHALL SET UP ACCOUNT WITH HELCO; PROVIDING STREET NAME(S), POLE NUMBER(S), GPS COORDINATES, WATTAGE, AND BILLING ADDRESS TO ENERGIZE LIGHTS IN THE SUBDIVISION. A COPY OF THE STREET LIGHT INFORMATION SHALL ALSO BE PROVIDED TO THE COUNTY FOR INSPECTION PURPOSES. THE DEVELOPER WILL ALSO BE RESPONSIBLE FOR ENERGY COST UNTIL STREET(S) ARE DEDICATED TO COUNTY; WHERE UPON BILLING WILL BE TRANSFERED TO THE COUNTY.
  - THE CONTRACTOR SHALL INSCRIBE THE MONTH AND YEAR OF INSTALLATION ON PHOTOELECTRIC (PE) CELLS AND LAMPS. ALL PE'S SHALL HAVE THE NORTH INDEX FACING NORTH.
  - ALL MATERIALS AND LABOR SHALL BE WARRANTED FOR A MINIMUM OF ONE YEAR FROM DATE OF FINAL ACCEPTANCE.
  - ACCEPTABLE STREET LIGHT MATERIALS:
    - LED LUMINAIRES:  
E2 LIGHTING:  
E2-H150-ST-35W-7PD-SF, 35W  
(OR LATEST MODELS\APPROVED EQUAL)
    - PHOTOELECTRIC CELLS: COMPLETELY SOLID STATE, FAIL "ON"  
FISHER PIERCE: FP-7790B SPS
    - ALUMINUM POLES: INTERNAL MOUNTED VIBRATION DAMPER, MIN. 0.188 WALL THICKNESS. MUST BE F.H.W.A. APPROVED AND SHALL COMPLY WITH THE CURRENT AASHTO STREET LIGHTING STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS, LUMINAIRES, AND TRAFFIC STANDARDS. 12" POLE MOUNT-BASE BOLT PATTERN; ARM LENGTH SHALL BE PER PLAN.  
HAPCO SINGLE MAST ARM POLE PART#RTA30D8BFM1 (\*SEE NOTE)-GC  
\*NOTE: MAST ARM LENGTH PART#CODE; 8=8', A=10'  
HAPCO SINGLE TRUSS ARM POLE PART#RTA30C8BF1 (\*SEE NOTE)-GC  
\*NOTE: MAST ARM LENGTH CATALOG#CODES; C=12', E=15'  
FOR TRUSS ARM TYPE, REFERENCE HAPCO STYLE 85 TAPERED TRUSS-STYLE WITH ALUMINUM BRACKET MOUNTING; CATALOG#CODES: CPB85-007 = 12' TRUSS ARM; CPB85-011 = 15' TRUSS ARM
    - TRANSFORMER BASES: ALUMINUM WITH 14" BASE BOLT CIRCLE. MUST BE F.H.W.A APPROVED AND IN COMPLIANCE WITH THE 2001 AMENDED AND ADOPTED AASHTO BREAK AWAY SPECIFICATIONS.  
HAPCO - 70501 (TB1-17)  
VALMONT - M093 (TB1-17)
    - WOODEN POLES:  
SOUTHERN YELLOW PINE OR DOUGLAS FIR, CLASS III, PENTA TREATED AS PER AWPA USE CATEGORY SYSTEM UC4B, COMMODITY SPECIFICATION D, 35' LENGTH
    - WIRE: RHW-STRANDED-SIZE SHALL BE PER PLAN. WHITE TAPE DENOTING NEUTRAL SHALL BE A MINIMUM OF 12".
  - SUBMIT A SCALED DRAWING OF STREET LIGHT LOCATIONS (PREFERABLY ON ONE SHEET) AND DETAILS OF FIXTURE MOUNTING, LUMINAIRES TYPE, ARM LENGTH, IDENTIFICATION TAGS. FOR UNDERGROUND CIRCUITS, FOUNDATIONS, BASES AND POLES, DRAWINGS SHALL ALSO BE SUBMITTED TO THE TRAFFIC DIVISION AFTER PLAN APPROVAL AND BEFORE CONSTRUCTION BEGINS.
  - SHOP DRAWINGS SHALL BE SUBMITTED FOR ANY DEVIATIONS FROM THE ORIGINAL PLAN FOR APPROVAL BY THE TRAFFIC DIVISION.
  - UPON APPROVAL BY THE COUNTY OF HAWAII, TRAFFIC DIVISION, ANY STREET LIGHT(S) REQUIRED ON EXISTING POLE(S) MAY BE INSTALLED BY THE TRAFFIC DIVISION AT A COST OF \$2500.00 PER LIGHT. THE DEVELOPER SHALL THEN SUBMIT A CHECK, PAYABLE TO THE COUNTY DIRECTOR OF FINANCE ALONG WITH THE SUBDIVISION NUMBER, DPW FOLDER NUMBER, TAX KEY AND POLE NUMBER(S).
  - WHEN STREET LIGHT(S) ARE INSTALLED ON ROADWAYS THAT ARE UNDER STATE JURISDICTION, THE DEVELOPER SHALL SUBMIT PLANS TO THE STATE DOT FOR APPROVAL. THE COUNTRY OF HAWAII, TRAFFIC DIVISION WILL THEN INSTALL ON EXISTING POLE(S) WITH COST DEPENDENT ON HEIGHT OF POLE.
  - ALL OVERHEAD WIRING STREET LIGHT FIXTURES SHALL BE BONDED TO THE NEUTRAL WIRE IN THE FIXTURE. ALL BONDED STREET LIGHT FIXTURES SHALL HAVE A 2"x2" REFLECTIVE GREEN STICKER PLACED AT THE BASE OF WIRE OPENING ON THE ALUMINUM ARM, SIGNIFYING THAT THE STREET LIGHTS ARE BONDED.
  - ALL UNDERGROUND STREET LIGHT WIRING SHALL HAVE A #6 AWG (MINIMUM) GROUND WIRE ROUTED IN SERIES FROM THE NEUTRAL-GROUND SOURCE POINT TO EACH STREET LIGHT GROUND ROD FOR A STREET LIGHT FIXTURE GROUND POINT. A GROUND TEST MEASUREMENT SHOULD INDICATE A MAXIMUM OF 25 OHMS TO GROUND.
  - A MINIMUM 8' X 5/8" COPPER GROUND ROD SHALL BE USED FOR EACH STREET LIGHT FOUNDATION.
  - ALL WORK SHALL CONFORM TO THE LATEST NATIONAL ELECTRICAL CODE.

REVISION DATE	DESCRIPTION	MADE BY	APPROVED
DEPARTMENT OF HAWAIIAN HOME LANDS LA'I OPIUA VILLAGE 4 SUBDIVISION PHASE 2 - HEMA TAX MAP KEY: (3) 7-4-21:12 (PORTION) KAILUA-KONA, NORTH KONA, HAWAII			
STREET LIGHT DETAIL			
Approved:			
COUNTY ENGINEER, DPW, COUNTY OF HAWAII			
Ronald N.S. Ho & Associates, Inc. Electrical Engineers 2102 North King Street, Suite 201 Honolulu, Hawaii 96819			
EXPIRATION DATE OF THE LICENSE			

FILE	POCKET	FOLDER	NO.





